

# Solutions and Ideas

Product Catalog







## Dual. Modular. Unique.

True to the original: Weatherproof and robust, the latest successor to our successful M1 through M12 dual camera models features interchangeable sensor modules as well as the latest MOBOTIX system technology. The result is a product completely unrivaled in terms of performance, functionality and design.



M16 Body	M16 Day & Night	Description	Image Angle horizontal	Focal Length	Aperture
Mx-M16A		M16 Outdoor dual lens camera w/o sensor modules			
	Mx-M16A-6D6N036	D16 Outdoor dual dome camera day/night with 2 sensor modules B036 (103° x 77°)		3.6 mm	f/1.8
	Mx-M16A-6D6N041	D16 Outdoor dual dome camera day/night with 2 sensor modules B041 (90° x 67°)		4.1 mm	f/1.8
	Mx-M16A-6D6N061	D16 Outdoor dual dome camera day/night with 2 sensor modules B061 (60° x 45°)		6.1 mm	f/1.8
	Mx-M16A-6D6N079	D16 Outdoor dual dome camera day/night with 2 sensor modules B079 (45° x 34°)		7.9 mm	f/1.8
	Mx-M16A-6D6N119	D16 Outdoor dual dome camera day/night with 2 sensor modules B119 (31° x 23°)		11.9 mm	f/1.8
	Mx-M16A-6D6N237	D16 Outdoor dual dome camera day/night with 2 sensor modules B237 (15° x 11°)		23.7 mm	f/1.8

**M16 Body, For M16/M15 Sensor Modules (Day/Night)**Artikelno.: **Mx-M16A**

Mx6

**Description:**

M16 camera module for connecting one or two M16/m15 sensor modules (to be ordered individually) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Image sensor options (via sensor module): 5 or 6 megapixels, color (day) and/or B/W (night) • Lens options (via sensor module): horizontal image angle from 180° to 8° • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)

EAN:

**4047438027724**

HS:

**85258091**

Weight (incl. packaging):

**1.756 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0****M16 Complete Cam 6MP, 2x B041 (Day & Night)**Artikelno.: **Mx-M16A-6D6N041**

Mx6

**Description:**

IP camera set with two installed sensor modules • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B041 super wide-angle (f/1.8, horizontal image angle 90°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), USB; IO and RS232 via additional MX Interface Box

EAN:

**4047438027731**

HS:

**85258091**

Weight (incl. packaging):

**1.961 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0****M16 Complete Cam 6MP, 2x B079 (Day & Night)**Artikelno.: **Mx-M16A-6D6N079**

Mx6

**Description:**

IP camera set with two installed sensor modules • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B079 standard (f/1.8, horizontal image angle 45°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), USB; IO and RS232 via additional MX Interface Box

EAN:

**4047438027748**

HS:

**85258091**

Weight (incl. packaging):

**1.969 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**



## Supplementary Program (SUP)

The supplementary program encompasses other camera models which include complete sets that are pre-assembled and focus calibrated. This service takes approximately 5 business days. These products can also be ordered from the standard program as individual components for self-assembly.

### M16 Complete Cam 6MP, 2x B036 (Day & Night)

Artikelno.: **Mx-M16A-6D6N036**



Mx6

#### Description:

IP camera set with two installed sensor modules • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B036 ultra wide-angle (f/1.8, horizontal image angle 103°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), USB; IO and RS232 via additional MX Interface Box

EAN:

**4047438027755**

HS:

**85258091**

Weight (incl. packaging):

**2.400 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

### M16 Complete Cam 6MP, 2x B061 (Day & Night)

Artikelno.: **Mx-M16A-6D6N061**



Mx6

#### Description:

IP camera set with two installed sensor modules • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B061 wide-angle (f/1.8, horizontal image angle 60°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), USB; IO and RS232 via additional MX Interface Box

EAN:

**4047438027762**

HS:

**85258091**

Weight (incl. packaging):

**1.969 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

### M16 Complete Cam 6MP, 2x B119 (Day & Night)

Artikelno.: **Mx-M16A-6D6N119**



Mx6

#### Description:

IP camera set with two installed sensor modules • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B119 tele (f/1.8, horizontal image angle 31°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), USB; IO and RS232 via additional MX Interface Box

EAN:

**4047438027779**

HS:

**85258091**

Weight (incl. packaging):

**2.400 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

### M16 Complete Cam 6MP, 2x B237 (Day & Night)

Artikelno.: **Mx-M16A-6D6N237**



Mx6

#### Description:

IP camera set with two installed sensor modules • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x B237 distant tele (f/1.8, horizontal image angle 15°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), USB; IO and RS232 via additional MX Interface Box

EAN:

**4047438027786**

HS:

**85258091**

Weight (incl. packaging):

**2.400 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**





## One Camera. Two Views.

Two lenses, two HiRes image sensors, internal MicroSD storage and a dual image of over 12 megapixels make the D16 DualDome an efficient security solution: Two different areas can be secured with just one camera. All without fragile mechanical components!



D16 Body	D16 Day & Night	Description	Image Angle horizontal	Focal Length	Aperture
Mx-D16A		MD6 Outdoor dual dome camera w/o sensor modules			
	MX-D16A-F-6D6N036	D16 Outdoor dual dome camera day/night with 2 sensor modules B036 (103° x 77°)		3.6 mm	f/1.8
	MX-D16A-F-6D6N041	D16 Outdoor dual dome camera day/night with 2 sensor modules B041 (90° x 67°)		4.1 mm	f/1.8
	MX-D16A-F-6D6N061	D16 Outdoor dual dome camera day/night with 2 sensor modules B061 (60° x 45°)		6.1 mm	f/1.8
	MX-D16A-F-6D6N079	D16 Outdoor dual dome camera day/night with 2 sensor modules B079 (45° x 34°)		7.9 mm	f/1.8
	MX-D16A-F-6D6N119	D16 Outdoor dual dome camera day/night with 2 sensor modules B119 (31° x 23°)		11.9 mm	f/1.8
	MX-D16A-F-6D6N237	D16 Outdoor dual dome camera day/night with 2 sensor modules B237 (15° x 11°)		23.7 mm	f/1.8
	MX-D16A-P-6D6D041	D16 Outdoor dual dome camera day with 2 sensor modules B041 (90° x 67°)		4.1 mm	f/1.8
	MX-D16A-P-6N6N041	D16 Outdoor dual dome camera night with 2 sensor modules B041 (90° x 67°)		4.1 mm	f/1.8

## D16 Body, For D16/D15 Sensor Modules (Day/Night)

Artikelno.: **Mx-D16A**



Mx6

### Description:

IP camera module for connecting one or two D16/D15 sensor modules or a D16/D15 lens bridge FIX/PAN (to be ordered individually) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Image sensor options (via sensor module/bridge): 6 megapixels, color (day) and/or B/W (night) • Lens options (via lens unit): horizontal image angle from 103° to 15° • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • Operating conditions: IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, microphone, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.65 ft • Incl. 1x standard lens cover • Interfaces: Ethernet 10/100 (RJ45), USB; IO and RS232 via additional MX Interface Box

EAN:

**4047438027717**

HS:

**85258091**

Weight (incl. packaging):

**1.450 g**

Dimensions (l/w/h) in cm:

**39,5 / 29,6 / 9,0**

## Supplementary Program (SUP)

The supplementary program encompasses other camera models which include complete sets that are pre-assembled and focus calibrated. This service takes approximately 5 business days. These products can also be ordered from the standard program as individual components for self-assembly.

### D16 Complete Cam 6MP, 2x B036 (Day & Night)

Artikelno.: **Mx-D16A-F-6D6N036**



Mx6

#### Description:

IP camera with two parallel aligned lenses • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x B036 ultra wide-angle (f/1.8, horizontal image angle 103°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; IO and RS232 via additional MX-232-IO-Box

EAN:

**4047438028974**

HS:

**85258091**

Weight (incl. packaging):

**1.980 g**

Dimensions (l/w/h) in cm:

**39,5 / 29,6 / 18,0**

### D16 Complete Cam 6MP, 2x B041 (Day & Night)

Artikelno.: **Mx-D16A-F-6D6N041**



Mx6

#### Description:

IP camera with two parallel aligned lenses • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x B041 super wide-angle (f/1.8, horizontal image angle 90°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; IO and RS232 via additional MX-232-IO-Box

EAN:

**4047438028981**

HS:

**85258091**

Weight (incl. packaging):

**1.980 g**

Dimensions (l/w/h) in cm:

**39,5 / 29,6 / 18,0**

### D16 Complete Cam 6MP, 2x B061 (Day & Night)

Artikelno.: **Mx-D16A-F-6D6N061**



Mx6

#### Description:

IP camera with two parallel aligned lenses • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x B061 wide-angle (f/1.8, horizontal image angle 60°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; IO and RS232 via additional MX-232-IO-Box

EAN:

**4047438028998**

HS:

**85258091**

Weight (incl. packaging):

**1.980 g**

Dimensions (l/w/h) in cm:

**39,5 / 29,6 / 18,0**

### D16 Complete Cam 6MP, 2x B079 (Day & Night)

Artikelno.: **Mx-D16A-F-6D6N079**



Mx6

#### Description:

IP camera with two parallel aligned lenses • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x B079 wide-angle (f/1.8, horizontal image angle 45°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; IO and RS232 via additional MX-232-IO-Box

EAN:

**4047438029001**

HS:

**85258091**

Weight (incl. packaging):

**1.980 g**

Dimensions (l/w/h) in cm:

**39,5 / 29,6 / 18,0**

### D16 Complete Cam 6MP, 2x B119 (Day & Night)

Artikelno.: **Mx-D16A-F-6D6N119**



Mx6

#### Description:

IP camera with two parallel aligned lenses • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x B119 tele (f/1.8, horizontal image angle 31°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; IO and RS232 via additional MX-232-IO-Box

EAN:

**4047438029018**

HS:

**85258091**

Weight (incl. packaging):

**1.980 g**

Dimensions (l/w/h) in cm:

**39,5 / 29,6 / 18,0**

## D16 Complete Cam 6MP, 2x B237 (Day & Night)

Artikelno.: **Mx-D16A-F-6D6N237**



Mx6

### Description:

IP camera with two parallel aligned lens units • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x B237 tele (f/1.8, horizontal image angle 15°) • Equipment line: Secure • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10 + with Vandalism Set, each -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; IO and RS232 via additional MX -232-IO-Box

EAN:

**4047438029025**

HS:

**85258091**

Weight (incl. packaging):

**1.980 g**

Dimensions (l/w/h) in cm:

**39,5 / 29,6 / 18,0**

## D16 Complete Cam 2x 6MP, Panorama 180° (Day)

Artikelno.: **Mx-D16A-P-6D6D041**



Mx6

### Description:

IP camera with PAN lens bridge • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 2 Moonlight sensors day, 6MP (3072 x 2048) • HD premium lenses: 2x B041 super wide-angle (horiz. image angle 180°) • Max. image size: 2x 6MP (6144 x 2048 Pixel) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount, IP66/IK10+ with Vandalism Set, each -30 bis 60 °C (-22 to 140°F) • Internal DVR: 4 GB microSD • Speaker, microphone, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:

**4047438028950**

HS:

**85258091**

Weight (incl. packaging):

**1.980 g**

Dimensions (l/w/h) in cm:

**39,5 / 29,6 / 18,0**

## D16 Complete Cam 2x 6MP, Panorama 180° (Day)

Artikelno.: **Mx-D16A-P-6N6N041**



Mx6

### Description:

IP camera with PAN sensor bridge • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 2 Moonlight sensors night, 6MP (3072 x 2048) • HD premium lenses: 2x B041 super wide-angle (horiz. image angle 180°) • Max. image size: 2x 6MP (6144 x 2048 Pixel) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount, IP66/IK10+ with Vandalism Set, each -30 bis 60 °C (-22 to 140°F) • Internal DVR: 4 GB microSD • Speaker, microphone, PIR sensor, temperature sensor, MxActivitySensor, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:

**4047438028967**

HS:

**85258091**

Weight (incl. packaging):

**1.980 g**

Dimensions (l/w/h) in cm:

**39,5 / 29,6 / 18,0**



The S16 from MOBOTIX is a weatherproof system that stands out first and foremost for the extremely flexible installation options it offers. Two sensor modules are connected to the concealed camera housing via cables up to three meters long. This makes it possible to discreetly monitor two neighboring rooms with just a single camera.



S16 Body	S16 Day & Night	Description	Image Angle horizontal	Focal Length	Aperture
Mx-S16A		S16 Built-in dual lens camera w/o sensor modules			f/1.8 to f/2.5
	Mx-S16A-S1	S16 Set Built-in dual lens camera day with 1 sensor module B016 (180° x 180°)		1.6 mm	f/1.8
	Mx-S16A-S2	S16 Set Built-in dual lens camera day with 2 sensor modules B016 (180° x 180°)		1.6 mm	f/1.8
	Mx-S16A-S3	S16 Set Built-in dual lens camera day/night with 2 sensor modules B016 (180° x 180°)		1.6 mm	f/1.8

## S16 Body, For S16/S15 Sensor Modules (Day/Night/Thermal)

Artikelno.: **Mx-S16A**



Mx6

### Description:

S16 camera module (body) for connecting one or two S16/S15 sensor modules (to be ordered individually) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Image sensor options (via sensor module): 6 megapixels, color (day) and/or B/W (night) and/or thermal • Lens options (via optical sensor module): horizontal image angle from 180° to 8° • IP65, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: temperature sensor, MxActivitySensor, shock detector • ethernet patch cable 0.5 m/1.65 ft • Interfaces: 2x connection for MOBOTIX sensor module (Cam1/Cam2), Ethernet 10/100 (RJ45 and LSA), USB, Audio (I/O); RS232 via MX Interface Box

EAN:  
**4047438027885**

HS:  
**85258091**

Weight (incl. packaging):  
**660 g**

Dimensions (l/w/h) in cm:  
**19,6 / 14,8 / 9,0**

## S16 Complete Cam, Set 1, 6MP, 1x B016 (Day)

Artikelno.: **Mx-S16A-S1**



Mx6

### Description:

S16 camera module (body), Mx6 system platform with H.264, MxPEG and M-JPEG • 1x sensor module with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • 1x sensor cable 2 m/6.6 ft • 1x extension set • 1x ethernet patch cable 0.5 m/1.65 ft • 1x replacement dome • IP66 • Optional connection of a second sensor module (incl. Thermal)

EAN:  
**4047438027854**

HS:  
**85258091**

Weight (incl. packaging):  
**720 g**

Dimensions (l/w/h) in cm:  
**34,5 / 34,0 / 16,0**

## S16 Complete Cam, Set 2, 6MP, 2x B016 (Day)

Artikelno.: **Mx-S16A-S2**



Mx6

### Description:

S16 camera module (body), Mx6 system platform with H.264, MxPEG and M-JPEG • 2x sensor module with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • 2x sensor cable 2 m/6.6 ft • 2x extension set • 1x ethernet patch cable 0.5 m/1.65 ft • 2x replacement dome • IP66

EAN:  
**4047438027861**

HS:  
**85258091**

Weight (incl. packaging):  
**1.700 g**

Dimensions (l/w/h) in cm:  
**34,5 / 34,0 / 16,0**

## S16 Complete Cam, Set 3, 6MP, 2x B016 (Day & Night)

Artikelno.: **Mx-S16A-S3**



Mx6

### Description:

S16 camera module (body), Mx6 system platform with H.264, MxPEG and M-JPEG • 1x sensor module with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • 1x sensor module with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048) • 2x sensor cable 2 m/6.6 ft • 1x extension set • 1x ethernet patch cable 0.5 m/1.65 ft • 2x replacement dome • IP66

EAN:  
**4047438027878**

HS:  
**85258091**

Weight (incl. packaging):  
**1.700 g**

Dimensions (l/w/h) in cm:  
**34,5 / 34,0 / 16,0**





## For Corner Mounting. High-Security Dual Camera System.

The V16 models are the most robust of all MOBOTIX cameras and can withstand even the toughest attacks. Inside, they always feature the latest, multifunctional MOBOTIX dual camera technology with the option of connecting external devices and sensors.



D16 Day	D16 Day & Day	D16 Day & Night	D16 Night & Night	Description	Image Angle horizontal	Focal Length	Aperture
Mx-V16A-6D041				V16 Armored high-security dual lens camera day with 1 lens B041 (90° x 67°)		4.1 mm	f/1.8
Mx-V16A-6D079				V16 Armored high-security dual lens camera day with 1 lens B079 (45° x 34°)		7.9 mm	f/1.8
	Mx-V16A-6D6D041			V16 Armored high-security dual lens camera day with 2 lenses B041 (90° x 67°)		4.1 mm	f/1.8
	Mx-V16A-6D6D079			V16 Armored high-security dual lens camera day with 2 lenses B079 (45° x 34°)		7.9 mm	f/1.8
		Mx-V16A-6D6N041		V16 Armored high-security dual lens camera day/night with 2 lenses B041 (90° x 67°)		4.1 mm	f/1.8
		Mx-V16A-6D6N079		V16 Armored high-security dual lens camera day/night with 2 lenses B079 (45° x 34°)		7.9 mm	f/1.8
			Mx-V16A-6N6N041	V16 Armored high-security dual lens camera night with 2 lenses B041 (90° x 67°)		4.1 mm	f/1.8
			Mx-V16A-6N6N079	V16 Armored high-security dual lens camera night with 2 lenses B079 (45° x 34°)		7.9 mm	f/1.8

**V16 Complete Cam 6MP, 1x B041 (Day)**Artikelno.: **Mx-V16A-6D041**

Mx6

**Description:**

V16 Vandalism with one 6MP Moonlight sensor day (3072 x 2048), HD premium lens B041 (f/1.8, horiz. image angle 90°) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10++/IP65 • Functional range like S16 • HD Audio: Microphone and speaker integrated in the housing

EAN:

**4047438027892**

HS:

**85258091**

Weight ( incl. packaging):

**4.600 g**

Dimensions (l/w/h) in cm:

**26,0 / 26,0 / 26,0****V16 Complete Cam 6MP, B079 (Day)**Artikelno.: **Mx-V16A-6D079**

Mx6

**Description:**

V16 Vandalism with one 6MP Moonlight sensor day (3072 x 2048), HD premium lens B079 (f/1.8, horiz. image angle 45°) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10++/IP65 • Functional range like S16 • HD Audio: Microphone and speaker integrated in the housing

EAN:

**4047438027939**

HS:

**85258091**

Weight ( incl. packaging):

**4.600 g**

Dimensions (l/w/h) in cm:

**26,0 / 26,0 / 26,0****V16 Complete Cam 6MP, 2x B041 (Day)**Artikelno.: **Mx-V16A-6D6D041**

Mx6

**Description:**

V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x Color (day), two HD premium lenses B041 (f/1.8, horiz. image angle 90°) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10++/IP65 • Functional range like S16 • HD Audio: Microphone and speaker integrated in the housing

EAN:

**4047438027908**

HS:

**85258091**

Weight ( incl. packaging):

**4.700 g**

Dimensions (l/w/h) in cm:

**26,0 / 26,0 / 26,0****V16 Complete Cam 2x 6MP, 2x B079 (Day)**Artikelno.: **Mx-V16A-6D6D079**

Mx6

**Description:**

V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x color (day), two HD premium lenses B079 (f/1.8, horiz. image angle 45°) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10++/IP65 • Functional range like S16 • HD Audio: Microphone and speaker integrated in the housing

EAN:

**4047438027946**

HS:

**85258091**

Weight ( incl. packaging):

**4.700 g**

Dimensions (l/w/h) in cm:

**26,0 / 26,0 / 26,0****V16 Complete Cam 2x 6MP, 2x B041 (Day & Night)**Artikelno.: **Mx-V16A-6D6N041**

Mx6

**Description:**

V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 1x color (day), 1x B/W (night), two HD premium lenses B041 (f/1.8, horiz. image angle 90°) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10++/IP65 • Functional range like S16 • HD Audio: Microphone and speaker integrated in the housing

EAN:

**4047438027915**

HS:

**85258091**

Weight ( incl. packaging):

**4.700 g**

Dimensions (l/w/h) in cm:

**26,0 / 26,0 / 26,0****V16 Complete Cam 2x 6MP, 2x B079 (Day & Night)**Artikelno.: **Mx-V16A-6D6N079**

Mx6

**Description:**

V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 1x color (day), 1x B/W (night), two HD premium lenses B079 (f/1.8, horiz. image angle 45°) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10++/IP65 • Functional range like S16 • HD Audio: Microphone and speaker integrated in the housing

EAN:

**4047438027953**

HS:

**85258091**

Weight ( incl. packaging):

**4.700 g**

Dimensions (l/w/h) in cm:

**26,0 / 26,0 / 26,0**

## V16 Complete Cam 2x 6MP, 2x B041 (Night)

Artikelno.: **Mx-V16A-6N6N041**



Mx6

### Description:

V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x B/W (night), two HD premium lenses B041 (f/1.8, horiz. image angle 90°) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10++/IP65 • Functional range like S16 • HD Audio: Microphone and speaker integrated in the housing

EAN:

**4047438027922**

HS:

**85258091**

Weight ( incl. packaging):

**4.700 g**

Dimensions (l/w/h) in cm:

**26,0 / 26,0 / 26,0**

Outdoor Dual

## V16 Complete Cam 2x 6MP, 2x B079 (Night)

Artikelno.: **Mx-V16A-6N6N079**



Mx6

### Description:

V16 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x B/W (night), two HD premium lenses B079 (f/1.8, horiz. image angle 45°) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 3-5 mm stainless steel casing • IK10++/IP65 • Functional range like S16 • HD Audio: Microphone and speaker integrated in the housing

EAN:

**4047438027960**

HS:

**85258091**

Weight ( incl. packaging):

**4.700 g**

Dimensions (l/w/h) in cm:

**26,0 / 26,0 / 26,0**





## Solid. For Every Application.

Our proven all-purpose camera system for mounting on ceilings, walls and poles also easily meets the demanding requirements of protection classes IP66 and IK10. The M26 features the latest 6MP technology and can be used for an especially broad range of applications, thanks to the comprehensive choice of lenses available.

Outdoor Mono



M26 Body Day	M26 Body Night	M26 Day	M26 Night	Description	Image Angle horizontal	Focal Length	Aperture
Mx-M26A-6D	Mx-M26A-6N			M26 Outdoor Allround camera day/night w/o lens			
		Mx-M26A-6D016		M26 Outdoor Allround camera day with lens B016 (180° x 180°)		1.6 mm	f/1.8
			Mx-M26A-6N016	M26 Outdoor Allround camera night with lens B016 (180° x 180°)		1.6 mm	f/1.8
		Mx-M26A-6D036	Mx-M26A-6N036	M26 Outdoor Allround camera day/night with lens B036 (103° x 77°)		3.6 mm	f/1.8
		Mx-M26A-6D041	Mx-M26A-6N041	M26 Outdoor Allround camera day/night with lens B041 (90° x 67°)		4.1 mm	f/1.8
		Mx-M26A-6D061	Mx-M26A-6N061	M26 Outdoor Allround camera day/night with lens B061 (60° x 45°)		6.1 mm	f/1.8
		Mx-M26A-6D079	Mx-M26A-6N079	M26 Outdoor Allround camera day/night with lens B079 (45° x 34°)		7.9 mm	f/1.8
		Mx-M26A-6D119	Mx-M26A-6N119	M26 Outdoor Allround camera day/night with lens B119 (31° x 23°)		11.9 mm	f/1.8
		Mx-M26A-6D237	Mx-M26A-6N237	M26 Outdoor Allround camera day/night with lens B237 (15° x 11°)		23.7 mm	f/1.8
		Mx-M26A-6D500	Mx-M26A-6N500	M26 Outdoor Allround camera day/ night with lens B500 (8° x 6°)		50.0 mm	f/2.5

**M26 Body 6MP (Day)**Artikelno.: **Mx-M26A-6D**

Mx6

**Description:**

IP camera module (body) with 6 Megapixel Moonlight Sensor, color (day) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B500) • For mounting the Super Tele Lens MX-B500, the Extended Replacement Lens Cover is needed (MOBOTIX accessory: MX-M24M-OPT-LCGL) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

EAN:

**4047438027977**

HS:

**85258091**

Weight (incl. packaging):

**1.336 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0****M26 Complete Cam 6MP, B016 (Day)**Artikelno.: **Mx-M26A-6D016**

Mx6

**Description:**

Hemispheric IP camera with 6 Megapixel Moonlight Sensor, color (day) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

EAN:

**4047438027991**

HS:

**85258091**

Weight (incl. packaging):

**1.342 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0****M26 Body 6MP (Night)**Artikelno.: **Mx-M26A-6N**

Mx6

**Description:**

IP camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B500) • For mounting the Super Tele Lens B500, the Extended Replacement Lens Cover is needed (MOBOTIX accessory: MX-M24M-OPT-LCGL) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

EAN:

**4047438027984**

HS:

**85258091**

Weight (incl. packaging):

**2.000 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

## Supplementary Program (SUP)

The supplementary program encompasses other camera models which include complete sets that are pre-assembled and focus calibrated. This service takes approximately 5 business days. Many products of the supplemental program can be ordered from the standard program as individual components for self-assembly.

### M26 Complete Cam 6MP, B036 (Day)

Artikelno.: **Mx-M26A-6D036**



Mx6

#### Description:

IP camera with 6 Megapixel Moonlight Sensor, color (day) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Ultra Wide Lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

EAN:

**4047438028004**

HS:

**85258091**

Weight (incl. packaging):

**1.350 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

### M26 Complete Cam 6MP, B041 (Day)

Artikelno.: **Mx-M26A-6D041**



Mx6

#### Description:

IP camera with 6 Megapixel Moonlight Sensor, color (day) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Super Wide Lens B041 (focal length 4.1 mm, f/1.8, 90° x 67°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

EAN:

**4047438028011**

HS:

**85258091**

Weight (incl. packaging):

**1.349 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

### M26 Complete Cam 6MP, B061 (Day)

Artikelno.: **Mx-M26A-6D061**



Mx6

#### Description:

IP camera with 6 Megapixel Moonlight Sensor, color (day) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Wide Lens B061 (focal length 6.1 mm, f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

EAN:

**4047438028028**

HS:

**85258091**

Weight (incl. packaging):

**1.352 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

### M26 Complete Cam 6MP, B079 (Day)

Artikelno.: **Mx-M26A-6D079**



Mx6

#### Description:

IP camera with 6 Megapixel Moonlight Sensor, color (day) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Standard Lens B079 (focal length 7.9 mm, f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

EAN:

**4047438028035**

HS:

**85258091**

Weight (incl. packaging):

**2.000 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

### M26 Complete Cam 6MP, B119 (Day)

Artikelno.: **Mx-M26A-6D119**



Mx6

#### Description:

IP camera with 6 Megapixel Moonlight Sensor, color (day) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Tele Lens B119 (focal length 11.9 mm, f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

EAN:

**4047438028042**

HS:

**85258091**

Weight (incl. packaging):

**1.355 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

### M26 Complete Cam 6MP, B237 (Day)

Artikelno.: **Mx-M26A-6D237**



Mx6

#### Description:

IP camera with 6 Megapixel Moonlight Sensor, color (day) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Distant Tele Lens B237 (focal length 23.7 mm, f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

EAN:

**4047438028059**

HS:

**85258091**

Weight (incl. packaging):

**2.000 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

## M26 Complete Cam 6MP, B500 (Day)

Artikelno.: **Mx-M26A-6D500**



Mx6

### Description:

IP camera with 6 Megapixel Moonlight Sensor, color (day) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Super Tele Lens B500 (focal length 50 mm, f/2.5, 8° x 6°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

EAN:

**4047438028066**

HS:

**85258091**

Weight ( incl. packaging):

**2.000 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

## M26 Complete Cam 6MP, B016 (Night)

Artikelno.: **Mx-M26A-6N016**



Mx6

### Description:

Hemispheric IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

EAN:

**4047438028073**

HS:

**85258091**

Weight ( incl. packaging):

**2.000 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

## M26 Complete Cam 6MP, B036 (Night)

Artikelno.: **Mx-M26A-6N036**



Mx6

### Description:

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Ultra Wide Lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

EAN:

**4047438028080**

HS:

**85258091**

Weight ( incl. packaging):

**2.000 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

## M26 Complete Cam 6MP, B041 (Night)

Artikelno.: **Mx-M26A-6N041**



Mx6

### Description:

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Super Wide Lens B041 (focal length 4.1 mm, f/1.8, 90° x 67°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

EAN:

**4047438028097**

HS:

**85258091**

Weight ( incl. packaging):

**2.000 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

## M26 Complete Cam 6MP, B061 (Night)

Artikelno.: **Mx-M26A-6N061**



Mx6

### Description:

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Wide Lens B061 (focal length 6.1 mm, f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

EAN:

**4047438028103**

HS:

**85258091**

Weight ( incl. packaging):

**2.000 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

## M26 Complete Cam 6MP, B079 (Night)

Artikelno.: **Mx-M26A-6N079**



Mx6

### Description:

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Standard Lens B079 (focal length 7.9 mm, f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

EAN:

**4047438028110**

HS:

**85258091**

Weight ( incl. packaging):

**2.000 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**



## M26 Complete Cam 6MP, B119 (Night)

Artikelno.: **Mx-M26A-6N119**



Mx6

### Description:

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Tele Lens B119 (focal length 11.9 mm, f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

EAN:

**4047438028127**

HS:

**85258091**

Weight (incl. packaging):

**2.000 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

## M26 Complete Cam 6MP, B237 (Night)

Artikelno.: **Mx-M26A-6N237**



Mx6

### Description:

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Distant Tele Lens B237 (focal length 23.7 mm, f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

EAN:

**4047438028134**

HS:

**85258091**

Weight (incl. packaging):

**2.000 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

## M26 Complete Cam 6MP, B500 (Night)

Artikelno.: **Mx-M26A-6N500**



Mx6

### Description:

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Super Tele Lens B500 (focal length 50 mm, f/2.5, 8° x 6°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

EAN:

**4047438028141**

HS:

**85258091**

Weight (incl. packaging):

**2.000 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**






## Traditional Design. Innovative Technology.

Bringing unprecedented technology and video performance to a traditional-dome camera form factor. The MOBOTIX D26 offers the same advanced engineering and innovative technology of all the MOBOTIX cameras.

Outdoor Mono



D26 Body Day	D26 Body Night	D26 Day	D26 Night	Description	Image Angle horizontal	Focal Length	Aperture
Mx-D26A-6D	Mx-D26A-6N			D26 Outdoor dome camera day w/o lens			
		Mx-D26A-6D036	Mx-D26A-6N036	D26 Outdoor dome camera day or night with lens B036 (103° x 77°)		3.6 mm	f/1.8
		Mx-D26A-6D041	Mx-D26A-6N041	D26 Outdoor dome camera day or night with lens B041 (90° x 67°)		4.1 mm	f/1.8
		Mx-D26A-6D061	Mx-D26A-6N061	D26 Outdoor dome camera day or night with lens B061 (60° x 45°)		6.1 mm	f/1.8
		Mx-D26A-6D079	Mx-D26A-6N079	D26 Outdoor dome camera day or night with lens B079 (45° x 34°)		7.9 mm	f/1.8
		Mx-D26A-6D119	Mx-D26A-6N119	D26 Outdoor dome camera day or night with lens B119 (31° x 23°)		11.9 mm	f/1.8
		Mx-D26A-6D237	Mx-D26A-6N237	D26 Outdoor dome camera day or night with lens B237 (15° x 11°)		23.7 mm	f/1.8

**D26 Body 6MP (Day)**Artikelno.: **Mx-D26A-6D**

Mx6

**Description:**

D26 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) • Mx6 system platform with H.264, MxPEG+ and M-JPEG  
 • Lens to be ordered individually (B036 to B237) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal  
 DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Lens  
 cover with sealing ring (polycarbonate, 1.5 mm) • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-  
 OPT-RS1-EXT)

EAN:

**4047438028233**


HS:

**85258091**

Weight (incl. packaging):

**1.580 g**

Dimensions (l/w/h) in cm:

**19,6 / 18,0 / 14,8****D26 Body 6MP (Night)**Artikelno.: **Mx-D26A-6N**

Mx6

**Description:**

D26 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) • Mx6 system platform with H.264, MxPEG+ and M-JPEG  
 • Lens to be ordered individually (B036 to B237) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal  
 DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Lens  
 cover with sealing ring (polycarbonate, 1.5 mm) • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-  
 OPT-RS1-EXT)

EAN:

**4047438028240**

HS:

**85258091**

Weight (incl. packaging):

**1.580 g**

Dimensions (l/w/h) in cm:

**19,6 / 18,0 / 14,8**

## Supplementary Program (SUP)

The supplementary program encompasses other camera models which include complete sets that are pre-assembled and focus calibrated. This service takes approximately 5 business days. These products can also be ordered from the standard program as individual components for self-assembly.

### D26 Complete Cam 6MP, B036 (Day)

Artikelno.: **Mx-D26A-6D036**



Mx6

#### Description:

IP camera with 6 Megapixel Moonlight Sensor, color (day) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Ultra wide lens B036 (f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

EAN:

**4047438028257**

HS:

**85258091**

Weight (incl. packaging):

**1.580 g**

Dimensions (l/w/h) in cm:

**19,6 / 18,0 / 14,8**

### D26 Complete Cam 6MP, B041 (Day)

Artikelno.: **Mx-D26A-6D041**



Mx6

#### Description:

IP camera with 6 Megapixel Moonlight Sensor, color (day) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Super wide lens B041 (f/1.8, 90° x 67°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

EAN:

**4047438028264**

HS:

**85258091**

Weight (incl. packaging):

**1.580 g**

Dimensions (l/w/h) in cm:

**19,6 / 18,0 / 14,8**

### D26 Complete Cam 6MP, B061 (Day)

Artikelno.: **Mx-D26A-6D061**



Mx6

#### Description:

IP camera with 6 Megapixel Moonlight Sensor, color (day) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Wide lens B061 (f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

EAN:

**4047438028271**

HS:

**85258091**

Weight (incl. packaging):

**1.580 g**

Dimensions (l/w/h) in cm:

**19,6 / 18,0 / 14,8**

### D26 Complete Cam 6MP, B079 (Day)

Artikelno.: **Mx-D26A-6D079**



Mx6

#### Description:

IP camera with 6 Megapixel Moonlight Sensor, color (day) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Standard lens B079 (f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via Interface Box (MOBOTIX accessor)

EAN:

**4047438028288**

HS:

**85258091**

Weight (incl. packaging):

**1.580 g**

Dimensions (l/w/h) in cm:

**19,6 / 18,0 / 14,8**

### D26 Complete Cam 6MP, B119 (Day)

Artikelno.: **Mx-D26A-6D119**



Mx6

#### Description:

IP camera with 6 Megapixel Moonlight Sensor, color (day) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Tele lens B119 (f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

EAN:

**4047438028295**

HS:

**85258091**

Weight (incl. packaging):

**1.580 g**

Dimensions (l/w/h) in cm:

**19,6 / 18,0 / 14,8**

### D26 Complete Cam 6MP, B237 (Day)

Artikelno.: **Mx-D26A-6D237**



Mx6

#### Description:

IP camera with 6 Megapixel Moonlight Sensor, color (day) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Distance tele lens B237 (f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

EAN:

**4047438028301**

HS:

**85258091**

Weight (incl. packaging):

**1.580 g**

Dimensions (l/w/h) in cm:

**19,6 / 18,0 / 14,8**

## D26 Complete Cam 6MP, B036 (Night)

Artikelno.: **Mx-D26A-6N036**



Mx6

### Description:

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Mx6 system platform with H.264, MxPEG and M-JPEG • Ultra wide lens B036 (f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

EAN:

**4047438028318**

HS:

**85258091**

Weight ( incl. packaging):

**1.580 g**

Dimensions (l/w/h) in cm:

**19,6 / 18,0 / 14,8**

## D26 Complete Cam 6MP, B041 (Night)

Artikelno.: **Mx-D26A-6N041**



Mx6

### Description:

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Super wide lens B041 (f/1.8, 90° x 67°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

EAN:

**4047438028325**

HS:

**85258091**

Weight ( incl. packaging):

**1.580 g**

Dimensions (l/w/h) in cm:

**19,6 / 18,0 / 14,8**

## D26 Complete Cam 6MP, B061 (Night)

Artikelno.: **Mx-D26A-6N061**



Mx6

### Description:

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Wide lens B061 (f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

EAN:

**4047438028332**

HS:

**85258091**

Weight ( incl. packaging):

**1.580 g**

Dimensions (l/w/h) in cm:

**19,6 / 18,0 / 14,8**

## D26 Complete Cam 6MP, B079 (Night)

Artikelno.: **Mx-D26A-6N079**



Mx6

### Description:

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Standard lens B079 (f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

EAN:

**4047438028349**

HS:

**85258091**

Weight ( incl. packaging):

**1.580 g**

Dimensions (l/w/h) in cm:

**19,6 / 18,0 / 14,8**

## D26 Complete Cam 6MP, B119 (Night)

Artikelno.: **Mx-D26A-6N119**



Mx6

### Description:

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Tele lens B119 (f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

EAN:

**4047438028356**

HS:

**85258091**

Weight ( incl. packaging):

**1.580 g**

Dimensions (l/w/h) in cm:

**19,6 / 18,0 / 14,8**

## D26 Complete Cam 6MP, B237 (Night)

Artikelno.: **Mx-D26A-6N237**



Mx6

### Description:

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Distance tele lens B237 (f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP66/IK10, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

EAN:

**4047438028363**

HS:

**85258091**

Weight ( incl. packaging):

**1.580 g**

Dimensions (l/w/h) in cm:

**19,6 / 18,0 / 14,8**



## Allround Elegance. Allround Secure.

An elegant, ultra-compact and weatherproof dome camera. The Q26 uses a hemispheric B016 lens which is fixed and sharply focused at the factory. Thanks to its 360° allround view for capturing an entire room, a widescreen panorama function and intelligent video analysis tools, the Q26 can be used in countless scenarios.

Outdoor Mono



Q26 Day	Q26 Night	Description	Image Angle horizontal	Focal Length	Aperture
Mx-Q26A-6D016	Mx-Q26A-6N016	Q26 Outdoor overview camera day/night with lens B016 (180° x 180°)		1.6 mm	f/2.0

## Q26 Complete Cam 6MP, B016 (Day)

Artikelno.: **Mx-Q26A-6D016**



Mx6

### Description:

Hemispheric IP camera with 6 Megapixel Moonlight Sensor, color (day) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK06, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

EAN:

**4047438028219**

HS:

**85258091**

Weight (incl. packaging):

**1.630 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 9,0**

## Q26 Complete Cam 6MP, B016 (Night)

Artikelno.: **Mx-Q26A-6N016**



Mx6

### Description:

Hemispheric IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK06, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

EAN:

**4047438028226**

HS:

**85258091**

Weight (incl. packaging):

**1.630 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 9,0**





## Hard To See, But Sees Everything.

The compact S26 Flex is a universally deployable, concealable video system with highly detailed resolution. A miniature sensor module is integrated into the camera housing of the completely weatherproof IP camera. Thanks to the hemispheric lens, an entire area can be monitored without any blind spots.

Outdoor Mono



S26 Day	S26 Night	Description	Image Angle horizontal	Focal Length	Aperture
Mx-S26A-6D016	Mx-S26A-6N016	S26 Built-in dual lens camera day or night with lens B016 (180° x 180°)		1.6 mm	f/2.0

**S26 Complete Cam 6MP, B016 (Day)**Artikelno.: **Mx-S26A-6D016****Description:**

Hemispheric IP camera with 6 Megapixel Moonlight Sensor, color (day) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK07, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

EAN:

**4047438028370**

HS:

**85258091**

Weight (incl. packaging):

**712 g**

Dimensions (l/w/h) in cm:

**19,6 / 14,8 / 9,0****S26 Complete Cam 6MP, B016 (Night)**Artikelno.: **Mx-S26A-6N016****Description:**

Hemispheric IP camera with 6 Megapixel Moonlight Sensor, BW (night) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66/IK07, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • Temperature sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB; I/O and RS232 via MX-232-IO-Box (MX-OPT-RS1-EXT)

EAN:

**4047438028387**

HS:

**85258091**

Weight (incl. packaging):

**712 g**

Dimensions (l/w/h) in cm:

**19,6 / 14,8 / 9,0**





## M15 Body, For 1–2 Sensor Modules (Day/Night)

Artikelno.: **MX-M15D-Sec**



### Description:

M15 camera module for connecting one or two sensor modules (to be ordered individually) • Image sensor options (via sensor module): 5 or 6 megapixels, color (day) and/or B/W (night) • Lens options (via sensor module): horizontal image angle from 180° to 8° • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box • Incl. 1 Blind Module (MX-SM-Blind-PW)

EAN:

**4047438018258**

HS:

**85258091**

Weight (incl. packaging):

**1.703 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

## M15 Complete Cam 6MP, 2x B041 (Day & Night)

Artikelno.: **MX-M15D-Sec-DNight-D22N22-6MP-F1.8**



### Description:

IP camera set with two installed sensor modules • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x L22/B041 super wide-angle (f/1.8, horizontal image angle 90°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box

EAN:

**4047438023009**

HS:

**85258091**

Weight (incl. packaging):

**1.908 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

## M15 Complete Cam 6MP, 2x B079 (Day & Night)

Artikelno.: **MX-M15D-Sec-DNight-D43N43-6MP-F1.8**



### Description:

IP camera set with two installed sensor modules • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x L43/B079 standard (f/1.8, horizontal image angle 45°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box

EAN:

**4047438023023**

HS:

**85258091**

Weight (incl. packaging):

**1.908 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

## Supplementary Program (SUP)

The supplementary program encompasses other camera models which include complete sets that are pre-assembled and focus calibrated. This service takes approximately 5 business days. These products can also be ordered from the standard program as individual components for self-assembly.

### M15 Complete Cam 6MP, 2x B036 (Day & Night)

Artikelno.: **MX-M15D-Sec-DNight-D20N20-6MP-F1.8**



#### Description:

IP camera set with two installed sensor modules • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x L20/B036 ultra wide-angle (f/1.8, horizontal image angle 103°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box

EAN:

**4047438022996**

HS:

**85258091**

Weight (incl. packaging):

**1.917 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

### M15 Complete Cam 6MP, 2x B061 (Day & Night)

Artikelno.: **MX-M15D-Sec-DNight-D32N32-6MP-F1.8**



#### Description:

IP camera set with two installed sensor modules • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x L32/B061 wide-angle (f/1.8, horizontal image angle 60°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box

EAN:

**4047438023016**

HS:

**85258091**

Weight (incl. packaging):

**2.510 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

### M15 Complete Cam 6MP, 2x B119 (Day & Night)

Artikelno.: **MX-M15D-Sec-DNight-D65N65-6MP-F1.8**



#### Description:

IP camera set with two installed sensor modules • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x L65/B119 tele (f/1.8, horizontal image angle 31°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box

EAN:

**4047438023030**

HS:

**85258091**

Weight (incl. packaging):

**2.510 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

### M15 Complete Cam 6MP, 2x B237 (Day & Night)

Artikelno.: **MX-M15D-Sec-DNight-D135N135-6MP-F1.8**



#### Description:

IP camera set with two installed sensor modules • Image sensors (via sensor module): 1/1.8" CMOS, 6 megapixels, 1x day and 1x night • HD premium lenses (via sensor module): 2x L135/B237 tele (f/1.8, horizontal image angle 15°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • Camera components: speaker and microphone (inside housing), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box

EAN:

**4047438023047**

HS:

**85258091**

Weight (incl. packaging):

**2.510 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

## D15 Body, For D16/D15 Sensor Modules (Day/Night)

Artikelno.: **MX-D15Di-Sec**



### Description:

IP camera module for connecting one or two sensor modules or a sensor bridgeFIX/PAN (to be ordered individually) • Image sensor options (via lens unit/carrier): 6 megapixels, color (day) and/or B/W (night) • Lens options (via lens unit): horizontal image angle from 103° to 15° • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • Operating conditions: IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, microphone, PIR sensor, temperature sensor, shock detector, MxActivitySensor, ethernet patch cable 0.5 m/1.65 ft • Incl. Standard lens cover • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX Interface Box

EAN:

**4047438017978**

HS:

**85258091**

Weight (incl. packaging):

**1.980 g**

Dimensions (l/w/h) in cm:

**39,5 / 29,6 / 9,0**

## Supplementary Program (SUP)

The supplementary program encompasses other camera models which include complete sets that are pre-assembled and focus calibrated. This service takes approximately 5 business days. These products can also be ordered from the standard program as individual components for self-assembly.

### D15 Complete Cam 6MP, 2x B036 (Day & Night)

Artikelno.: **MX-D15Di-Sec-DNight-D20N20-FIX-6MP-F1.8**



#### Description:

IP camera with two parallel aligned lenses • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x L20/B036 ultra wide-angle (f/1.8, horizontal image angle 103°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box

EAN:

**4047438023238**

HS:

**85258091**

Weight (incl. packaging):

**1.980 g**

Dimensions (l/w/h) in cm:

**39,5 / 29,6 / 18,0**

### D15 Complete Cam 6MP, 2x B041 (Day & Night)

Artikelno.: **MX-D15Di-Sec-DNight-D22N22-FIX-6MP-F1.8**



#### Description:

IP camera with two parallel aligned lenses • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x L22/B041 super wide-angle (f/1.8, horizontal image angle 90°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box

EAN:

**4047438023245**

HS:

**85258091**

Weight (incl. packaging):

**1.980 g**

Dimensions (l/w/h) in cm:

**39,5 / 29,6 / 18,0**

### D15 Complete Cam 6MP, 2x B061 (Day & Night)

Artikelno.: **MX-D15Di-Sec-DNight-D32N32-FIX-6MP-F1.8**



#### Description:

IP camera with two parallel aligned lenses • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x L32/B061 wide-angle (f/1.8, horizontal image angle 60°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box

EAN:

**4047438023252**

HS:

**85258091**

Weight (incl. packaging):

**1.980 g**

Dimensions (l/w/h) in cm:

**39,5 / 29,6 / 18,0**

### D15 Complete Cam 6MP, 2x B079 (Day & Night)

Artikelno.: **MX-D15Di-Sec-DNight-D43N43-FIX-6MP-F1.8**



#### Description:

IP camera with two parallel aligned lenses • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x L43/B079 wide-angle (f/1.8, horizontal image angle 45°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box

EAN:

**4047438023269**

HS:

**85258091**

Weight (incl. packaging):

**1.980 g**

Dimensions (l/w/h) in cm:

**39,5 / 29,6 / 18,0**

### D15 Complete Cam 6MP, 2x B119 (Day & Night)

Artikelno.: **MX-D15Di-Sec-DNight-D65N65-FIX-6MP-F1.8**



#### Description:

IP camera with two parallel aligned lenses • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x L65/B119 tele (f/1.8, horizontal image angle 31°) • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box

EAN:

**4047438023276**

HS:

**85258091**

Weight (incl. packaging):

**1.980 g**

Dimensions (l/w/h) in cm:

**39,5 / 29,6 / 18,0**

### D15 Complete Cam 6MP, 2x B237 (Day & Night)

Artikelno.: **MX-D15Di-Sec-DNight-D135N135-FIX-6MP-F1.8**



#### Description:

IP camera with two parallel aligned lens units • 6 megapixel Moonlight sensors, 1x day and 1x night • HD premium lenses: 2x L135/B237 tele (f/1.8, horizontal image angle 15°) • Equipment line: Secure • Max. image size (per image sensor): 6MP (3072 x 2048 pixels) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount or IP66/IK10+ with Vandalism Set, each -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • Camera components: speaker, PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional MX-232-IO-Box

EAN:

**4047438023283**

HS:

**85258091**

Weight (incl. packaging):

**1.980 g**

Dimensions (l/w/h) in cm:

**39,5 / 29,6 / 18,0**



## D15 Complete Cam 2x 6MP, Panorama 180° (Day)

Artikelno.: **MX-D15Di-Sec-180-6MP-F1.8**



### Description:

IP camera with double lens unit • 2 Moonlight sensors day, 6MP (3072 x 2048) • HD premium lenses: 2x L22/B041 super wide-angle (horiz. image angle 180°) • Max. image size: 2x 6MP (6144 x 2048 Pixel) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount, IP66/IK10+ with Vandalism Set, each -30 bis 60 °C (-22 to 140°F) • Internal DVR: 4 GB microSD • Speaker, microphone, PIR sensor, temperature sensor, shock detector, MxActivitySensor, ethernet patch cable 0,5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:

**4047438023290**

HS:

**85258091**

Weight (incl. packaging):

**1.980 g**

Dimensions (l/w/h) in cm:

**39,5 / 29,6 / 18,0**

## D15 Complete Cam 2x 6MP, Panorama 180° (Night)

Artikelno.: **MX-D15Di-Sec-Night-180-6MP-F1.8**



### Description:

IP camera with double lens unit • 2 Moonlight sensors night, 6MP (3072 x 2048) • HD premium lenses: 2x L22/B041 super wide-angle (horiz. image angle 180°) • Max. image size: 2x 6MP (6144 x 2048 Pixel) • IP54 without accessories, IP65/IK10 with Outdoor Wall Mount, IP66/IK10+ with Vandalism Set, each -30 bis 60 °C (-22 to 140°F) • Internal DVR: 4 GB microSD • Speaker, microphone, PIR sensor, temperature sensor, shock detector, MxActivitySensor, ethernet patch cable 0,5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:

**4047438023306**

HS:

**85258091**

Weight (incl. packaging):

**1.980 g**

Dimensions (l/w/h) in cm:

**39,5 / 29,6 / 18,0**

**S15D Body, For 1–2 Sensor Modules (Day/Night/Thermal)**

Artikelno.: **MX-S15D-Sec**



**Description:**

S15D camera module (body) for connecting one or two sensor modules (to be ordered individually) • Image sensor options (via sensor module): 6 megapixels, color (day) and/or B/W (night) and/or thermal • Lens options (via optical sensor module): horizontal image angle from 180° to 8° • IP65, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: temperature sensor, shock detector, MxActivitySensor, ethernet patch cable 0.5 m/1.65 ft • Interfaces: 2x connection for MOBOTIX sensor module (Cam1/Cam2), Ethernet 10/100 (RJ45 and LSA), MxBus, USB, Audio I/O; RS232 via MX Interface Box • Connection of MOBOTIX Door Station modules

EAN:  
**4047438017725**

HS:  
**85258091**

Weight (incl. packaging):  
**704 g**

Dimensions (l/w/h) in cm:  
**19,6 / 14,8 / 9,0**

**S15D Complete Cam, Set 1, 6MP, 1x B016 (Day)**

Artikelno.: **MX-S15D-Set1-6MP**



**Description:**

S15D camera module (body) • 1x sensor module with HD premium lens L10/B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • 1x sensor cable 2 m/6.6 ft • 1x extension set • 1x ethernet patch cable 0.5 m/1.65 ft • 1x replacement dome • IP66 • Optional connection of a second sensor module (incl. Thermal) or MOBOTIX Door Station modules

EAN:  
**4047438023313**

HS:  
**85258091**

Weight (incl. packaging):  
**1.670 g**

Dimensions (l/w/h) in cm:  
**34,5 / 34,0 / 16,0**

**S15D Complete Cam, Set 2, 6MP, 2x B016 (Day)**

Artikelno.: **MX-S15D-Set2-6MP**



**Description:**

S15D IP camera module (body) • 2x sensor module with HD premium lens L10/B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • 2x sensor cable 2 m/6.6 ft • 2x extension set • 1x ethernet patch cable 0.5 m/1.65 ft • 2x replacement dome • IP66 • Connection of MOBOTIX Door Station modules

EAN:  
**4047438023320**

HS:  
**85258091**

Weight (incl. packaging):  
**1.670 g**

Dimensions (l/w/h) in cm:  
**34,5 / 34,0 / 16,0**

**S15D Complete Cam, Set 3, 6MP, 2x L10 (Day & Night)**

Artikelno.: **MX-S15D-Set3-6MP**



**Description:**

S15D camera module (body) • 1x sensor module with HD premium lens L10/B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • 1x sensor module with HD premium lens L10/B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048) • 2x sensor cable 2 m/6.6 ft • 1x extension set • 1x ethernet patch cable 0.5 m/1.65 ft • 2x replacement dome • IP66 • Connection of MOBOTIX Door Station modules

EAN:  
**4047438023337**

HS:  
**85258091**

Weight (incl. packaging):  
**1.670 g**

Dimensions (l/w/h) in cm:  
**34,5 / 34,0 / 16,0**

**S15M Complete Cam 6MP, B016 (Day)**

Artikelno.: **MX-S15-D016**



**Description:**

Hemispheric IP camera with 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65/IK06, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics (incl. behavioral detection), ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory) • Connection of MOBOTIX Door Station modules

EAN:  
**4047438026833**

HS:  
**85258091**

Weight (incl. packaging):  
**720 g**

Dimensions (l/w/h) in cm:  
**19,6 / 14,8 / 9,0**

**S15M Complete Cam 6MP, B016 (Night)**

Artikelno.: **MX-S15-N016**



**Description:**

Hemispheric IP camera with 6 Megapixel Moonlight Sensor, BW (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65/IK06, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics (incl. behavioral detection), ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory) • Connection of MOBOTIX Door Station modules

EAN:  
**4047438026840**

HS:  
**85258091**

Weight (incl. packaging):  
**720 g**

Dimensions (l/w/h) in cm:  
**19,6 / 14,8 / 9,0**

## V15 Complete Cam 6MP, 1x B041, Day

Artikelno.: **MX-V15M-Sec-D22-6MP-F1.8**



### Description:

V15 Vandalism with one 6MP Moonlight sensor day (3072 x 2048), HD premium lens L22/B041 (f/1.8, horiz. image angle 90°) • 3-5 mm stainless steel casing • IK10+/IP65 • Functional range like S15 • HD Audio: Microphone and speaker integrated in the housing

EAN:

**4047438024310**

HS:

**85258091**

Weight (incl. packaging):

**4.680 g**

Dimensions (l/w/h) in cm:

**26,0 / 26,0 / 26,0**

## V15 Complete Cam 6MP, 1x B079, Day

Artikelno.: **MX-V15M-Sec-D43-6MP-F1.8**



### Description:

V15 Vandalism with one 6MP Moonlight sensor day (3072 x 2048), HD premium lens L43/B079 (f/1.8, horiz. image angle 45°) • 3-5 mm stainless steel casing • IK10+/IP65 • Functional range like S15 • HD Audio: Microphone and speaker integrated in the housing

EAN:

**4047438024327**

HS:

**85258091**

Weight (incl. packaging):

**4.680 g**

Dimensions (l/w/h) in cm:

**26,0 / 26,0 / 26,0**

## V15 Complete Cam 2x 6MP, 2x B041, Day

Artikelno.: **MX-V15D-Sec-D22D22-6MP-F1.8**



### Description:

V15 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x color (day), two HD premium lenses L22/B041 (f/1.8, horiz. image angle 90°) • 3-5 mm stainless steel casing • IK10+/IP65 • Functional range like S15 • HD Audio: Microphone and speaker integrated in the housing

EAN:

**4047438024334**

HS:

**85258091**

Weight (incl. packaging):


**4.680 g**

Dimensions (l/w/h) in cm:

**26,0 / 26,0 / 26,0**

## V15 Complete Cam 2x 6MP, 2x B041, Day & Night

Artikelno.: **MX-V15D-Sec-DNight-D22N22-6MP-F1.8**



### Description:

V15 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 1x color (day), 1x B/W (night), two HD premium lenses L22/B041 (f/1.8, horiz. image angle 90°) • 3-5 mm stainless steel casing • IK10+/IP65 • Functional range like S15 • HD Audio: Microphone and speaker integrated in the housing

EAN:

**4047438024372**

HS:

**85258091**

Weight (incl. packaging):

**4.680 g**

Dimensions (l/w/h) in cm:

**26,0 / 26,0 / 26,0**

## V15 Complete Cam 2x 6MP, 2x B041, Night

Artikelno.: **MX-V15D-Sec-Night-N22N22-6MP-F1.8**



### Description:

V15 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x B/W (night), two HD premium lenses L22/B041 (f/1.8, horiz. image angle 90°) • 3-5 mm stainless steel casing • IK10+/IP65 • Functional range like S15 • HD Audio: Microphone and speaker integrated in the housing

EAN:

**4047438024358**

HS:

**85258091**

Weight (incl. packaging):

**4.680 g**

Dimensions (l/w/h) in cm:

**26,0 / 26,0 / 26,0**

## V15 Complete Cam 2x 6MP, 2x B079, Day

Artikelno.: **MX-V15D-Sec-D43D43-6MP-F1.8**



### Description:

V15 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x color (day), two HD premium lenses L43/B079 (f/1.8, horiz. image angle 45°) • 3-5 mm stainless steel casing • IK10+/IP65 • Functional range like S15 • HD Audio: Microphone and speaker integrated in the housing

EAN:

**4047438024341**

HS:

**85258091**

Weight (incl. packaging):

**4.680 g**

Dimensions (l/w/h) in cm:

**26,0 / 26,0 / 26,0**

## V15 Complete Cam 2x 6MP, 2x B079, Day & Night

Artikelno.: **MX-V15D-Sec-DNight-D43N43-6MP-F1.8**



**Description:**

V15 Vandalism with two 6MP Moonlight sensors (3072 x 2048): 1x color (day), 1x B/W (night), two HD premium lenses L43/B079 (f/1.8, horiz. image angle 45°) • 3-5 mm stainless steel casing • IK10+/IP65 • Functional range like S15 • HD Audio: Microphone and speaker integrated in the housing

EAN:

**4047438024389**

HS:

**85258091**

Weight (incl. packaging):

**4.680 g**

Dimensions (l/w/h) in cm:

**26,0 / 26,0 / 26,0**

## V15 Complete Cam 2x 6MP, 2x B079, Night

Artikelno.: **MX-V15D-Sec-Night-N43N43-6MP-F1.8**



**Description:**

V15D Vandalism with two 6MP Moonlight sensors (3072 x 2048): 2x B/W (night), two HD premium lenses L43/B079 (f/1.8, horiz. image angle 45°) • 3-5 mm stainless steel casing • IK10+/IP65 • Functional range like S15 • HD Audio: Microphone and speaker integrated in the housing

EAN:

**4047438024365**

HS:

**85258091**

Weight (incl. packaging):

**4.680 g**

Dimensions (l/w/h) in cm:

**26,0 / 26,0 / 26,0**

**M25 Body 6MP, Day**Artikelno.: **MX-M25-BOD1****Description:**

IP camera module (body) with 6 Megapixel Moonlight Sensor, color (day) • Lens to be ordered individually (B036 to B500) • For mounting the Super Tele Lens MX-B500, the Extended Replacement Lens Cover is needed (MOBOTIX accessory: MX-M24M-OPT-LCGL) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:

**4047438024891**

HS:

**85258091**

Weight (incl. packaging):

**1.330 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0****M25 Body 6MP, Night**Artikelno.: **MX-M25-BOD1-N****Description:**

IP camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) • Lens to be ordered individually (B036 to B500) • For mounting the Super Tele Lens B500, the Extended Replacement Lens Cover is needed (MOBOTIX accessory: MX-M24M-OPT-LCGL) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:

**4047438024907**

HS:

**85258091**

Weight (incl. packaging):

**2.000 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0****M25 Complete Cam 6MP, B016, Tag**Artikelno.: **MX-M25-D016****Description:**

Hemispheric IP camera with 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:

**4047438024914**

HS:

**85258091**

Weight (incl. packaging):

**1.338 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

## Supplementary Program (SUP)

The supplementary program encompasses other camera models which include complete sets that are pre-assembled and focus calibrated. This service takes approximately 5 business days. Many products of the supplemental program can be ordered from the standard program as individual components for self-assembly.

### M25 Complete Cam 6MP, B036, Day

Artikelno.: **MX-M25-D036**



#### Description:

IP camera with 6 Megapixel Moonlight Sensor, color (day) • Ultra Wide Lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:

**4047438024778**

HS:

**85258091**

Weight (incl. packaging):

**2.000 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

### M25 Complete Cam 6MP, B041, Day

Artikelno.: **MX-M25-D041**



#### Description:

IP camera with 6 Megapixel Moonlight Sensor, color (day) • Super Wide Lens B041 (focal length 4.1 mm, f/1.8, 90° x 67°) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:

**4047438024785**

HS:

**85258091**

Weight (incl. packaging):

**1.347 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

### M25 Complete Cam 6MP, B061, Day

Artikelno.: **MX-M25-D061**



#### Description:

IP camera with 6 Megapixel Moonlight Sensor, color (day) • Wide Lens B061 (focal length 6.1 mm, f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:

**4047438024792**

HS:

**85258091**

Weight (incl. packaging):

**1.351 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

### M25 Complete Cam 6MP, B079, Day

Artikelno.: **MX-M25-D079**



#### Description:

IP camera with 6 Megapixel Moonlight Sensor, color (day) • Standard Lens B079 (focal length 7.9 mm, f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:

**4047438024808**

HS:

**85258091**

Weight (incl. packaging):

**2.000 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

### M25 Complete Cam 6MP, B119, Day

Artikelno.: **MX-M25-D119**



#### Description:

IP camera with 6 Megapixel Moonlight Sensor, color (day) • Tele Lens B119 (focal length 11.9 mm, f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:

**4047438024815**

HS:

**85258091**

Weight (incl. packaging):

**1.340 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

### M25 Complete Cam 6MP, B237, Day

Artikelno.: **MX-M25-D237**



#### Description:

IP camera with 6 Megapixel Moonlight Sensor, color (day) • Distant Tele Lens B237 (focal length 23.7 mm, f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:

**4047438024822**

HS:

**85258091**

Weight (incl. packaging):

**2.000 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

## M25 Complete Cam 6MP, B500, Day

Artikelno.: **MX-M25-D500**



### Description:

IP camera with 6 Megapixel Moonlight Sensor, color (day) • Super Tele Lens B500 (focal length 50 mm, f/2.5, 8° x 6°) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:

**4047438024952**

HS:

**85258091**

Weight (incl. packaging):

**1.363 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

## M25 Complete Cam 6MP, B016, Night

Artikelno.: **MX-M25-N016**



### Description:

Hemispheric IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:

**4047438024921**

HS:

**85258091**

Weight (incl. packaging):

**1.338 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

## M25 Complete Cam 6MP, B036, Night

Artikelno.: **MX-M25-N036**



### Description:

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Ultra Wide Lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:

**4047438024839**

HS:

**85258091**

Weight (incl. packaging):

**2.000 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

## M25 Complete Cam 6MP, B041, Night

Artikelno.: **MX-M25-N041**



### Description:

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Super Wide Lens B041 (focal length 4.1 mm, f/1.8, 90° x 67°) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:

**4047438024846**

HS:

**85258091**

Weight (incl. packaging):

**1.344 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

## M25 Complete Cam 6MP, B061, Night

Artikelno.: **MX-M25-N061**



### Description:

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Wide Lens B061 (focal length 6.1 mm, f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:

**4047438024853**

HS:

**85258091**

Weight (incl. packaging):

**2.000 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

## M25 Complete Cam 6MP, B079, Night

Artikelno.: **MX-M25-N079**



### Description:

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Standard Lens B079 (focal length 7.9 mm, f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:

**4047438024860**

HS:

**85258091**

Weight (incl. packaging):

**1.346 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

## M25 Complete Cam 6MP, B119, Night

Artikelno.: **MX-M25-N119**



### Description:

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Tele Lens B119 (focal length 11.9 mm, f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:

**4047438024877**

HS:

**85258091**

Weight (incl. packaging):

**1.343 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

## M25 Complete Cam 6MP, B237, Night

Artikelno.: **MX-M25-N237**



### Description:

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Distant Tele Lens B237 (focal length 23.7 mm, f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:

**4047438024884**

HS:

**85258091**

Weight (incl. packaging):

**2.000 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

## M25 Complete Cam 6MP, B500, Night

Artikelno.: **MX-M25-N500**



### Description:

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Super Tele Lens B500 (focal length 50 mm, f/2.5, 8° x 6°) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:

**4047438024969**

HS:

**85258091**

Weight (incl. packaging):

**2.000 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**



## D25 Body 6MP, Day

Artikelno.: **MX-D25-BOD1**



### Description:

D25 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) • Lens to be ordered individually (B036 to B237) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:

**4047438025249**

HS:

**85258091**

Weight (incl. packaging):


**1.580 g**

Dimensions (l/w/h) in cm:

**19,6 / 18,0 / 14,8**

## D25 Body 6MP, Night

Artikelno.: **MX-D25-BOD1-N**



### Description:

D25 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) • Lens to be ordered individually (B036 to B237) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:

**4047438025256**

HS:

**85258091**

Weight (incl. packaging):

**1.580 g**

Dimensions (l/w/h) in cm:

**19,6 / 18,0 / 14,8**

## Supplementary Program (SUP)

The supplementary program encompasses other camera models which include complete sets that are pre-assembled and focus calibrated. This service takes approximately 5 business days. These products can also be ordered from the standard program as individual components for self-assembly.

### D25 Complete Cam 6MP, B036, Day

Artikelno.: **MX-D25-D036**



#### Description:

IP camera with 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:

**4047438025126**

HS:

**85258091**

Weight (incl. packaging):

**1.580 g**

Dimensions (l/w/h) in cm:

**19,6 / 18,0 / 14,8**

### D25 Complete Cam 6MP, B041, Day

Artikelno.: **MX-D25-D041**



#### Description:

IP camera with 6 Megapixel Moonlight Sensor, color (day) • Super wide lens B041 (f/1.8, 90° x 67°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:

**4047438025133**

HS:

**85258091**

Weight (incl. packaging):

**1.580 g**

Dimensions (l/w/h) in cm:

**19,6 / 18,0 / 14,8**

### D25 Complete Cam 6MP, B061, Day

Artikelno.: **MX-D25-D061**



#### Description:

IP camera with 6 Megapixel Moonlight Sensor, color (day) • Wide lens B061 (f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:

**4047438025140**

HS:

**85258091**

Weight (incl. packaging):

**1.580 g**

Dimensions (l/w/h) in cm:

**19,6 / 18,0 / 14,8**

### D25 Complete Cam 6MP, B079, Day

Artikelno.: **MX-D25-D079**



#### Description:

IP camera with 6 Megapixel Moonlight Sensor, color (day) • Standard lens B079 (f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:

**4047438025157**

HS:

**85258091**

Weight (incl. packaging):

**1.580 g**

Dimensions (l/w/h) in cm:

**19,6 / 18,0 / 14,8**

### D25 Complete Cam 6MP, B119, Day

Artikelno.: **MX-D25-D119**



#### Description:

IP camera with 6 Megapixel Moonlight Sensor, color (day) • Tele lens B119 (f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:

**4047438025164**

HS:

**85258091**

Weight (incl. packaging):

**1.580 g**

Dimensions (l/w/h) in cm:

**19,6 / 18,0 / 14,8**

### D25 Complete Cam 6MP, B237, Day

Artikelno.: **MX-D25-D237**



#### Description:

IP camera with 6 Megapixel Moonlight Sensor, color (day) • Distance tele lens B237 (f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:

**4047438025171**

HS:

**85258091**

Weight (incl. packaging):

**1.580 g**

Dimensions (l/w/h) in cm:

**19,6 / 18,0 / 14,8**

## D25 Complete Cam 6MP, B036, Night

Artikelno.: **MX-D25-N036**



### Description:

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:  
**4047438025188**

HS:  
**85258091**

Weight (incl. packaging):  
**1.580 g**

Dimensions (l/w/h) in cm:  
**19,6 / 18,0 / 14,8**

## D25 Complete Cam 6MP, B041, Night

Artikelno.: **MX-D25-N041**



### Description:

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Super wide lens B041 (f/1.8, 90° x 67°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:  
**4047438025195**

HS:  
**85258091**

Weight (incl. packaging):  
**1.580 g**

Dimensions (l/w/h) in cm:  
**19,6 / 18,0 / 14,8**

## D25 Complete Cam 6MP, B061, Night

Artikelno.: **MX-D25-N061**



### Description:

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Wide lens B061 (f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:  
**4047438025201**

HS:  
**85258091**

Weight (incl. packaging):  
**1.580 g**

Dimensions (l/w/h) in cm:  
**19,6 / 18,0 / 14,8**

## D25 Complete Cam 6MP, B079, Night

Artikelno.: **MX-D25-N079**



### Description:

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Standard lens B079 (f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:  
**4047438025218**

HS:  
**85258091**

Weight (incl. packaging):  
**1.580 g**

Dimensions (l/w/h) in cm:  
**19,6 / 18,0 / 14,8**

## D25 Complete Cam 6MP, B119, Night

Artikelno.: **MX-D25-N119**



### Description:

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Tele lens B119 (f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:  
**4047438025225**

HS:  
**85258091**

Weight (incl. packaging):  
**1.580 g**

Dimensions (l/w/h) in cm:  
**19,6 / 18,0 / 14,8**

## D25 Complete Cam 6MP, B237, Night

Artikelno.: **MX-D25-N237**



### Description:

IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • Distance tele lens B237 (f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft, lens cover with sealing ring • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory)

EAN:  
**4047438025232**

HS:  
**85258091**

Weight (incl. packaging):  
**1.580 g**

Dimensions (l/w/h) in cm:  
**19,6 / 18,0 / 14,8**

## Q25 Complete Cam 6MP, B016, Day

Artikelno.: **MX-Q25-D016**



### Description:

Hemispheric IP camera with 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics (incl. behavioral detection), ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory) • Color: white

EAN:

**4047438025829**

HS:

**85258091**

Weight (incl. packaging):

**834 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 9,0**

## Q25 Complete Cam 6MP, B016, Night

Artikelno.: **MX-Q25-N016**



### Description:

Hemispheric IP camera with 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, shock detector, MxActivitySensor, MxAnalytics (incl. behavioral detection), ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; I/O and RS232 via Interface Box (MOBOTIX accessory) • Color: white

EAN:

**4047438025843**

HS:

**85258091**

Weight (incl. packaging):

**837 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 9,0**



## Indoor Ceiling Camera. Easy To Install.

The c26 is the smallest and lightest MOBOTIX hemispheric complete video system for ceiling installation indoors. Its features include a light-sensitive 6MP day or night sensor and MxAnalytics video analysis tools, which can be used for depicting customer movements in sales rooms, for instance.



Indoor

c26 Day or Night	c26 Audio Day or Night	Description	Image Angle horizontal	Focal Length	Aperture
Mx-c26A-6D016		c26 Indoor overview camera day with lens B016 (180° x 180°) white		1.6 mm	f/2.0
Mx-c26A-6D036		c26 Indoor overview camera day with lens B036 (103° x 77°) white		3.6 mm	f/1.8
Mx-c26A-6N016		c26 Indoor overview camera night with lens B016 (180° x 180°) white		1.6 mm	f/2.0
Mx-c26A-6N036		c26 Indoor overview camera night with lens B036 (103° x 77°) white		3.6 mm	f/1.8
	Mx-c26A-AU-6D016	c26 Indoor overview camera day with lens B016 (180° x 180°) white		1.6 mm	f/2.0
	Mx-c26A-AU-6D036	c26 Indoor overview camera day with lens B036 (103° x 77°) white		3.6 mm	f/1.8
	Mx-c26A-AU-6N016	c26 Indoor overview camera night with lens B016 (180° x 180°) white		1.6 mm	f/2.0
	Mx-c26A-AU-6N036	c26 Indoor overview camera night with lens B036 (103° x 77°) white		3.6 mm	f/1.8

**c26 Complete Cam 6MP, B016, Day**Artikelno.: **Mx-c26A-6D016**

Mx6

**Description:**

Hemispheric IP indoor camera for ceiling mounting • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

EAN:

**4047438028677**

HS:

**85258091**

Weight (incl. packaging):

**400 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5****c26 Complete Cam 6MP, B036, Day**Artikelno.: **Mx-c26A-6D036**

Mx6

**Description:**

IP indoor camera for ceiling mounting • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

EAN:

**4047438028684**

HS:

**85258091**

Weight (incl. packaging):

**400 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5****c26 Complete Cam 6MP, B016, Night**Artikelno.: **Mx-c26A-6N016**

Mx6

**Description:**

Hemispheric IP indoor camera for ceiling mounting • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

EAN:

**4047438028691**

HS:

**85258091**

Weight (incl. packaging):

**400 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5****c26 Complete Cam 6MP, B036, Night**Artikelno.: **Mx-c26A-6N036**

Mx6

**Description:**

IP indoor camera for ceiling mounting • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

EAN:

**4047438028714**

HS:

**85258091**

Weight (incl. packaging):

**400 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5****c26 Complete Cam 6MP, B016, Day, Audio Package**Artikelno.: **Mx-c26A-AU-6D016**

Mx6

**Description:**

Hemispheric IP indoor camera for ceiling mounting • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

EAN:

**4047438028707**

HS:

**85258091**

Weight (incl. packaging):

**400 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5****c26 Complete Cam 6MP, B036, Day, Audio Package**Artikelno.: **Mx-c26A-AU-6D036**

Mx6

**Description:**

IP indoor camera for ceiling mounting • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

EAN:

**4047438028721**

HS:

**85258091**

Weight (incl. packaging):

**400 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5**

**c26 Complete Cam 6MP, B016, Night, Audio Package**

Artikelno.: **Mx-c26A-AU-6N016**



**Description:**

Hemispheric IP indoor camera for ceiling mounting • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

EAN:  
**4047438028738**

HS:  
**85258091**

Weight (incl. packaging):  
**400 g**

Dimensions (l/w/h) in cm:  
**17,5 / 14,0 / 13,5**

**c26 Complete Cam 6MP, B036, Night, Audio Package**

Artikelno.: **Mx-c26A-AU-6N036**



**Description:**

IP indoor camera for ceiling mounting • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104° F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection), shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

EAN:  
**4047438028745**

HS:  
**85258091**

Weight (incl. packaging):  
**400 g**

Dimensions (l/w/h) in cm:  
**17,5 / 14,0 / 13,5**



## Perfect Wall Installation - Compact, Discreet And Inexpensive.

The i26 was specially developed for wall installation. Thanks to its tilt angle of 15°, it provides a perfect overview. A single i26 with a 180° lens monitors an entire room. The camera's compact design ensures an inconspicuous appearance in all environments.



i26 Day or Night	i26 Day or Night	i26 Audio Day or Night	Description	Image Angle horizontal	Focal Length	Aperture	
Mx-i26A-6D			i26 Indoor wall camera night w/o lens				
Mx-i26A-6N			i26 Indoor wall camera night w/o lens				
	Mx-i26A-6D016		i26 Indoor wall camera day with lens B016 (180° x 180°) white		1.6 mm	f/2.0	
	Mx-i26A-6D036		i26 Indoor wall camera day with lens B036 (103° x 77°) white		3.6 mm	f/1.8	
	Mx-i26A-6N016		i26 Indoor wall camera night with lens B016 (180° x 180°) white		1.6 mm	f/2.0	
	Mx-i26A-6N036		i26 Indoor wall camera night with lens B036 (103° x 77°) white		3.6 mm	f/1.8	
		Mx-i26A-AU-6D016	i26 Indoor wall camera day with lens B016 (180° x 180°) white incl. audio set		1.6 mm	f/2.0	
		Mx-i26A-AU-6D036	i26 Indoor wall camera day with lens B036 (103° x 77°) white incl. audio set		3.6 mm	f/1.8	
		Mx-i26A-AU-6N016	i26 Indoor wall camera night with lens B016 (180° x 180°) white incl. audio set		1.6 mm	f/2.0	
		Mx-i26A-AU-6N036	i26 Indoor wall camera night with lens B036 (103° x 77°) white incl. audio set		3.6 mm	f/1.8	



**i26 Complete Cam 6MP, B016, Day**Artikelno.: **Mx-i26A-6D016**

Mx6

**Description:**

Hemispheric IP indoor camera for wall mounting • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

EAN:

**4047438028592**

HS:

**85258091**

Weight (incl. packaging):

**420 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5****i26 Complete Cam 6MP, B036, Day**Artikelno.: **Mx-i26A-6D036**

Mx6

**Description:**

IP indoor camera for wall mounting • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

EAN:

**4047438028608**

HS:

**85258091**

Weight (incl. packaging):

**420 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5****i26 Complete Cam 6MP, B016, Night**Artikelno.: **Mx-i26A-6N016**

Mx6

**Description:**

Hemispheric IP indoor camera for wall mounting • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

EAN:

**4047438028622**

HS:

**85258091**

Weight (incl. packaging):

**420 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5****i26 Complete Cam 6MP, B036, Night**Artikelno.: **Mx-i26A-6N036**

Mx6

**Description:**

IP indoor camera for wall mounting • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

EAN:

**4047438028639**

HS:

**85258091**

Weight (incl. packaging):

**420 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5****i26 Complete Cam 6MP, B016, Day, Audio Package**Artikelno.: **Mx-i26A-AU-6D016**

Mx6

**Description:**

Hemispheric IP indoor camera for wall mounting • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

EAN:

**4047438028615**

HS:

**85258091**

Weight (incl. packaging):

**420 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5****i26 Complete Cam 6MP, B036, Day, Audio Package**Artikelno.: **Mx-i26A-AU-6D036**

Mx6

**Description:**

IP indoor camera for wall mounting • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Audio package with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

EAN:

**4047438028646**

HS:

**85258091**

Weight (incl. packaging):

**420 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5**

**i26 Complete Cam 6MP, B016, Night, Audio Package**

Artikelno.: **Mx-i26A-AU-6N016**



**Mx6**

**Description:**

Hemispheric IP indoor camera for wall mounting • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

EAN:

**4047438028653**

HS:

**85258091**

Weight (incl. packaging):

**420 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5**

**i26 Complete Cam 6MP, B036, Night, Audio Package**

Artikelno.: **Mx-i26A-AU-6N036**



**Mx6**

**Description:**

IP indoor camera for wall mounting • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104° F) • 4-GB microSD • Audio package with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

EAN:

**4047438028660**

HS:

**85258091**

Weight (incl. packaging):

**420 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5**



## Flexible And Compact. Adapts To Meet Your Requirements.

The p26 is equipped with a light-sensitive 6-megapixel Moonlight sensor and manually adjustable lens (15° distance telephoto to 180° hemispheric) as standard, making it well suited for every indoor environment. Thanks to its competitive price, full range of MOBOTIX functions and inclusion of MxManagementCenter software free of charge, this system represents one of the most appealing indoor security solutions on the market.



Indoor

p26 Day	p26 Night	p26 Audio Day	p26 Audio Night	Description	Image Angle horizontal	Focal Length	Aperture
Mx-p26A-6D	Mx-p26A-6N			p26 Indoor ceiling camera day or night w/o lens white			
Mx-p26A-6D016				p26 Indoor ceiling camera day with lens B016 (180° x 180°) white		1.6 mm	f/1.8
Mx-p26A-6D036				p26 Indoor ceiling camera day with lens B036 (103° x 77°) white		3.6 mm	f/1.8
Mx-p26A-6D061				p26 Indoor ceiling camera day with lens B061 (60° x 45°) white		6.1 mm	f/1.8
Mx-p26A-6D079				p26 Indoor ceiling camera day with lens B079 (45° x 34°) white		7.9 mm	f/1.8
Mx-p26A-6D119				p26 Indoor ceiling camera day with lens B119 (31° x 23°) white		11.9 mm	f/1.8
Mx-p26A-6D237				p26 Indoor ceiling camera day with lens B237 (15° x 11°) white		23.7 mm	f/1.8
	Mx-p26A-6N016			p26 Indoor ceiling camera night with lens B016 (180° x 180°) white		1.6 mm	f/2.0
	Mx-p26A-6N036			p26 Indoor ceiling camera night with lens B036 (103° x 77°) white		3.6 mm	f/1.8
		Mx-p26A-AU-6D	Mx-p26A-AU-6N	p26 Indoor ceiling camera day or night w/o lens, white			
		Mx-p26A-AU-6D016	Mx-p26A-AU-6N016	p26 Indoor ceiling camera day or night with lens B016 (180° x 180°), white		1.6 mm	f/2.0
		Mx-p26A-AU-6D036	Mx-p26A-AU-6N036	p26 Indoor ceiling camera day or night with lens B036 (103° x 77°), white		3.6 mm	f/1.8

**p26 Body 6MP, Day**

Artikelno.: **Mx-p26A-6D**



Mx6

**Description:**

p26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

EAN:  
**4047438028462**

HS:  
**85258091**

Weight (incl. packaging):  
**480 g**

Dimensions (l/w/h) in cm:  
**16,0 / 13,0 / 13,0**

**p26 Complete Cam 6MP, B016, Day**

Artikelno.: **Mx-p26A-6D016**



Mx6

**Description:**

Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

EAN:  
**4047438028448**

HS:  
**85258091**

Weight (incl. packaging):  
**480 g**

Dimensions (l/w/h) in cm:  
**16,0 / 13,0 / 13,0**

**p26 Body 6MP, Night**

Artikelno.: **Mx-p26A-6N**



Mx6

**Description:**

p26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B235, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

EAN:  
**4047438028479**

HS:  
**85258091**

Weight (incl. packaging):  
**480 g**

Dimensions (l/w/h) in cm:  
**16,0 / 13,0 / 13,0**

**p26 Complete Cam 6MP, B016, Night**

Artikelno.: **Mx-p26A-6N016**



Mx6

**Description:**

Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

EAN:  
**4047438028530**

HS:  
**85258091**

Weight (incl. packaging):  
**480 g**

Dimensions (l/w/h) in cm:  
**16,0 / 13,0 / 13,0**

**p26 Body 6MP, Day, Audio Package**

Artikelno.: **Mx-p26A-AU-6D**



Mx6

**Description:**

p26 camera module (body) with 6 Megapixel Moonlight Sensor, color (day) and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD-Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

EAN:  
**4047438028752**

HS:  
**85258091**

Weight (incl. packaging):  
**480 g**

Dimensions (l/w/h) in cm:  
**16,0 / 13,0 / 13,0**

**p26 Complete Cam 6MP, B016, Day, Audio Package**

Artikelno.: **Mx-p26A-AU-6D016**



Mx6

**Description:**

Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

EAN:  
**4047438028486**

HS:  
**85258091**

Weight (incl. packaging):  
**480 g**

Dimensions (l/w/h) in cm:  
**16,0 / 13,0 / 13,0**

**p26 Body 6MP, Night, Audio Package**

Artikelno.: **Mx-p26A-AU-6N**



Mx6

**Description:**

p26 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) and lens mount • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Lens to be ordered individually (B036 to B235, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

EAN:

**4047438028585**

HS:

**85258091**

Weight (incl. packaging):

**480 g**

Dimensions (l/w/h) in cm:

**16,0 / 13,0 / 13,0**

**p26 Complete Cam 6MP, B016, Night, Audio Package**

Artikelno.: **Mx-p26A-AU-6N016**



Mx6

**Description:**

Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

EAN:

**4047438028561**

HS:

**85258091**

Weight (incl. packaging):

**480 g**

Dimensions (l/w/h) in cm:

**16,0 / 13,0 / 13,0**

**Supplementary Program (SUP)**

The supplementary program encompasses other camera models which include complete sets that are pre-assembled and focus calibrated. This service takes approximately 5 business days. Many products of the supplemental program can be ordered from the standard program as individual components for self-assembly.

**p26 Complete Cam 6MP, B036, Day**

Artikelno.: **Mx-p26A-6D036**



**Mx6** Description:

IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

EAN:  
**4047438028455**

HS:  
**85258091**

Weight (incl. packaging):  
**480 g**

Dimensions (l/w/h) in cm:  
**16,0 / 13,0 / 13,0**

**p26 Complete Cam 6MP, B061, Day**

Artikelno.: **Mx-p26A-6D061**



**Mx6** Description:

IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Wide lens B061 (focal length 6.1 mm, f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

EAN:  
**4047438028493**

HS:  
**85258091**

Weight (incl. packaging):  
**480 g**

Dimensions (l/w/h) in cm:  
**16,0 / 13,0 / 13,0**

**p26 Complete Cam 6MP, B079, Day**

Artikelno.: **Mx-p26A-6D079**



**Mx6** Description:

IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Standard lens B079 (focal length 7.9 mm, f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

EAN:  
**4047438028509**

HS:  
**85258091**

Weight (incl. packaging):  
**480 g**

Dimensions (l/w/h) in cm:  
**16,0 / 13,0 / 13,0**

**p26 Complete Cam 6MP, B119, Day**

Artikelno.: **Mx-p26A-6D119**



**Mx6** Description:

IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Tele lens B119 (focal length 11.9 mm, f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

EAN:  
**4047438028516**

HS:  
**85258091**

Weight (incl. packaging):  
**480 g**

Dimensions (l/w/h) in cm:  
**16,0 / 13,0 / 13,0**

**p26 Complete Cam 6MP, B237, Day**

Artikelno.: **Mx-p26A-6D237**



**Mx6** Description:

IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Distant Tele lens B237 (focal length 23.7 mm, f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

EAN:  
**4047438028523**

HS:  
**85258091**

Weight (incl. packaging):  
**480 g**

Dimensions (l/w/h) in cm:  
**16,0 / 13,0 / 13,0**

**p26 Complete Cam 6MP, B036, Night**

Artikelno.: **Mx-p26A-6N036**



**Mx6** Description:

IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra Wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

EAN:  
**4047438028547**

HS:  
**85258091**

Weight (incl. packaging):  
**480 g**

Dimensions (l/w/h) in cm:  
**16,0 / 13,0 / 13,0**

**p26 Complete Cam 6MP, B036, Day, Audio Package**

Artikelno.: **Mx-p26A-AU-6D036**



**Description:**

IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

EAN:  
**4047438028554**

HS:  
**85258091**

Weight (incl. packaging):  
**480 g**

Dimensions (l/w/h) in cm:  
**16,0 / 13,0 / 13,0**

**p26 Complete Cam 6MP, B036, Night, Audio Package**

Artikelno.: **Mx-p26A-AU-6N036**



**Description:**

IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Color: white

EAN:  
**4047438028578**

HS:  
**85258091**

Weight (incl. packaging):  
**480 g**

Dimensions (l/w/h) in cm:  
**16,0 / 13,0 / 13,0**







## Perfectly Protected. Professionally Fitted.

The dome camera, which is available in black or white, can be fitted with six different MOBOTIX HD premium lenses with fields of view of 103° to 15°. An on-wall set with an integrated microphone and speaker is optionally available, as is a vandalism set for increased camera protection featuring a stainless steel ring and reinforced dome.



Indoor

v26 Day or Night	v26 Black Day or Night	Description	Image Angle horizontal	Focal Length	Aperture
Mx-v26A-6D		v26 Indoor dome camera day w/o lens white			
Mx-v26A-6D036		v26 Indoor dome camera day with lens B036 (103° x 77°) white		1.6 mm	f/2.0
Mx-v26A-6N		v26 Indoor dome camera night w/o lens white			
	Mx-v26A-6D-b	v26 Indoor dome camera day w/o lens black		1.6 mm	f/2.0
	Mx-v26A-6N-b	v26 Indoor dome camera night w/o lens black		3.6 mm	f/1.8

**v26 Body 6MP, Day, White**Artikelno.: **Mx-v26A-6D**

Mx6

**Description:**

v26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Housing color: white

EAN:

**4047438028394**

HS:

**85258091**

Weight (incl. packaging):

**690 g**

Dimensions (l/w/h) in cm:

**20,5 / 19,8 / 12,3****v26 Body 6MP, Day, Black**Artikelno.: **Mx-v26A-6D-b**

Mx6

**Description:**

v26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Housing color: black

EAN:

**4047438028424**

HS:

**85258091**

Weight (incl. packaging):

**690 g**

Dimensions (l/w/h) in cm:

**20,5 / 19,8 / 12,3****v26 Complete Cam 6MP, B036, Day, White**Artikelno.: **Mx-v26A-6D036**

Mx6

**Description:**

IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle 0° to -90° • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Housing color: white

EAN:

**4047438028417**

HS:

**85258091**

Weight (incl. packaging):

**700 g**

Dimensions (l/w/h) in cm:

**20,5 / 19,8 / 12,3****v26 Body 6MP, Night, White**Artikelno.: **Mx-v26A-6N**

Mx6

**Description:**

v26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Housing color: white

EAN:

**4047438028400**

HS:

**85258091**

Weight (incl. packaging):

**690 g**

Dimensions (l/w/h) in cm:

**20,5 / 19,8 / 12,3****v26 Body 6MP, Night, Black**Artikelno.: **Mx-v26A-6N-b**

Mx6

**Description:**

v26 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • Mx6 system platform with H.264, MxPEG+ and M-JPEG • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics, shock detector • Ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45), USB, slot for MxIOBoard-IC (Mx-A-IO-IC) • Housing color: black

EAN:

**4047438028431**

HS:

**85258091**

Weight (incl. packaging):

**690 g**

Dimensions (l/w/h) in cm:

**20,5 / 19,8 / 12,3**



**c25 Complete Cam 6MP, B016, Day**Artikelno.: **MX-c25-D016****Description:**

Hemispheric IP indoor camera for ceiling mounting • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection) • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

EAN:

**4047438026611**

HS:

**85258091**

Weight (incl. packaging):

**400 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5****c25 Complete Cam 6MP, B036, Day**Artikelno.: **MX-c25-D036****Description:**

IP indoor camera for ceiling mounting • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection) • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

EAN:

**4047438026635**

HS:

**85258091**

Weight (incl. packaging):

**400 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5****c25 Complete Cam 6MP, B016, Night**Artikelno.: **MX-c25-N016****Description:**

Hemispheric IP indoor camera for ceiling mounting • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection) • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

EAN:

**4047438026628**

HS:

**85258091**

Weight (incl. packaging):

**400 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5****c25 Complete Cam 6MP, B016, Day, Audio Package**Artikelno.: **MX-c25-D016-AUD****Description:**

Hemispheric IP indoor camera for ceiling mounting • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection) • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

EAN:

**4047438026659**

HS:

**85258091**

Weight (incl. packaging):

**400 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5**

## Supplementary Program (SUP)

The supplementary program encompasses other camera models which include complete sets that are pre-assembled and focus calibrated. This service takes approximately 5 business days.

### c25 Complete Cam 6MP, B036, Night

Artikelno.: **MX-c25-N036**



#### Description:

IP indoor camera for ceiling mounting • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection) • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

EAN:

**4047438026642**

HS:

**85258091**

Weight (incl. packaging):

**400 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5**

### c25 Complete Cam 6MP, B036, Day, Audio Package

Artikelno.: **MX-c25-D036-AUD**



#### Description:

IP indoor camera for ceiling mounting • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection) • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

EAN:

**4047438026673**

HS:

**85258091**

Weight (incl. packaging):

**400 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5**

### c25 Complete Cam 6MP, B016, Night, Audio Package

Artikelno.: **MX-c25-N016-AUD**



#### Description:

Hemispheric IP indoor camera for ceiling mounting • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection) • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

EAN:

**4047438026666**

HS:

**85258091**

Weight (incl. packaging):

**400 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5**

### c25 Complete Cam 6MP, B036, Night, Audio Package

Artikelno.: **MX-c25-N036-AUD**



#### Description:

IP indoor camera for ceiling mounting • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics (incl. behavioral detection) • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

EAN:

**4047438026680**

HS:

**85258091**

Weight (incl. packaging):

**400 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5**

**i25 Complete Cam 6MP, B016, Day**Artikelno.: **MX-i25-D016****Description:**

Hemispheric IP indoor camera for wall mounting • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

EAN:

**4047438026697**

HS:

**85258091**

Weight (incl. packaging):

**420 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5****i25 Complete Cam 6MP, B036, Day**Artikelno.: **MX-i25-D036****Description:**

IP indoor camera for wall mounting • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

EAN:

**4047438026710**

HS:

**85258091**

Weight (incl. packaging):

**420 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5****i25 Complete Cam 6MP, B016, Day, Audio Package**Artikelno.: **MX-i25-D016-AUD****Description:**

Hemispheric IP indoor camera for wall mounting • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

EAN:

**4047438026734**

HS:

**85258091**

Weight (incl. packaging):

**420 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5**

## Supplementary Program (SUP)

The supplementary program encompasses other camera models which include complete sets that are pre-assembled and focus calibrated. This service takes approximately 5 business days.

**i25 Complete Cam 6MP, B016, Night**Artikelno.: **MX-i25-N016**

## Description:

Hemispheric IP indoor camera for wall mounting • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

EAN:

**4047438026703**

HS:

**85258091**

Weight (incl. packaging):

**420 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5****i25 Complete Cam 6MP, B036, Night**Artikelno.: **MX-i25-N036**

## Description:

IP indoor camera for wall mounting • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

EAN:

**4047438026727**

HS:

**85258091**

Weight (incl. packaging):

**420 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5****i25 Complete Cam 6MP, B036, Day, Audio Package**Artikelno.: **MX-i25-D036-AUD**

## Description:

IP indoor camera for wall mounting • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Audio package with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

EAN:

**4047438026758**

HS:

**85258091**

Weight (incl. packaging):

**420 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5****i25 Complete Cam 6MP, B016, Night, Audio Package**Artikelno.: **MX-i25-N016-AUD**

## Description:

Hemispheric IP indoor camera for wall mounting • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

EAN:

**4047438026741**

HS:

**85258091**

Weight (incl. packaging):

**420 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5****i25 Complete Cam 6MP, B036, Night, Audio Package**Artikelno.: **MX-i25-N036-AUD**

## Description:

IP indoor camera for wall mounting • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP30, 0 to 40°C (32 to 104°F) • 4-GB microSD • Audio package with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

EAN:

**4047438026765**

HS:

**85258091**

Weight (incl. packaging):

**420 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5**

**p25 Body 6MP, Day**

Artikelno.: **MX-p25-BOD1**



**Description:**

p25 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

EAN:  
**4047438026482**

HS:  
**85258091**

Weight ( incl. packaging):  
**480 g**

Dimensions (l/w/h) in cm:  
**17,5 / 14,0 / 13,5**

**p25 Body 6MP, Night**

Artikelno.: **MX-p25-BOD1-N**



**Description:**

p25 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B235, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

EAN:  
**4047438026499**

HS:  
**85258091**

Weight ( incl. packaging):  
**480 g**

Dimensions (l/w/h) in cm:  
**17,5 / 14,0 / 13,5**

**p25 Body 6MP, Day, Audio Package**

Artikelno.: **MX-p25-BOD1-AUD**



**Description:**

p25 camera module (body) with 6 Megapixel Moonlight Sensor, color (day) and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD-Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

EAN:  
**4047438026819**

HS:  
**85258091**

Weight ( incl. packaging):  
**480 g**

Dimensions (l/w/h) in cm:  
**17,5 / 14,0 / 13,5**

**p25 Body 6MP, Night, Audio Package**

Artikelno.: **MX-p25-BOD1-N-AUD**



**Description:**

p25 camera module (body) with 6 Megapixel Moonlight Sensor, B/W (night) and lens mount • Lens to be ordered individually (B036 to B235, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle -5° to -45° • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

EAN:  
**4047438026826**

HS:  
**85258091**

Weight ( incl. packaging):  
**480 g**

Dimensions (l/w/h) in cm:  
**17,5 / 14,0 / 13,5**

**p25 Complete Cam 6MP, B016, Day**

Artikelno.: **MX-p25-D016**



**Description:**

Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

EAN:  
**4047438026406**

HS:  
**85258091**

Weight ( incl. packaging):  
**480 g**

Dimensions (l/w/h) in cm:  
**17,5 / 14,0 / 13,5**

**p25 Complete Cam 6MP, B036, Day**

Artikelno.: **MX-p25-D036**



**Description:**

IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

EAN:  
**4047438026420**

HS:  
**85258091**

Weight ( incl. packaging):  
**480 g**

Dimensions (l/w/h) in cm:  
**17,5 / 14,0 / 13,5**



## p25 Complete Cam 6MP, B016, Day, Audio Package

Artikelno.: **MX-p25-D016-AUD**



### Description:

Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

EAN:

**4047438026772**

HS:

**85258091**

Weight (incl. packaging):

**480 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5**

**Supplementary Program (SUP)**

The supplementary program encompasses other camera models which include complete sets that are pre-assembled and focus calibrated. This service takes approximately 5 business days. Many products of the supplemental program can be ordered from the standard program as individual components for self-assembly.

**p25 Complete Cam 6MP, B061, Day**

Artikelno.: **MX-p25-D061**



**Description:**

IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, color (day) • Wide lens B061 (focal length 6.1 mm, f/1.8, 60° x 45°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

EAN:

**4047438026444**

HS:

**85258091**

Weight (incl. packaging):

**480 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5**

**p25 Complete Cam 6MP, B079, Day**

Artikelno.: **MX-p25-D079**



**Description:**

IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, color (day) • Standard lens B079 (focal length 7.9 mm, f/1.8, 45° x 34°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

EAN:

**4047438026451**

HS:

**85258091**

Weight (incl. packaging):

**480 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5**

**p25 Complete Cam 6MP, B119, Day**

Artikelno.: **MX-p25-D119**



**Description:**

IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, color (day) • Tele lens B119 (focal length 11.9 mm, f/1.8, 31° x 23°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

EAN:

**4047438026468**

HS:

**85258091**

Weight (incl. packaging):

**480 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5**

**p25 Complete Cam 6MP, B237, Day**

Artikelno.: **MX-p25-D237**



**Description:**

IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, color (day) • Distant Tele lens B237 (focal length 23.7 mm, f/1.8, 15° x 11°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

EAN:

**4047438026475**

HS:

**85258091**

Weight (incl. packaging):

**480 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5**

**p25 Complete Cam 6MP, B016, Night**

Artikelno.: **MX-p25-N016**



**Description:**

Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

EAN:

**4047438026413**

HS:

**85258091**

Weight (incl. packaging):

**480 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5**

**p25 Complete Cam 6MP, B036, Night**

Artikelno.: **MX-p25-N036**



**Description:**

IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra Wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Internal DVR: 4-GB MicroSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

EAN:

**4047438026437**

HS:

**85258091**

Weight (incl. packaging):

**480 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5**

**p25 Complete Cam 6MP, B036, Day, Audio Package**

Artikelno.: **MX-p25-D036-AUD**



**Description:**

IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

EAN:  
**4047438026796**

HS:  
**85258091**

Weight (incl. packaging):  
**480 g**

Dimensions (l/w/h) in cm:  
**17,5 / 14,0 / 13,5**

**p25 Complete Cam 6MP, B016, Night, Audio Package**

Artikelno.: **MX-p25-N016-AUD**



**Description:**

Hemispheric IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

EAN:  
**4047438026789**

HS:  
**85258091**

Weight (incl. packaging):  
**480 g**

Dimensions (l/w/h) in cm:  
**17,5 / 14,0 / 13,5**

**p25 Complete Cam 6MP, B036, Night, Audio Package**

Artikelno.: **MX-p25-N036-AUD**



**Description:**

IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle -5° to -45° • 6 Megapixel Moonlight Sensor, B/W (night) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • 4-GB microSD • HD Audio with integrated microphone and speaker • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Color: white

EAN:  
**4047438026802**

HS:  
**85258091**

Weight (incl. packaging):  
**480 g**

Dimensions (l/w/h) in cm:  
**17,5 / 14,0 / 13,5**

**v25 Body 6MP, Day, White**Artikelno.: **MX-v25-BOD1****Description:**

v25 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Housing color: white

EAN:

**4047438027571**

HS:

**85258091**

Weight (incl. packaging):

**690 g**

Dimensions (l/w/h) in cm:

**20,5 / 19,8 / 12,3****v25 Body 6MP, Day, Black**Artikelno.: **MX-v25-BOD1-b****Description:**

v25 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Housing color: black

EAN:

**4047438027656**

HS:

**85258091**

Weight (incl. packaging):

**690 g**

Dimensions (l/w/h) in cm:

**20,5 / 19,8 / 12,3****v25 Body 6MP, Night, White**Artikelno.: **MX-v25-BOD1-N****Description:**

v25 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Housing color: white

EAN:

**4047438027588**

HS:

**85258091**

Weight (incl. packaging):

**690 g**

Dimensions (l/w/h) in cm:

**20,5 / 19,8 / 12,3****v25 Body 6MP, Night, Black**Artikelno.: **MX-v25-BOD1-N-b****Description:**

v25 camera module (body) with image sensor and lens mount • Lens to be ordered individually (B036 to B237, focal length 3.6 to 23.7 mm, f/1.8) • Manually adjustable lens tilt angle 0° to -90° • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Housing color: black

EAN:

**4047438027663**

HS:

**85258091**

Weight (incl. packaging):

**690 g**

Dimensions (l/w/h) in cm:

**20,5 / 19,8 / 12,3****v25 Complete Cam 6MP, B036, Day, White**Artikelno.: **MX-v25-D036****Description:**

IP indoor camera for ceiling mounting • Manually adjustable lens tilt angle 0° to -90° • 6 Megapixel Moonlight Sensor, color (day) • Ultra wide lens B036 (focal length 3.6 mm, f/1.8, 103° x 77°) • Max. image size: 6MP (3072 x 2048) • IP20, 0 to 40°C (32 to 104°F) • Lens cover with sealing ring (polycarbonate, 1.5 mm) • Internal DVR: 4 GB microSD • Temperature sensor, illumination sensor, movement sensor, MxActivitySensor, MxAnalytics • 0.5 m/1.6 ft Ethernet patch cable • Interfaces: Ethernet 10/100 (RJ45), USB, slot for IO module MX-OPT-IO3-INT • Housing color: white

EAN:

**4047438027649**

HS:

**85258091**

Weight (incl. packaging):

**700 g**

Dimensions (l/w/h) in cm:

**20,5 / 19,8 / 12,3**



## Featuring Thermal Radiometry For Measurable Added Value.

The MOBOTIX TR cameras feature a calibrated thermal image sensor. Thermal radiation measurements made across the entire image area can be used to trigger an event based on the temperature increasing above or decreasing below an individually set trigger level (camera alarm, network message, activation of a signal output etc.).



M16 Thermal	Description	Image Angle horizontal	Focal Length	Aperture
Mx-M16TA-T079	M16 Thermographic camera with 1 thermographic sensor module T079 (45° x 34°)		7.9 mm	f/1.8
Mx-M16TA-T119	M16 Thermographic camera with 1 thermographic sensor module T119 (31° x 23°)		11.9 mm	f/1.8
Mx-M16TA-T237	M16 Thermographic camera with 1 thermographic sensor module T237 (15° x 11°)		23.7 mm	f/1.8

M16 Thermal TR	Description	Image Angle horizontal	Focal Length	Aperture
Mx-M16TA-R079	M16 Thermographic camera with 1 thermographic sensor module and Germanium lens R079 (45° x 34°)		7.9 mm	f/1.8
Mx-M16TA-R119	M16 Thermographic camera with 1 thermographic sensor module and Germanium lens R119 (31° x 23°)		11.9 mm	f/1.8
Mx-M16TA-R237	M16 Thermographic camera with 1 thermographic sensor module and Germanium lens R237 (15° x 11°)		23.7 mm	f/1.8

Thermal

**M16 Thermographic Camera TR, 50 mK, R079 (45°)**Artikelno.: **Mx-M16TA-R079**

Mx6

**Description:**

IP thermographic camera TR with Germanium Lens: B079 equivalent, horizontal/vertical image angle 45°/32° • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), USB; IO and RS232 via additional Interface Box

EAN:

**4047438027823**

HS:

**85258091**

Weight (incl. packaging):

**2.480 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0****M16 Thermographic Camera TR, 50 mK, R119 (25°)**Artikelno.: **Mx-M16TA-R119**

Mx6

**Description:**

IP thermographic camera TR with Germanium Lens: B119 equivalent, horizontal/vertical image angle 25°/19° • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), USB; IO and RS232 via additional Interface Box

EAN:

**4047438027830**

HS:

**85258091**

Weight (incl. packaging):

**2.480 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0****M16 Thermographic Camera TR, 50 mK, R237 (17°)**Artikelno.: **Mx-M16TA-R237**

Mx6

**Description:**

IP thermographic camera TR with Germanium Lens: B237 equivalent, horizontal/vertical image angle 17°/13° • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), USB; IO and RS232 via additional Interface Box

EAN:

**4047438027847**

HS:

**85258091**

Weight (incl. packaging):

**2.480 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0****M16 Thermographic Camera 50 mK, T079 (45°)**Artikelno.: **Mx-M16TA-T079**

Mx6

**Description:**

IP thermographic camera with T079 thermal lens, horizontal/vertical image angle 45°/32°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), USB; IO and RS232 via additional Interface Box

EAN:

**4047438027793**

HS:

**85258091**

Weight (incl. packaging):

**2.460 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0****M16 Thermographic Camera 50 mK, T119 (25°)**Artikelno.: **Mx-M16TA-T119**

Mx6

**Description:**

IP thermographic camera with T119 thermal lens, horizontal/vertical image angle 25°/19°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), USB; IO and RS232 via additional Interface Box

EAN:

**4047438027809**

HS:

**85258091**

Weight (incl. packaging):

**2.460 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**

**M16 Thermographic Camera 50 mK, T237 (17°)**Artikelno.: **Mx-M16TA-T237****Mx6****Description:**

IP thermographic camera with T237 thermal lens, horizontal/vertical image angle 17°/13°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • Mx6 system platform with H.264, MxPEG+ and M-JPEG • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, MxActivitySensor, shock detector • VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), USB; IO and RS232 via additional Interface Box

EAN:

**4047438027816**

HS:

**85258091**

Weight (incl. packaging):

**2.460 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**



**M15 Thermographic Camera TR, 50 mK, B079 (45°)**

 Artikelno.: **MX-M15-TR079**

**Description:**

IP thermographic camera TR with Germanium Lens: B079 equivalent, horizontal/vertical image angle 45°/32° • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional Interface Box

EAN:

**4047438027014**

HS:

**85258091**

Weight (incl. packaging):

**2.480 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**
**M15 Thermographic Camera TR, 50 mK, B119 (25°)**

 Artikelno.: **MX-M15-TR119**

**Description:**

IP thermographic camera TR with Germanium Lens: B119 equivalent, horizontal/vertical image angle 25°/19° • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional Interface Box

EAN:

**4047438027021**

HS:

**85258091**

Weight (incl. packaging):

**2.480 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**
**M15 Thermographic Camera TR, 50 mK, B237 (17°)**

 Artikelno.: **MX-M15-TR237**

**Description:**

IP thermographic camera TR with Germanium Lens: B237 equivalent, horizontal/vertical image angle 17°/13° • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second, 336 x 252 pixels (can be scaled up to 6MP) • Optional optical 6MP sensor module (to be ordered individually) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional Interface Box

EAN:

**4047438027038**

HS:

**85258091**

Weight (incl. packaging):

**2.480 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**
**M15 Thermographic Camera, 50 mK, L43 (45°)**

 Artikelno.: **MX-M15D-Thermal-L43**

**Description:**

IP thermographic camera with L43 thermal lens, horizontal/vertical image angle 45°/32°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional Interface Box

EAN:

**4047438020589**

HS:

**85258091**

Weight (incl. packaging):

**2.460 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**
**M15 Thermographic Camera, 50 mK, L65 (25°)**

 Artikelno.: **MX-M15D-Thermal-L65**

**Description:**

IP thermographic camera with L65 thermal lens, horizontal/vertical image angle 25°/19°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB microSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional Interface Box

EAN:

**4047438020596**

HS:

**85258091**

Weight (incl. packaging):

**2.460 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**



**M15 Thermographic Camera, 50 mK, L135 (17°)**Artikelno.: **MX-M15D-Thermal-L135****Description:**

IP thermographic camera with L135 thermal lens, horizontal/vertical image angle 17°/13°, optional connection of an additional optical 6MP sensor module (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Image size (thermal): 336 x 252 pixels (can be scaled up) • IP66, -30 to 60°C (-22 to 140°F) • Internal DVR: 4 GB MicroSD • System components: speaker and microphone (inside housing), PIR sensor, temperature sensor, shock detector, MxActivitySensor, VarioFlex wall/ceiling mount (can be used with additional pole mount: MX-MH-SecureFlex-ESWS), ethernet patch cable 0.5 m/1.65 ft • Interfaces: Ethernet 10/100 (RJ45), MxBus, USB; IO and RS232 via additional Interface Box

EAN:

**4047438020602**

HS:

**85258091**

Weight (incl. packaging):

**2.460 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 18,0**



## Compact. Clever. Combinable.

The weatherproof interface boxes enable you to easily and cost-effectively expand your security solution. The compact devices require a single installation point which can be located out of sight behind a standard camera wall mount, for example. Data traffic is encrypted at all times - with MxBus via two-wire cables of up to 100 m in length.

**Thermal Sensor Module TR For S16/S15, 50 mK, B079 (45°)**

Artikelno.: **Mx-O-SMA-TS-R079**



**Description:**

Thermal Sensor Module TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B079 equivalent, horizontal/vertical image angle 45°/32° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)

EAN:  
**4047438030090**

HS:  
**90275000**

Weight (incl. packaging):  
**650 g**

Dimensions (l/w/h) in cm:  
**17,5 / 14,0 / 13,5**

**Thermal Sensor Module TR For S16/S15, 50 mK, B119 (25°)**

Artikelno.: **Mx-O-SMA-TS-R119**



**Description:**

Thermal Sensor Module TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B119 equivalent, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)

EAN:  
**4047438030106**

HS:  
**90275000**

Weight (incl. packaging):  
**650 g**

Dimensions (l/w/h) in cm:  
**17,5 / 14,0 / 13,5**

**Thermal Sensor Module TR For S16/S15, 50 mK, B237 (17°)**

Artikelno.: **Mx-O-SMA-TS-R237**



**Description:**

Thermal Sensor Module TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B237 equivalent, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)

EAN:  
**4047438030113**

HS:  
**90275000**

Weight (incl. packaging):  
**650 g**

Dimensions (l/w/h) in cm:  
**17,5 / 14,0 / 13,5**

**PTMount-Thermal TR For S16/S15, 50 mK, B079 (45°), White**

Artikelno.: **Mx-O-SMA-TP-R079**



**Description:**

PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B079 equivalent, horizontal/vertical image angle 45°/32° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White

EAN:  
**4047438030120**

HS:  
**90275000**

Weight (incl. packaging):  
**890 g**

Dimensions (l/w/h) in cm:  
**17,5 / 14,0 / 13,5**

**PTMount-Thermal TR For S16/S15, 50 mK, B119 (25°), White**

Artikelno.: **Mx-O-SMA-TP-R119**



**Description:**

PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B119 equivalent, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White

EAN:  
**4047438030137**

HS:  
**90275000**

Weight (incl. packaging):  
**890 g**

Dimensions (l/w/h) in cm:  
**17,5 / 14,0 / 13,5**

**PTMount-Thermal TR For S16/S15, 50 mK, B237 (17°), White**

Artikelno.: **Mx-O-SMA-TP-R237**



**Description:**

PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550°C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B237 equivalent, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White

EAN:  
**4047438030144**

HS:  
**90275000**

Weight (incl. packaging):  
**890 g**

Dimensions (l/w/h) in cm:  
**17,5 / 14,0 / 13,5**

## PTMount-Thermal TR For S16/S15, 50 mK, B079 (45°), Black

Artikelno.: **Mx-O-SMA-TP-R079-b**



### Description:

PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550 °C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B079 equivalent, horizontal/vertical image angle 45°/32° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black

EAN:

**4047438030151**

HS:

**90275000**

Weight ( incl. packaging):

**890 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5**

## PTMount-Thermal TR For S16/S15, 50 mK, B119 (25°), Black

Artikelno.: **Mx-O-SMA-TP-R119-b**



### Description:

PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550 °C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B119 equivalent, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black

EAN:

**4047438030168**

HS:

**90275000**

Weight ( incl. packaging):

**890 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5**

## PTMount-Thermal TR For S16/S15, 50 mK, B237 (17°), Black

Artikelno.: **Mx-O-SMA-TP-R237-b**



### Description:

PTMount-Thermal TR for the S16/S15 • Thermal radiometry (TR): calibrated thermal sensor for temperature events from -40 to 550 °C (-40 to 1022°F) • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (2 m/6.6 ft, included): B237 equivalent, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black

EAN:

**4047438030175**

HS:

**90275000**

Weight ( incl. packaging):

**890 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5**

## Thermal Sensor Module For S16/S15, 50 mK, B079 (45°)

Artikelno.: **Mx-O-SMA-TS-T079**



### Description:

Suitable for: S16/S15 (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B079, horizontal/vertical image angle 45°/32° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: Black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)

EAN:

**4047438029049**

HS:

**90275000**

Weight ( incl. packaging):

**650 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5**

## Thermal Sensor Module For S16/S15, 50 mK, B119 (25°)

Artikelno.: **Mx-O-SMA-TS-T119**



### Description:

Suitable for: S16/S15 (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B119, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)

EAN:

**4047438029056**

HS:

**90275000**

Weight ( incl. packaging):

**650 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5**

## Thermal Sensor Module For S16/S15, 50 mK, B237 (17°)

Artikelno.: **Mx-O-SMA-TS-T237**



### Description:

Suitable for: S16/S15 (to be ordered individually) • Highly sensitive thermal image sensor: NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B237, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • IP66, -30 to 60°C (-22 to 140°F) • Housing: black anodized aluminum • Camera connection via MOBOTIX sensor cable (max. 3 m/9.8 ft, to be ordered individually)

EAN:

**4047438029063**

HS:

**90275000**

Weight ( incl. packaging):

**650 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5**

**PTMount-Thermal For S16/S15, 50 mK, B079 (45°), White**

Artikelno.: **Mx-O-SMA-TP-T079**



**Description:**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16/S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B079, horizontal/vertical image angle 45°/32° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White

EAN:  
**4047438029070**

HS:  
**90275000**

Weight ( incl. packaging):  
**890 g**

Dimensions (l/w/h) in cm:  
**17,5 / 14,0 / 13,5**

**PTMount-Thermal For S16/S15, 50 mK, B119 (25°), White**

Artikelno.: **Mx-O-SMA-TP-T119**



**Description:**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16/S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B119, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White

EAN:  
**4047438029087**

HS:  
**90275000**

Weight ( incl. packaging):  
**890 g**

Dimensions (l/w/h) in cm:  
**17,5 / 14,0 / 13,5**

**PTMount Thermal For S16/S15, 50 mK, B237 (17°), White**

Artikelno.: **Mx-O-SMA-TP-T237**



**Description:**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16/S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B237, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: White

EAN:  
**4047438029094**

HS:  
**90275000**

Weight ( incl. packaging):  
**890 g**

Dimensions (l/w/h) in cm:  
**17,5 / 14,0 / 13,5**

**PTMount-Thermal For S16, S15, 50 mK, B079 (45°), Black**

Artikelno.: **Mx-O-SMA-TP-T079-b**



**Description:**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16, S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B079, horizontal/vertical image angle 45°/32° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black

EAN:  
**4047438030021**

HS:  
**90275000**

Weight ( incl. packaging):  
**890 g**

Dimensions (l/w/h) in cm:  
**17,5 / 14,0 / 13,5**

**PTMount-Thermal For S16, S15, 50 mK, B119 (25°), Black**

Artikelno.: **Mx-O-SMA-TP-T119-b**



**Description:**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16, S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B119, horizontal/vertical image angle 25°/19° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: Black

EAN:  
**4047438030038**

HS:  
**90275000**

Weight ( incl. packaging):  
**890 g**

Dimensions (l/w/h) in cm:  
**17,5 / 14,0 / 13,5**

**PTMount Thermal For S16, S15, 50 mK, B237 (17°), Black**

Artikelno.: **Mx-O-SMA-TP-T237-b**



**Description:**

PTMount-Thermal with integrated highly sensitive thermal image sensor for the S16, S15 • NETD typ. 50 mK, <79 mK, IR range 7.5 to 13.5 micrometer, uncooled micro bolometer, up to 9 frames per second • Germanium Lens (included): B237, horizontal/vertical image angle 17°/13° • Image size: 336 x 252 pixels (can be scaled up to 6MP) • Operating conditions: IP66, -30 to 60°C (-22 to 140°F) • Camera connection via MOBOTIX sensor cable (2 m/6.6 ft, included) • Color: black

EAN:  
**4047438030045**

HS:  
**90275000**

Weight ( incl. packaging):  
**890 g**

Dimensions (l/w/h) in cm:  
**17,5 / 14,0 / 13,5**

**Sensor Module 6MP, B016 (Day), White**

Artikelno.: **Mx-O-SMA-S-6D016**



Description:

Sensor module S16/M16, S15/M15 with HD premium fisheye lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white

EAN:  
**4047438029100**

HS:  
**90021900**

Weight ( incl. packaging):  
**144 g**

Dimensions (l/w/h) in cm:  
**10,5 / 6,8 / 10,5**

**Sensor Module 6MP, B036 (Day), White**

Artikelno.: **Mx-O-SMA-S-6D036**



Description:

Sensor module S16/M16, S15/M15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white

EAN:  
**4047438029117**

HS:  
**90021900**

Weight ( incl. packaging):  
**144 g**

Dimensions (l/w/h) in cm:  
**10,5 / 6,8 / 10,5**

**Sensor Module 6MP, B041 (Day), White**

Artikelno.: **Mx-O-SMA-S-6D041**



Description:

Sensor module S16/M16, S15/M15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white

EAN:  
**4047438029124**

HS:  
**90021900**

Weight ( incl. packaging):  
**144 g**

Dimensions (l/w/h) in cm:  
**10,5 / 6,8 / 10,5**

**Sensor Module 6MP, B061 (Day), White**

Artikelno.: **Mx-O-SMA-S-6D061**



Description:

Sensor module S16/M16, S15/M15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white

EAN:  
**4047438029131**

HS:  
**90021900**

Weight ( incl. packaging):  
**144 g**

Dimensions (l/w/h) in cm:  
**10,5 / 6,8 / 10,5**

**Sensor Module 6MP, B079 (Day), White**

Artikelno.: **Mx-O-SMA-S-6D079**



Description:

Sensor module S16/M16, S15/M15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white

EAN:  
**4047438029148**

HS:  
**90021900**

Weight ( incl. packaging):  
**144 g**

Dimensions (l/w/h) in cm:  
**10,5 / 6,8 / 10,5**

**Sensor Module 6MP, B119 (Day), White**

Artikelno.: **Mx-O-SMA-S-6D119**



Description:

Sensor module S16/M16, S15/M15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white

EAN:  
**4047438029155**

HS:  
**90021900**

Weight ( incl. packaging):  
**144 g**

Dimensions (l/w/h) in cm:  
**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B237 (Day), White

Artikelno.: **Mx-O-SMA-S-6D237**



**Description:**

Sensor module S16/M16, S15/M15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white

EAN:  
**4047438029162**

HS:  
**90021900**

Weight ( incl. packaging):  
**144 g**

Dimensions (l/w/h) in cm:  
**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B500 (Day), White

Artikelno.: **Mx-O-SMA-S-6D500**



**Description:**

Sensor module S16/M16, S15/M15 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, white

EAN:  
**4047438029179**

HS:  
**90021900**

Weight ( incl. packaging):  
**144 g**

Dimensions (l/w/h) in cm:  
**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, CSVario 4,5-10 mm (Day), White

Artikelno.: **Mx-O-SMA-S-6DCSV**



**Description:**

Sensor module S16/M16, S15/M15 with CSVario Lens B045-100-CS focal length 4.5-10 mm, f/1.6-2.3, 39°-89° x 29°-65° • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 60°C / -22 to 140°F (only with lens protection cap), white

EAN:  
**4047438030052**

HS:  
**90021900**

Weight ( incl. packaging):  
**190 g**

Dimensions (l/w/h) in cm:  
**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, CS-Mount (Day), White

Artikelno.: **Mx-O-SMA-S-6DCS**



**Description:**

Sensor module S16/M16, S15/M15 for standard lenses with CS mount (e.g., for Vario lens MX-B045-100-CS) • 6 Megapixel Moonlight Sensor, color (day) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 60°C / -22 to 140°F (only with lens protection cap), white

EAN:  
**4047438030076**

HS:  
**90021900**

Weight ( incl. packaging):  
**146 g**

Dimensions (l/w/h) in cm:  
**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B016 (Night), White

Artikelno.: **Mx-O-SMA-S-6N016**



**Description:**

Sensor module S16/M16, S15/M15 with HD premium fisheye lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white

EAN:  
**4047438029186**

HS:  
**90021900**

Weight ( incl. packaging):  
**144 g**

Dimensions (l/w/h) in cm:  
**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B036 (Night), White

Artikelno.: **Mx-O-SMA-S-6N036**



**Description:**

Sensor module S16/M16, S15/M15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white

EAN:  
**4047438029193**

HS:  
**90021900**

Weight ( incl. packaging):  
**144 g**

Dimensions (l/w/h) in cm:  
**10,5 / 6,8 / 10,5**



## Sensor Module 6MP, B041 (Night), White

Artikelno.: **Mx-O-SMA-S-6N041**



**Description:**

Sensor module S16/M16, S15/M15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white

EAN:

**4047438029209**

HS:

**90021900**

Weight ( incl. packaging):

**144 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B061 (Night), White

Artikelno.: **Mx-O-SMA-S-6N061**



**Description:**

Sensor module S16/M16, S15/M15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white

EAN:

**4047438029216**

HS:

**90021900**

Weight ( incl. packaging):

**144 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B079 (Night), White

Artikelno.: **Mx-O-SMA-S-6N079**



**Description:**

Sensor module S16/M16, S15/M15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white

EAN:

**4047438029223**

HS:

**90021900**

Weight ( incl. packaging):

**144 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B119 (Night), White

Artikelno.: **Mx-O-SMA-S-6N119**



**Description:**

Sensor module S16/M16, S15/M15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white

EAN:

**4047438029230**

HS:

**90021900**

Weight ( incl. packaging):

**144 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B237 (Night), White

Artikelno.: **Mx-O-SMA-S-6N237**



**Description:**

Sensor module S16/M16, S15/M15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white

EAN:

**4047438029247**

HS:

**90021900**

Weight ( incl. packaging):

**144 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B500 (Night), White

Artikelno.: **Mx-O-SMA-S-6N500**



**Description:**

Sensor module S16/M16, S15/M15 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, white

EAN:

**4047438029254**

HS:

**90021900**

Weight ( incl. packaging):

**144 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5**



## Sensor Module 6MP, CSVario 4,5-10 mm (Night), White

Artikelno.: **Mx-O-SMA-S-6NCSV**



### Description:

Sensor module S16/M16, S15/M15 with CSVario Lens B045-100-CS (focal length 4.5-10 mm, f/1.6-2.3, 39°-89° x 29°-65°) • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 60°C / -22 to 140°F (only with lens protection cap), white

EAN:  
**4047438030069**

HS:  
**90021900**

Weight ( incl. packaging):  
**190 g**

Dimensions (l/w/h) in cm:  
**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, CS-Mount (Night), White

Artikelno.: **Mx-O-SMA-S-6NCS**



### Description:

Sensor module S16/M16, S15/M15 for standard lenses with CS mount (e.g., for Vario lens MX-B045-100-CS) • 6 Megapixel Moonlight Sensor, B/W (night) • Max. image size: 6MP (3072 x 2048) • IP66, -30 to 60°C / -22 to 140°F (only with lens protection cap), white

EAN:  
**4047438030083**

HS:  
**90021900**

Weight ( incl. packaging):  
**146 g**

Dimensions (l/w/h) in cm:  
**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B016 (Night LPF), White

Artikelno.: **Mx-O-SMA-S-6L016**



### Description:

Sensor module S16/M16, S15/M15 with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white

EAN:  
**4047438029261**

HS:  
**90021900**

Weight ( incl. packaging):  
**144 g**

Dimensions (l/w/h) in cm:  
**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B036 (Night LPF), White

Artikelno.: **Mx-O-SMA-S-6L036**



### Description:

Sensor module S16/M16, S15/M15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white

EAN:  
**4047438029278**

HS:  
**90021900**

Weight ( incl. packaging):  
**144 g**

Dimensions (l/w/h) in cm:  
**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B041 (Night LPF), White

Artikelno.: **Mx-O-SMA-S-6L041**



### Description:

Sensor module S16/M16, S15/M15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white

EAN:  
**4047438029285**

HS:  
**90021900**

Weight ( incl. packaging):  
**144 g**

Dimensions (l/w/h) in cm:  
**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B061 (Night LPF), White

Artikelno.: **Mx-O-SMA-S-6L061**



### Description:

Sensor module S16/M16, S15/M15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white

EAN:  
**4047438029292**

HS:  
**90021900**

Weight ( incl. packaging):  
**144 g**

Dimensions (l/w/h) in cm:  
**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B079 (Night LPF), White

Artikelno.: **Mx-O-SMA-S-6L079**



### Description:

Sensor module S16/M16, S15/M15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white

EAN:

**4047438029308**

HS:

**90021900**

Weight (incl. packaging):

**144 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B119 (Night LPF), White

Artikelno.: **Mx-O-SMA-S-6L119**



### Description:

Sensor module S16/M16, S15/M15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white

EAN:

**4047438029315**

HS:

**90021900**

Weight (incl. packaging):

**144 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B237 (Night LPF), White

Artikelno.: **Mx-O-SMA-S-6L237**



### Description:

Sensor module S16/M16, S15/M15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white

EAN:

**4047438029322**

HS:

**90021900**

Weight (incl. packaging):

**144 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B500 (Night LPF), White

Artikelno.: **Mx-O-SMA-S-6L500**



### Description:

Sensor module S16/M16, S15/M15 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, white

EAN:

**4047438029339**

HS:

**90021900**

Weight (incl. packaging):

**144 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B016 (Day), Black

Artikelno.: **Mx-O-SMA-S-6D016-b**



### Description:

Sensor module S16/M16, S15/M15 with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black

EAN:

**4047438029346**

HS:

**90021900**

Weight (incl. packaging):

**144 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B036 (Day), Black

Artikelno.: **Mx-O-SMA-S-6D036-b**



### Description:

Sensor module S16/M16, S15/M15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black

EAN:

**4047438029353**

HS:

**90021900**

Weight (incl. packaging):

**144 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B041 (Day), Black

Artikelno.: **Mx-O-SMA-S-6D041-b**



**Description:**

Sensor module S16/M16, S15/M15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black

EAN:  
**4047438029360**

HS:  
**90021900**

Weight ( incl. packaging):  
**144 g**

Dimensions (l/w/h) in cm:  
**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B061 (Day), Black

Artikelno.: **Mx-O-SMA-S-6D061-b**



**Description:**

Sensor module S16/M16, S15/M15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black

EAN:  
**4047438029377**

HS:  
**90021900**

Weight ( incl. packaging):  
**144 g**

Dimensions (l/w/h) in cm:  
**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B079 (Day), Black

Artikelno.: **Mx-O-SMA-S-6D079-b**



**Description:**

Sensor module S16/M16, S15/M15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black

EAN:  
**4047438029384**

HS:  
**90021900**

Weight ( incl. packaging):  
**144 g**

Dimensions (l/w/h) in cm:  
**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B119 (Day), Black

Artikelno.: **Mx-O-SMA-S-6D119-b**



**Description:**

Sensor module S16/M16, S15/M15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black

EAN:  
**4047438029391**

HS:  
**90021900**

Weight ( incl. packaging):  
**144 g**

Dimensions (l/w/h) in cm:  
**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B237 (Day), Black

Artikelno.: **Mx-O-SMA-S-6D237-b**



**Description:**

Sensor module S16/M16, S15/M15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black

EAN:  
**4047438029407**

HS:  
**90021900**

Weight ( incl. packaging):  
**144 g**

Dimensions (l/w/h) in cm:  
**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B500 (Day), Black

Artikelno.: **Mx-O-SMA-S-6D500-b**



**Description:**

Sensor module S16/M16, S15/M15 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor day, 6MP (3072 x 2048), IP66, black

EAN:  
**4047438029414**

HS:  
**90021900**

Weight ( incl. packaging):  
**144 g**

Dimensions (l/w/h) in cm:  
**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B016 (Night), Black

Artikelno.: **Mx-O-SMA-S-6N016-b**



**Description:**

Sensor module S16/M16, S15/M15 with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black

EAN:

**4047438029421**

HS:

**90021900**

Weight ( incl. packaging):

**144 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B036 (Night), Black

Artikelno.: **Mx-O-SMA-S-6N036-b**



**Description:**

Sensor module S16/M16, S15/M15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black

EAN:

**4047438029438**

HS:

**90021900**

Weight ( incl. packaging):

**144 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B041 (Night), Black

Artikelno.: **Mx-O-SMA-S-6N041-b**



**Description:**

Sensor module S16/M16, S15/M15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black

EAN:

**4047438029445**

HS:

**90021900**

Weight ( incl. packaging):

**144 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B061 (Night), Black

Artikelno.: **Mx-O-SMA-S-6N061-b**



**Description:**

Sensor module S16/M16, S15/M15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black

EAN:

**4047438029452**

HS:

**90021900**

Weight ( incl. packaging):

**144 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B079 (Night), Black

Artikelno.: **Mx-O-SMA-S-6N079-b**



**Description:**

Sensor module S16/M16, S15/M15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black

EAN:

**4047438029469**

HS:

**90021900**

Weight ( incl. packaging):

**144 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B119 (Night), Black

Artikelno.: **Mx-O-SMA-S-6N119-b**



**Description:**

Sensor module S16/M16, S15/M15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black

EAN:

**4047438029476**

HS:

**90021900**

Weight ( incl. packaging):

**144 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B237 (Night), Black

Artikelno.: **Mx-O-SMA-S-6N237-b**



**Description:**

Sensor module S16/M16, S15/M15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black

EAN:  
**4047438029483**

HS:  
**90021900**

Weight ( incl. packaging):  
**144 g**

Dimensions (l/w/h) in cm:  
**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B500 (Night), Black

Artikelno.: **Mx-O-SMA-S-6N500-b**



**Description:**

Sensor module S16/M16, S15/M15 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), IP66, black

EAN:  
**4047438029490**

HS:  
**90021900**

Weight ( incl. packaging):  
**144 g**

Dimensions (l/w/h) in cm:  
**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B016 (Night LPF), Black

Artikelno.: **Mx-O-SMA-S-6L016-b**



**Description:**

Sensor module S16/M16, S15/M15 with HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black

EAN:  
**4047438029506**

HS:  
**90021900**

Weight ( incl. packaging):  
**144 g**

Dimensions (l/w/h) in cm:  
**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B036 (Night LPF), Black

Artikelno.: **Mx-O-SMA-S-6L036-b**



**Description:**

Sensor module S16/M16, S15/M15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black

EAN:  
**4047438029513**

HS:  
**90021900**

Weight ( incl. packaging):  
**144 g**

Dimensions (l/w/h) in cm:  
**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B041 (Night LPF), Black

Artikelno.: **Mx-O-SMA-S-6L041-b**



**Description:**

Sensor module S16/M16, S15/M15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black

EAN:  
**4047438029520**

HS:  
**90021900**

Weight ( incl. packaging):  
**144 g**

Dimensions (l/w/h) in cm:  
**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B061 (Night LPF), Black

Artikelno.: **Mx-O-SMA-S-6L061-b**



**Description:**

Sensor module S16/M16, S15/M15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black

EAN:  
**4047438029537**

HS:  
**90021900**

Weight ( incl. packaging):  
**144 g**

Dimensions (l/w/h) in cm:  
**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B079 (Night LPF), Black

Artikelno.: **Mx-O-SMA-S-6L079-b**



### Description:

Sensor module S16/M16, S15/M15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black

EAN:

**4047438029544**

HS:

**90021900**

Weight (incl. packaging):

**144 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B119 (Night LPF), Black

Artikelno.: **Mx-O-SMA-S-6L119-b**



### Description:

Sensor module S16/M16, S15/M15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black

EAN:

**4047438029551**

HS:

**90021900**

Weight (incl. packaging):

**144 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B237 (Night LPF), Black

Artikelno.: **Mx-O-SMA-S-6L237-b**



### Description:

Sensor module S16/M16, S15/M15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black

EAN:

**4047438029568**

HS:

**90021900**

Weight (incl. packaging):

**144 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5**

## Sensor Module 6MP, B500 (Night LPF), Black

Artikelno.: **Mx-O-SMA-S-6L500-b**



### Description:

Sensor module S16/M16, S15/M15 with HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared), IP66, black

EAN:

**4047438029575**

HS:

**90021900**

Weight (incl. packaging):

**144 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5**

**BlockFlexMount 6MP, Incl. Hemispheric B016 (Day)**

Artikelno.: **Mx-O-SMA-B-6D016**



**Description:**

Suitable for: S16, S15 • HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

EAN:  
**4047438029797**

HS:  
**90021900**

Weight (incl. packaging):  
**155 g**

Dimensions (l/w/h) in cm:  
**10,7 / 5,2 / 8,7**

**BlockFlexMount 6MP, Incl. B036 (Day)**

Artikelno.: **Mx-O-SMA-B-6D036**



**Description:**

Suitable for: S16, S15 • HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

EAN:  
**4047438029803**

HS:  
**90021900**

Weight (incl. packaging):  
**155 g**

Dimensions (l/w/h) in cm:  
**10,7 / 5,2 / 8,7**

**BlockFlexMount 6MP, Incl. B041 (Day)**

Artikelno.: **Mx-O-SMA-B-6D041**



**Description:**

Suitable for: S16, S15 • HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

EAN:  
**4047438029810**

HS:  
**90021900**

Weight (incl. packaging):  
**155 g**

Dimensions (l/w/h) in cm:  
**10,7 / 5,2 / 8,7**

**BlockFlexMount 6MP, Incl. B061 (Day)**

Artikelno.: **Mx-O-SMA-B-6D061**



**Description:**

Suitable for: S16, S15 • HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

EAN:  
**4047438029827**

HS:  
**90021900**

Weight (incl. packaging):  
**155 g**

Dimensions (l/w/h) in cm:  
**10,7 / 5,2 / 8,7**

**BlockFlexMount 6MP, Incl. B079 (Day)**

Artikelno.: **Mx-O-SMA-B-6D079**



**Description:**

Suitable for: S16, S15 • HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

EAN:  
**4047438029834**

HS:  
**90021900**

Weight (incl. packaging):  
**155 g**

Dimensions (l/w/h) in cm:  
**10,7 / 5,2 / 8,7**

**BlockFlexMount 6MP, Incl. B119 (Day)**

Artikelno.: **Mx-O-SMA-B-6D119**



**Description:**

Suitable for: S16, S15 • HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

EAN:  
**4047438029841**

HS:  
**90021900**

Weight (incl. packaging):  
**155 g**

Dimensions (l/w/h) in cm:  
**10,7 / 5,2 / 8,7**



## BlockFlexMount 6MP, Incl. B237 (Day)

Artikelno.: **Mx-O-SMA-B-6D237**



### Description:

Suitable for: S16, S15 • HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

EAN:

**4047438029858**

HS:

**90021900**

Weight (incl. packaging):

**155 g**

Dimensions (l/w/h) in cm:

**10,7 / 5,2 / 8,7**

## BlockFlexMount 6MP, incl. B500 (Day)

Artikelno.: **Mx-O-SMA-B-6D500**



### Description:

Suitable for: S16, S15 • HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

EAN:

**4047438029865**

HS:

**90021900**

Weight (incl. packaging):


**155 g**

Dimensions (l/w/h) in cm:

**10,7 / 5,2 / 8,7**

## BlockFlexMount 6MP, For CS Mount Lens (Day)

Artikelno.: **Mx-O-SMA-B-6DCS**



### Description:

Suitable for: S16, S15 • For standard lenses with CS mount (e.g., MX-B045-100-CS), Moonlight sensor day, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

EAN:

**4047438029766**

HS:

**90021900**

Weight (incl. packaging):


**155 g**

Dimensions (l/w/h) in cm:

**10,7 / 5,2 / 8,7**

## BlockFlexMount 6MP, Incl. Hemispheric B016 (Night)

Artikelno.: **Mx-O-SMA-B-6N016**



### Description:

Suitable for: S16, S15 • HD premium lens B016 (f/2.0, horiz. image angle 180°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

EAN:

**4047438029872**

HS:

**90021900**

Weight (incl. packaging):

**155 g**

Dimensions (l/w/h) in cm:

**10,7 / 5,2 / 8,7**

## BlockFlexMount 6MP, Incl. B036 (Night)

Artikelno.: **Mx-O-SMA-B-6N036**



### Description:

Suitable for: S16, S15 • HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

EAN:

**4047438029889**

HS:

**90021900**

Weight (incl. packaging):

**155 g**

Dimensions (l/w/h) in cm:

**10,7 / 5,2 / 8,7**

## BlockFlexMount 6MP, Incl. B041 (Night)

Artikelno.: **Mx-O-SMA-B-6N041**



### Description:

Suitable for: S16, S15 • HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

EAN:

**4047438029896**

HS:

**90021900**

Weight (incl. packaging):

**155 g**

Dimensions (l/w/h) in cm:

**10,7 / 5,2 / 8,7**



## BlockFlexMount 6MP, Incl. B061 (Night)

Artikelno.: **Mx-O-SMA-B-6N061**



### Description:

Suitable for: S16, S15 • HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

EAN:  
**4047438029902**

HS:  
**90021900**

Weight (incl. packaging):  
**155 g**

Dimensions (l/w/h) in cm:  
**10,7 / 5,2 / 8,7**

## BlockFlexMount 6MP, Incl. B079 (Night)

Artikelno.: **Mx-O-SMA-B-6N079**



### Description:

Suitable for: S16, S15 • HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

EAN:  
**4047438029919**

HS:  
**90021900**

Weight (incl. packaging):  
**155 g**

Dimensions (l/w/h) in cm:  
**10,7 / 5,2 / 8,7**

## BlockFlexMount 6MP, Incl. B119 (Night)

Artikelno.: **Mx-O-SMA-B-6N119**



### Description:

Suitable for: S16, S15 • HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

EAN:  
**4047438029926**

HS:  
**90021900**

Weight (incl. packaging):  
**155 g**

Dimensions (l/w/h) in cm:  
**10,7 / 5,2 / 8,7**

## BlockFlexMount 6MP, Incl. B237 (Night)

Artikelno.: **Mx-O-SMA-B-6N237**



### Description:

Suitable for: S16, S15 • HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

EAN:  
**4047438029933**

HS:  
**90021900**

Weight (incl. packaging):  
**155 g**

Dimensions (l/w/h) in cm:  
**10,7 / 5,2 / 8,7**

## BlockFlexMount 6MP, Incl. B500 (Night)

Artikelno.: **Mx-O-SMA-B-6N500**



### Description:

Suitable for: S16, S15 • HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

EAN:  
**4047438029940**


HS:  
**90021900**

Weight (incl. packaging):  
**155 g**

Dimensions (l/w/h) in cm:  
**10,7 / 5,2 / 8,7**

## BlockFlexMount 6MP, For CS Mount Lens (Night)

Artikelno.: **Mx-O-SMA-B-6NCS**



### Description:

Suitable for: S16, S15 • For standard lenses with CS mount (e.g., MX-B045-100-CS), Moonlight sensor night, 6MP (3072 x 2048) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

EAN:  
**4047438029773**

HS:  
**90021900**

Weight (incl. packaging):  
**155 g**

Dimensions (l/w/h) in cm:  
**10,7 / 5,2 / 8,7**

**BlockFlexMount 6MP, Incl. B036 (Night LPF)**Artikelno.: **Mx-O-SMA-B-6L036****Description:**

Suitable for: S16, S15 • HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

EAN:

**4047438029957**

HS:

**90021900**

Weight (incl. packaging):

**155 g**

Dimensions (l/w/h) in cm:

**10,7 / 5,2 / 8,7****BlockFlexMount 6MP, Incl. B041 (Night LPF)**Artikelno.: **Mx-O-SMA-B-6L041****Description:**

Suitable for: S16, S15 • HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

EAN:

**4047438029964**

HS:

**90021900**

Weight (incl. packaging):

**155 g**

Dimensions (l/w/h) in cm:

**10,7 / 5,2 / 8,7****BlockFlexMount 6MP, Incl. B061 (Night LPF)**Artikelno.: **Mx-O-SMA-B-6L061****Description:**

Suitable for: S16, S15 • HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

EAN:

**4047438029971**

HS:

**90021900**

Weight (incl. packaging):

**155 g**

Dimensions (l/w/h) in cm:

**10,7 / 5,2 / 8,7****BlockFlexMount 6MP, Incl. B079 (Night LPF)**Artikelno.: **Mx-O-SMA-B-6L079****Description:**

Suitable for: S16, S15 • HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

EAN:

**4047438029988**

HS:

**90021900**

Weight (incl. packaging):

**155 g**

Dimensions (l/w/h) in cm:

**10,7 / 5,2 / 8,7****BlockFlexMount 6MP, Incl. B119 (Night LPF)**Artikelno.: **Mx-O-SMA-B-6L119****Description:**

Suitable for: S16, S15 • HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

EAN:

**4047438029995**

HS:

**90021900**

Weight (incl. packaging):

**155 g**

Dimensions (l/w/h) in cm:

**10,7 / 5,2 / 8,7****BlockFlexMount 6MP, Incl. B237 (Night LPF)**Artikelno.: **Mx-O-SMA-B-6L237****Description:**

Suitable for: S16, S15 • HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

EAN:

**4047438030007**

HS:

**90021900**

Weight (incl. packaging):

**155 g**

Dimensions (l/w/h) in cm:

**10,7 / 5,2 / 8,7**

## BlockFlexMount 6MP, Incl. B500 (Night LPF)

Artikelno.: **Mx-O-SMA-B-6L500**



### Description:

Suitable for: S16, S15 • HD premium lens B500 (f/2.5, horiz. image angle 8°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

EAN:

**4047438030014**

HS:

**90021900**

Weight (incl. packaging):


**155 g**

Dimensions (l/w/h) in cm:

**10,7 / 5,2 / 8,7**

## BlockFlexMount 6MP, For CS Mount Lens (Night LPF)

Artikelno.: **Mx-O-SMA-B-6LCS**



### Description:

Suitable for: S16, S15 • For standard lenses with CS mount (e.g., MX-B045-100-CS), Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared) • Operating conditions: IP30, 0 to 50°C (32 to 122°F) • Integrated microphone and status LEDs • Camera connection via MOBOTIX sensor cable (to be ordered individually)

EAN:

**4047438029780**

HS:

**90021900**

Weight (incl. packaging):

**155 g**

Dimensions (l/w/h) in cm:

**10,7 / 5,2 / 8,7**

**Sensor Bridge FIX For D16/D15, 2x 6MP (Day & Night)**

Artikelno.: **Mx-O-SDA-F-6D6N**



Description:

Day & Night sensor bridge für D16/D15 Body, including two parallel aligned 6MP sensors (1x Day, 1x Night) and a XL cover (MX-D15-DCT-XL) • Lenses not included (two lenses B036 to B237 possible, to be ordered separately)

EAN:  
**4047438030182**

HS:  
**90021900**

Weight ( incl. packaging):  
**351 g**

Dimensions (l/w/h) in cm:  
**19,6 / 18,0 / 14,8**

**Sensor Bridge PAN/180° For D16/D15, 2x 6MP (Day)**

Artikelno.: **Mx-O-SDA-P-6D6D**



Description:

Panorama/180° sensor bridge for D16/D15 Body, including two day sensors 6MP and a XL cover (MX-D15-DCT-XL) • Lenses not included (two lenses B041 needed for 180° panoramic image, to be ordered separately)

EAN:  
**4047438030199**

HS:  
**90021900**

Weight ( incl. packaging):  
**346 g**

Dimensions (l/w/h) in cm:  
**19,6 / 18,0 / 14,8**

**Sensor Bridge PAN-N/180° for D16/D15, 2x 6MP (Night)**

Artikelno.: **Mx-O-SDA-P-6N6N**



Description:

Panorama/180° sensor bridge for D16/D15 Body, including two night sensors 6MP and a XL cover (MX-D15-DCT-XL) • Lenses not included (two lenses B041 needed for 180° panoramic image, to be ordered separately)

EAN:  
**4047438030205**

HS:  
**90021900**

Weight ( incl. packaging):  
**346 g**

Dimensions (l/w/h) in cm:  
**19,6 / 18,0 / 14,8**

**Sensor Module D16/D15 6MP, Incl. B036 (Day)**

Artikelno.: **Mx-O-SDA-S-6D036**



Description:

Sensor module D16/D15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048)

EAN:  
**4047438029582**

HS:  
**90021900**

Weight ( incl. packaging):  
**64 g**

Dimensions (l/w/h) in cm:  
**7,5 / 4,9 / 9,0**

**Sensor Module D16/D15 6MP, Incl. B041 (Day)**

Artikelno.: **Mx-O-SDA-S-6D041**



Description:

Sensor module D16/D15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor day, 6MP (3072 x 2048)

EAN:  
**4047438029599**

HS:  
**90021900**

Weight ( incl. packaging):  
**64 g**

Dimensions (l/w/h) in cm:  
**7,5 / 4,9 / 9,0**

**Sensor Module D16/D15 6MP, Incl. B061 (Day)**

Artikelno.: **Mx-O-SDA-S-6D061**



Description:

Sensor module D16/D15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor day, 6MP (3072 x 2048)

EAN:  
**4047438029605**

HS:  
**90021900**

Weight ( incl. packaging):  
**64 g**

Dimensions (l/w/h) in cm:  
**7,5 / 4,9 / 9,0**

## Sensor Module D16/D15 6MP, Incl. B079 (Day)

Artikelno.: **Mx-O-SDA-S-6D079**

6MP  
Sensor



Description:

Sensor module D16/D15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor day, 6MP (3072 x 2048)

EAN:

**4047438029612**

HS:

**90021900**

Weight ( incl. packaging):

**64 g**

Dimensions (l/w/h) in cm:

**7,5 / 4,9 / 9,0**

## Sensor Module D16/D15 6MP, Incl. B119 (Day)

Artikelno.: **Mx-O-SDA-S-6D119**

6MP  
Sensor



Description:

Sensor module D16/D15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor day, 6MP (3072 x 2048)

EAN:

**4047438029629**

HS:

**90021900**

Weight ( incl. packaging):

**64 g**

Dimensions (l/w/h) in cm:

**7,5 / 4,9 / 9,0**

## Sensor Module D16/D15 6MP, Incl. B237 (Day)

Artikelno.: **Mx-O-SDA-S-6D237**

6MP  
Sensor



Description:

Sensor module D16/D15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor day, 6MP (3072 x 2048)

EAN:

**4047438029636**

HS:

**90021900**

Weight ( incl. packaging):

**64 g**

Dimensions (l/w/h) in cm:

**7,5 / 4,9 / 9,0**

## Sensor Module D16/D15 6MP, Incl. B036 (Night)

Artikelno.: **Mx-O-SDA-S-6N036**

6MP  
Sensor



Description:

Sensor module D16/D15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor day, 6MP (3072 x 2048)

EAN:

**4047438029643**

HS:

**90021900**

Weight ( incl. packaging):

**64 g**

Dimensions (l/w/h) in cm:

**7,5 / 4,9 / 9,0**

## Sensor Module D16/D15 6MP, Incl. B041 (Night)

Artikelno.: **Mx-O-SDA-S-6N041**

6MP  
Sensor



Description:

Sensor module D16/D15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048)

EAN:

**4047438029650**

HS:

**90021900**

Weight ( incl. packaging):

**64 g**

Dimensions (l/w/h) in cm:

**7,5 / 4,9 / 9,0**

## Sensor Module D16/D15 6MP, Incl. B061 (Night)

Artikelno.: **Mx-O-SDA-S-6N061**

6MP  
Sensor



Description:

Sensor module D16/D15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048)

EAN:

**4047438029667**

HS:

**90021900**

Weight ( incl. packaging):

**64 g**

Dimensions (l/w/h) in cm:

**7,5 / 4,9 / 9,0**

## Sensor Module D16/D15 6MP, Incl. B079 (Night)

Artikelno.: **Mx-O-SDA-S-6N079**

6MP  
Sensor



**Description:**

Sensor module D16/D15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048)

EAN:

**4047438029674**

HS:

**90021900**

Weight ( incl. packaging):

**64 g**

Dimensions (l/w/h) in cm:

**7,5 / 4,9 / 9,0**

## Sensor Module D16/D15 6MP, Incl. B119 (Night)

Artikelno.: **Mx-O-SDA-S-6N119**

6MP  
Sensor



**Description:**

Sensor module D16/D15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048)

EAN:

**4047438029681**

HS:

**90021900**

Weight ( incl. packaging):

**64 g**

Dimensions (l/w/h) in cm:

**7,5 / 4,9 / 9,0**

## Sensor Module D16/D15 6MP, Incl. B237 (Night)

Artikelno.: **Mx-O-SDA-S-6N237**

6MP  
Sensor



**Description:**

Sensor module D16/D15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048)

EAN:

**4047438029698**

HS:

**90021900**

Weight ( incl. packaging):

**64 g**

Dimensions (l/w/h) in cm:

**7,5 / 4,9 / 9,0**

## Sensor Module D16/D15 6MP, Incl. B036 (Night LPF)

Artikelno.: **Mx-O-SDA-S-6L036**

6MP  
Sensor



**Description:**

Sensor module D16/D15 with HD premium lens B036 (f/1.8, horiz. image angle 103°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)

EAN:

**4047438029704**

HS:

**90021900**

Weight ( incl. packaging):

**64 g**

Dimensions (l/w/h) in cm:

**7,5 / 4,9 / 9,0**

## Sensor Module D16/D15 6MP, Incl. B041 (Night LPF)

Artikelno.: **Mx-O-SDA-S-6L041**

6MP  
Sensor



**Description:**

Sensor module D16/D15 with HD premium lens B041 (f/1.8, horiz. image angle 90°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)

EAN:

**4047438029711**

HS:

**90021900**

Weight ( incl. packaging):

**64 g**

Dimensions (l/w/h) in cm:

**7,5 / 4,9 / 9,0**

## Sensor Module D16/D15 6MP, Incl. B061 (Night LPF)

Artikelno.: **Mx-O-SDA-S-6L061**

6MP  
Sensor



**Description:**

Sensor module D16/D15 with HD premium lens B061 (f/1.8, horiz. image angle 60°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)

EAN:

**4047438029728**

HS:

**90021900**

Weight ( incl. packaging):

**64 g**

Dimensions (l/w/h) in cm:

**7,5 / 4,9 / 9,0**

## Sensor Module D16/D15 6MP, Incl. B079 (Night LPF)

Artikelno.: **Mx-O-SDA-S-6L079**

6MP  
Sensor



### Description:

Sensor module D16/D15 with HD premium lens B079 (f/1.8, horiz. image angle 45°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)

EAN:  
**4047438029735**

HS:  
**90021900**

Weight (incl. packaging):  
**64 g**

Dimensions (l/w/h) in cm:  
**7,5 / 4,9 / 9,0**

## Sensor Module D16/D15 6MP, Incl. B119 (Night LPF)

Artikelno.: **Mx-O-SDA-S-6L119**

6MP  
Sensor



### Description:

Sensor module D16/D15 with HD premium lens B119 (f/1.8, horiz. image angle 31°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)

EAN:  
**4047438029742**

HS:  
**90021900**

Weight (incl. packaging):  
**64 g**

Dimensions (l/w/h) in cm:  
**7,5 / 4,9 / 9,0**

## Sensor Module D16/D15 6MP, Incl. B237 (Night LPF)

Artikelno.: **Mx-O-SDA-S-6L237**

6MP  
Sensor



### Description:

Sensor module D16/D15 with HD premium lens B237 (f/1.8, horiz. image angle 15°) and Moonlight sensor night, 6MP (3072 x 2048), LPF special lens, e.g., for license plate detection (with infrared)

EAN:  
**4047438029759**

HS:  
**90021900**

Weight (incl. packaging):  
**64 g**

Dimensions (l/w/h) in cm:  
**7,5 / 4,9 / 9,0**

**Ultra Wide Lens B036, Focal Length: 3.6 mm**

Artikelno.: **MX-B036**



**Description:**

Ultra Wide lens B036 • HD premium quality • Focal length: 3.6 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 103° x 77° (up to 5MP resolution) and 122° x 80° (6MP resolution)

EAN:  
**4047438026536**

HS:  
**90021900**

Weight (incl. packaging):  
**30 g**

Dimensions (l/w/h) in cm:  
**7,5 / 4,9 / 9,0**

**Super Wide Lens B041, Focal Length: 4.1 mm**

Artikelno.: **MX-B041**



**Description:**

Super Wide lens B041 • HD premium quality • Focal length: 4.1 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 90° x 67° (up to 5MP resolution) and 110° x 70° (6MP resolution)

EAN:  
**4047438026543**

HS:  
**90021900**

Weight (incl. packaging):  
**34 g**

Dimensions (l/w/h) in cm:  
**7,5 / 4,9 / 9,0**

**Wide Lens B061, Focal Length: 6.1 mm**

Artikelno.: **MX-B061**



**Description:**

Wide lens B061 • HD premium quality • Focal length: 6.1 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 60° x 45° (up to 5MP resolution) and 70.5° x 46° (6MP resolution)

EAN:  
**4047438026550**

HS:  
**90021900**

Weight (incl. packaging):  
**30 g**

Dimensions (l/w/h) in cm:  
**7,5 / 4,9 / 9,0**

**Standard Lens B079, Focal Length: 7.9 mm**

Artikelno.: **MX-B079**



**Description:**

Standard lens B079 • HD premium quality • Focal length: 7.9 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 45° x 34° (up to 5MP resolution) and 54° x 36° (6MP resolution)

EAN:  
**4047438026567**


HS:  
**90021900**

Weight (incl. packaging):  
**35 g**

Dimensions (l/w/h) in cm:  
**7,5 / 4,9 / 9,0**

**Tele Lens B119, Focal Length: 11.9 mm**

Artikelno.: **MX-B119**



**Description:**

Tele lens B119 • HD premium quality • Focal length: 11.9 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 31° x 23° (up to 5MP resolution) and 36° x 24.5° (6MP resolution)

EAN:  
**4047438026574**

HS:  
**90021900**

Weight (incl. packaging):  
**30 g**

Dimensions (l/w/h) in cm:  
**7,5 / 4,9 / 9,0**

**Distant Tele Lens B237, Focal Length: 23.7 mm**

Artikelno.: **MX-B237**



**Description:**

Distant Tele lens B237 • HD premium quality • Focal length: 23.7 mm • Aperture: f/1.8 • Image angle (horizontal x vertical, on camera with 6MP sensor): 15° x 11° (up to 5MP resolution) and 17° x 11.5° (6MP resolution)

EAN:  
**4047438026581**

HS:  
**90021900**

Weight (incl. packaging):  
**30 g**

Dimensions (l/w/h) in cm:  
**7,5 / 4,9 / 9,0**



## Super Tele Lens B500, Focal Length: 50 mm

Artikelno.: **MX-B500**



**Description:**

Super Tele lens B500 • HD premium quality • Focal length: 50 mm • Aperture: f/2.5 • Image angle (horizontal x vertical): 8° x 6° (up to 5MP resolution) and 9° x 6° (6MP resolution) • For mounting this lens on the M2x, the extended replacement lens cover is needed (MOBOTIX accessory: MX-M24M-OPT-LCGL)

EAN:  
**4047438026598**

HS:  
**90021900**

Weight (incl. packaging):  
**30 g**

Dimensions (l/w/h) in cm:  
**7,5 / 4,9 / 9,0**

## CSVario Lens For Cameras With CS-Mount

Artikelno.: **MX-B045-100-CS**



**Description:**

CS Vario lens B045-100-CS • HD premium quality • Variable focal length: 4,5-10 mm • Variable aperture: f/1.6-2.3 • Variable image angle (horizontal x vertical): 39°-89° x 29°-65°

EAN:  
**4047438026604**

HS:  
**90021900**

Weight (incl. packaging):  
**60 g**

Dimensions (l/w/h) in cm:  
**7,5 / 4,9 / 9,0**

## Polarization Filter For Sensor Modules

Artikelno.: **MX-SM-OPT-POL**



**Description:**

Suitable for all M1x/S1x sensor modules except with the lenses B016, B036, B500 and CSVario or CS Mount • Filter replaces the lens cover (made of glass) • Example: Recognition of people through the windshield of a car - the filter reduces the mirror reflection (and about 50 % of the sensor light sensitivity)

EAN:  
**4047438019781**

HS:  
**90079100**

Weight (incl. packaging):  
**20 g**

Dimensions (l/w/h) in cm:  
**7,5 / 4,9 / 9,0**

**Replacement Lens Cover M2x, Standard**

Artikelno.: **MX-M24M-OPT-LCSK**



**Description:**

Suitable for: M2x (not CSVario, Hemispheric or super tele lens B500) and S1x/M1x sensor module with super tele lens B500 • Weather lens protection made of plastic (IP66)

EAN:  
**4047438012980**

HS:  
**90079100**

Weight (incl. packaging):  
**26 g**

Dimensions (l/w/h) in cm:  
**7,5 / 4,9 / 9,0**

**Replacement Lens Cover M2x, With Glass Pane**

Artikelno.: **MX-M24M-OPT-LCSG**



**Description:**

Suitable for: M2x (not CSVario, Hemispheric or super tele lens B500) and S1x/M1x sensor module with super tele lens B500 • Lens protection made of scratch-proof glass for extreme weather conditions (IP66)

EAN:  
**4047438012997**

HS:  
**90079100**

Weight (incl. packaging):  
**34 g**

Dimensions (l/w/h) in cm:  
**7,5 / 4,9 / 9,0**

**Replacement Lens Cover M2x, Extended**

Artikelno.: **MX-M24M-OPT-LCGL**



**Description:**

Suitable for: M2x and S1x/M1x sensor module with CSVario lens B045-100-CS or M2x with super tele lens B500 • Lens protection made of scratch-proof glass for extreme weather conditions (IP66)

EAN:  
**4047438013000**

HS:  
**90079100**

Weight (incl. packaging):  
**54 g**

Dimensions (l/w/h) in cm:  
**9,8 / 7,5 / 9,0**

**Replacement Cover Hemispheric**

Artikelno.: **MX-OPT-DK-L11**



**Description:**

Suitable for: Hemispheric sensor modules (for S1x/M1x), S26, S1xM, T2x and Q2x with Vanadlism Kit • Mounted with the blue MOBOTIX lens wrench (supplied with the Mx camera) • Polycarbonate (1.5 mm)

EAN:  
**4047438016469**

HS:  
**90079100**

Weight (incl. packaging):  
**19 g**

Dimensions (l/w/h) in cm:  
**7,5 / 4,9 / 9,0**

**Replacement Cover D1x/v2x, Standard**

Artikelno.: **MX-D15-OPT-DCT**



**Description:**

Suitable for: D1x and v2x • Not for Pano/180° and DNight-Fix models (XL cover needed)

EAN:  
**4047438018227**

HS:  
**90079100**

Weight (incl. packaging):  
**54 g**

Dimensions (l/w/h) in cm:  
**12,0 / 12,0 / 8,0**

**Replacement Cover D1x/v2x, Tinted**

Artikelno.: **MX-D15-OPT-DCS**



**Description:**

Suitable for: D1x and v2x • Not for Pano/180° and DNight-Fix models (XL cover needed) • Tinted (50%) for especially bright environments

EAN:  
**4047438018210**

HS:  
**90079100**

Weight (incl. packaging):  
**54 g**

Dimensions (l/w/h) in cm:  
**12,0 / 12,0 / 8,0**

**Replacement Cover D1x FIX/PAN, XL**

Artikelno.: **MX-D15-DCT-XL**



**Description:**

Suitable for: D1x PAN/180° and FIX/Day&Night models • Polycarbonate (1.5 mm)

EAN:

**4047438027519**

HS:

**90079100**

Weight ( incl. packaging):

**60 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5**

**Replacement Cover D1x PAN/FIX, XL Tinted**

Artikelno.: **MX-D15-DCS-XL**



**Description:**

Suitable for: D1x PAN/180° and FIX/Day&Night models • Tinted (50%) for especially bright environments • Polycarbonate (1.5 mm)

EAN:

**4047438027526**

HS:

**90079100**

Weight ( incl. packaging):

**60 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5**

**Replacement Cover D2x, Standard**

Artikelno.: **MX-D24M-OPT-DCT**



**Description:**

Suitable for: D2x • With sealing ring

EAN:

**4047438011419**

HS:

**90079100**

Weight ( incl. packaging):

**54 g**

Dimensions (l/w/h) in cm:

**12,0 / 12,0 / 8,0**

**Replacement Cover D2x, Tinted**

Artikelno.: **MX-D24M-OPT-DCS**



**Description:**

Suitable for: D2x • With sealing ring • Tinted (50%) for especially bright environments

EAN:

**4047438011402**

HS:

**90079100**

Weight ( incl. packaging):

**54 g**

Dimensions (l/w/h) in cm:

**12,0 / 12,0 / 8,0**

**Vandalism Set For D1x, Matt**

Artikelno.: **MX-D15-Vandal-ESMA**



**Description:**

Suitable for: D1x • Stainless steel vandalism ring with safetey screws replaces the standard outer shell • Deletes the PIR and audio features (use ExtIO if necessary) • Raises camera protection class from IP54 to IP66 and IK10 • Reinforced Dome (3 mm) – not suitable for Pano and DNight-Fix models

EAN:

**4047438018173**

HS:

**90079100**

Weight ( incl. packaging):

**1.116 g**

Dimensions (l/w/h) in cm:

**30,5 / 24,0 / 16,5**

**Vandalism Set For D1x, Polished**

Artikelno.: **MX-D15-Vandal-ESPO**



**Description:**

Suitable for: D1x • Stainless steel vandalism ring with safetey screws replaces the standard outer shell • Deletes the PIR and audio features (use ExtIO if necessary) • Raises camera protection class from IP54 to IP66 and IK10 • Reinforced Dome (3 mm) – not suitable for Pano and DNight-Fix models

EAN:

**4047438018166**

HS:

**90079100**

Weight ( incl. packaging):

**1.116 g**

Dimensions (l/w/h) in cm:

**30,5 / 24,0 / 16,5**

**Vandalism Set For D1x, Black**

Artikelno.: **MX-D15-Vandal-PUBL**



**Description:**

Suitable for: D1x • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Deletes the PIR and audio features (use ExtIO if necessary) • Raises camera protection class from IP54 to IP66 and IK10 • Reinforced Dome (3 mm) – not suitable for Pano and DNight-Fix models

EAN:

**4047438018203**

HS:

**90079100**

Weight ( incl. packaging):

**1.116 g**

Dimensions (l/w/h) in cm:

**30,5 / 24,0 / 16,5**

**Vandalism Set For D1x, Gray**

Artikelno.: **MX-D15-Vandal-PUGR**



**Description:**

Suitable for: D1x • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Deletes the PIR and audio features (use ExtIO if necessary) • Raises camera protection class from IP54 to IP66 and IK10 • Reinforced Dome (3 mm) – not suitable for Pano and DNight-Fix models

EAN:

**4047438018180**

HS:

**90079100**

Weight ( incl. packaging):

**1.116 g**

Dimensions (l/w/h) in cm:

**30,5 / 24,0 / 16,5**

**Vandalism Set For D1x, White**

Artikelno.: **MX-D15-Vandal-PUWH**



**Description:**

Suitable for: D1x • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Deletes the PIR and audio features (use ExtIO if necessary) • Raises camera protection class from IP54 to IP66 and IK10 • Reinforced Dome (3 mm) – not suitable for Pano and DNight-Fix models

EAN:

**4047438018197**

HS:

**90079100**

Weight ( incl. packaging):

**1.116 g**

Dimensions (l/w/h) in cm:

**30,5 / 24,0 / 16,5**

**Replacement Cover D1x/v2x, Vandalism**

Artikelno.: **MX-D15-DCT-V**



**Description:**

Reinforced replacement cover (polycarbonate, 3 mm) for D1x and v25 Vandalism Sets • Suitable for: D1x and v2x • Not for D1x PAN/180° and FIX/Day&Night models (XL cover needed)

EAN:

**4047438027533**

HS:

**90079100**

Weight ( incl. packaging):

**60 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5**

**Vandalism Set For D2x, Matt**

Artikelno.: **MX-D24M-Vandal-ESMA**



**Description:**

Suitable for: D2x Dome • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Raises camera protection class to IP66 and IK10 • Reinforced Dome (3 mm)

EAN:

**4047438011143**

HS:

**90079100**

Weight ( incl. packaging):

**672 g**

Dimensions (l/w/h) in cm:

**30,5 / 24,0 / 12,0**

**Vandalism Set For D2x, Polished**

Artikelno.: **MX-D24M-Vandal-ESPO**



**Description:**

Suitable for: D2x Dome • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Raises camera protection class to IP66 and IK10 • Reinforced Dome (3 mm)

EAN:

**4047438011150**

HS:

**90079100**

Weight ( incl. packaging):

**668 g**

Dimensions (l/w/h) in cm:

**30,5 / 24,0 / 12,0**

**Vandalism Set For D2x, Black**

Artikelno.: **MX-D24M-Vandal-PUBL**



**Description:**

Suitable for: D2x Dome • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Raises camera protection class to IP66 and IK10 • Reinforced Dome (3 mm)

EAN:  
**4047438011181**

HS:  
**90079100**

Weight ( incl. packaging):  
**676 g**

Dimensions (l/w/h) in cm:  
**30,5 / 24,0 / 12,0**

**Vandalism Set For D2x, Gray**

Artikelno.: **MX-D24M-Vandal-PUGR**



**Description:**

Suitable for: D2x Dome • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Raises camera protection class to IP66 and IK10 • Reinforced Dome (3 mm)

EAN:  
**4047438011174**

HS:  
**90079100**

Weight ( incl. packaging):  
**676 g**

Dimensions (l/w/h) in cm:  
**30,5 / 24,0 / 12,0**

**Vandalism Set For D2x, White**

Artikelno.: **MX-D24M-Vandal-PUWH**



**Description:**

Suitable for: D2x Dome • Stainless steel vandalism ring with safety screws replaces the standard outer shell • Raises camera protection class to IP66 and IK10 • Reinforced Dome (3 mm)

EAN:  
**4047438011167**

HS:  
**90079100**

Weight ( incl. packaging):  
**682 g**

Dimensions (l/w/h) in cm:  
**30,5 / 24,0 / 12,0**

**Replacement D2x, Vandalism**

Artikelno.: **MX-D25-DCT-V**



**Description:**

Reinforced replacement cover (polycarbonate, 3 mm) for D2x Vandalism Kits • With sealing ring

EAN:  
**4047438027700**

HS:  
**90079100**

Weight ( incl. packaging):  
**60 g**

Dimensions (l/w/h) in cm:  
**17,5 / 14,0 / 13,5**

**Vandalism Set For Q2x, Matt**

Artikelno.: **MX-Q24M-Vandal-ESMA**



**Description:**

Suitable for: Q2x • Vandalism-proof housing with lens protection • Ideally suited for surveillance at extremely critical locations • Raises camera protection class to IP66 and IK10 • Stainless steel, finish matt • Incl. security screws • Incl. 3 reinforced domes (3 mm polycarbonate) • Audio features still available

EAN:  
**4047438011273**

HS:  
**90079100**

Weight ( incl. packaging):  
**736 g**

Dimensions (l/w/h) in cm:  
**30,5 / 23,5 / 12,0**

**Vandalism Set For Q2x, Polished**

Artikelno.: **MX-Q24M-Vandal-ESPO**



**Description:**

Suitable for: Q2x • Vandalism-proof housing with lens protection • Ideally suited for surveillance at extremely critical locations • Raises camera protection class to IP66 and IK10 • Stainless steel, finish polished • Incl. security screws • Incl. 3 reinforced domes (3 mm polycarbonate) • Audio features still available

EAN:  
**4047438011280**

HS:  
**90079100**

Weight ( incl. packaging):  
**756 g**

Dimensions (l/w/h) in cm:  
**30,5 / 23,5 / 12,0**

## Vandalism Set For v2x

Artikelno.: **MX-MT-v25-V**



### Description:

Suitable for: v2x without On-Wall Mounting Set with Audio • Stainless steel vandalism ring (matt) with safety screws • Protects the camera housing (only without On-Wall Set) • Reinforced lens cover (polycarbonate, 3 mm) • IK10+

EAN:

**4047438027601**

HS:

**90079100**

Weight (incl. packaging):

**500 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 9,0**

## Vandalism Set For v2x With On-Wall Mounting Set

Artikelno.: **MX-MT-v25-V-XL**



### Description:

Suitable for: v2x with On-Wall Mounting Set with Audio • XL stainless steel vandalism ring (matt) with safety screws • Protects the camera housing (only with mounted On-Wall Set) • Reinforced lens cover (polycarbonate, 3 mm) • IK10+

EAN:

**4047438027625**

HS:

**90079100**

Weight (incl. packaging):

**450 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 9,0**

**DualMount S1x, White**Artikelno.: **MX-FLEX-OPT-DM-PW****Description:**

For surveillance of one area with two sensor modules (in particular, for day and night) • Suitable for all available sensor modules of the S1x (not included) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: White

EAN:

**4047438017626**

HS:

**90079100**

Weight (incl. packaging):

**442 g**

Dimensions (l/w/h) in cm:

**22,5 / 19,2 / 8,5****SurroundMount S1x, White**Artikelno.: **MX-FLEX-OPT-SM-PW****Description:**

For surveillance of long and narrow spaces (e.g., bus, train, hallway, etc.) without blind spots • Two sensor modules of the S1x can be integrated in the mount (not included) • For all 6MP Sensor modules (B016 to B500 and CS Mount) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: White

EAN:

**4047438016407**

HS:

**90079100**

Weight (incl. packaging):

**463 g**

Dimensions (l/w/h) in cm:

**22,5 / 19,2 / 8,5****PTMount S1x, White**Artikelno.: **MX-PTMount-OPT-PW****Description:**

Manually adjustable dome mount for one sensor module (not included) • Features three axes that allow it to compensate for sideways tilt and to re-align the image horizon horizontally when mounted to a wall • Suitable for all screwable sensor modules for S1x • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling or wall installation • Color: white

EAN:

**4047438021166**

HS:

**90079100**

Weight (incl. packaging):

**610 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5****DualMount S1x, Black**Artikelno.: **MX-FLEX-OPT-DM-BL****Description:**

For surveillance of one area with two sensor modules (in particular, for day and night) • Suitable for all screwable sensor modules of the S1x (not included) • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: black

EAN:

**4047438021869**

HS:

**90079100**

Weight (incl. packaging):

**442 g**

Dimensions (l/w/h) in cm:

**22,5 / 19,2 / 8,5****SurroundMount S1x, Black**Artikelno.: **MX-FLEX-OPT-SM-BL****Description:**

For surveillance of long and narrow spaces (e.g., bus, train, hallway, etc.) without blind spots • Two sensor modules of the S1x can be integrated in the mount (not included) • For all screwable sensor modules • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling installation, with a 25° tilt of the lenses • Color: black

EAN:

**4047438021845**

HS:

**90079100**

Weight (incl. packaging):

**463 g**

Dimensions (l/w/h) in cm:

**22,5 / 19,2 / 8,5****PTMount S1x, Black**Artikelno.: **MX-PTMount-OPT-BL****Description:**

Manually adjustable dome mount for one sensor module (not included) • Features three axes that allow it to compensate for sideways tilt and to re-align the image horizon horizontally when mounted to a wall • Suitable for all screwable sensor modules for S1x • Concealed cabling, weatherproof from -30 to 60°C/-22 to 140°F • Suitable for ceiling or wall installation • Color: black

EAN:

**4047438021852**

HS:

**90079100**

Weight (incl. packaging):

**610 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5**

**HaloMount S1x, White**Artikelno.: **MX-HALO-EXT-PW****Description:**

Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S1x (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W)

EAN:

**4047438017664**

HS:

**90079100**

Weight ( incl. packaging):

**175 g**

Dimensions (l/w/h) in cm:

**13,5 / 12,0 / 4,5****HaloMount S1x, Black**Artikelno.: **MX-HALO-EXT-BL****Description:**

Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S1x (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W)

EAN:

**4047438017671**

HS:

**90079100**

Weight ( incl. packaging):

**175 g**

Dimensions (l/w/h) in cm:

**13,5 / 12,0 / 4,5****HaloMount S1x, Matt Chrome**Artikelno.: **MX-HALO-EXT-CM****Description:**

Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S1x (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W)

EAN:

**4047438017633**

HS:

**90079100**

Weight ( incl. packaging):

**175 g**

Dimensions (l/w/h) in cm:

**13,5 / 12,0 / 4,5****HaloMount S1x, Chrome**Artikelno.: **MX-HALO-EXT-CO****Description:**

Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S1x (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W)

EAN:

**4047438017640**

HS:

**90079100**

Weight ( incl. packaging):

**175 g**

Dimensions (l/w/h) in cm:

**13,5 / 12,0 / 4,5****HaloMount S1x, Brushed Nickel**Artikelno.: **MX-HALO-EXT-NG****Description:**

Indoor installation mount for a sensor module (in-wall or in-ceiling) • Suitable for all available sensor modules S1x (not included) • Flexible setting of inner ring, sensor module can be tilted up to 20° • High-quality metal design • Also for lighting equipment (QR-CBC/MR16 LED Sharp Array 4/6 W)

EAN:

**4047438017657**

HS:

**90079100**

Weight ( incl. packaging):

**175 g**

Dimensions (l/w/h) in cm:

**13,5 / 12,0 / 4,5****SpeakerMount S1x, White**Artikelno.: **MX-HALO-SP-EXT-PW****Description:**

Integrated speaker incl. mount, white • Suitable for the installation in ceilings or walls, indoor (IP20) • Compatible with all cameras S1x and V1x • Direct connection via two-wire cable, no additional power supply unit needed • Inner ring with speaker can be tilted up to 20° • Temperature range: -30 to 60°C/-22 to 140°F • IP code: IP20 • Impedance: 8 ohm • Speaker material: metall with perforated plate covering • Connection type: two-wired strand, clamp included

EAN:

**4047438017688**

HS:

**85182200**

Weight ( incl. packaging):

**273 g**

Dimensions (l/w/h) in cm:

**13,5 / 12,0 / 4,5**



**SpeakerMount S1x, Matt Chrome**Artikelno.: **MX-HALO-SP-EXT-CM****Description:**

Integrated speaker incl. mount, matt chrome • Suitable for the installation in ceilings or walls, indoor (IP20) • Compatible with all cameras S1x and V1x • Direct connection via two-wire cable, no additional power supply unit needed • Inner ring with speaker can be tilted up to 20° • Temperature range: -30 to 60°C/-22 to 140°F • IP code: IP20 • impedance: 8 ohm • Speaker material: metall with perforated plate covering • Connection type: two-wired strand, clamp included

EAN:

**4047438017695**

HS:

**85182200**

Weight ( incl. packaging):

**273 g**

Dimensions (l/w/h) in cm:

**13,5 / 12,0 / 4,5****Extension Set Sensor Module, 40 mm And 15°**Artikelno.: **MX-S14-OPT-MK-CW****Description:**

Complete set for wall or ceiling mounting of a sensor module using 15° wedges • Incl. extension to increase the installation depth • Suitable for all S1x sensor modules • 1x extension 40 mm/1.6 in • 2x 15° wedges (white and black) • 2x wedge sealing rings • 1x nut

EAN:

**4047438016384**

HS:

**90079100**

Weight ( incl. packaging):

**134 g**

Dimensions (l/w/h) in cm:

**21,3 / 8,7 / 8,7****Extension Sensor Module, 40 mm**Artikelno.: **MX-S14-OPT-MK-EX****Description:**

1x extension 40 mm/1.6 inch, increases the installation depth • Suitable for all (screwable) S1x sensor modules • Can be mounted directly onto the sensor modules themselves or onto existing extensions

EAN:

**4047438016391**

HS:

**90079100**

Weight ( incl. packaging):

**62 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5****AudioMount S26/S1xM, Self-Adhesive**Artikelno.: **MX-FLEX-OPT-AM-BL****Description:**

Suitable for: S26, S15M, S14M • Easy, quick and concealed mounting with adhesive foil (e.g. behind a stainless steel plate) • Speaker and microphone with camera connection cable included • Use of the camera as a door station by connecting an external doorbell (e.g., connected via MX-232-IO-Box)

EAN:

**4047438019873**

HS:

**85299065**

Weight ( incl. packaging):

**386 g**

Dimensions (l/w/h) in cm:

**24,0 / 13,6 / 5,3**

**On-Wall Mounting Set With Audio For v26, White**

Artikelno.: **Mx-M-OWA-AU**



**Description:**

On-Wall Set with Audio for v26 • Consists of on-wall mount, mounting parts, integrated speaker, microphone and camera plug-in connection cable • Enables on-wall cabling of the camera and integrates two additional Interface Box modules • Housing color: white

EAN:  
**4047438030328**

HS:  
**90079100**

Weight ( incl. packaging):  
**300 g**

Dimensions (l/w/h) in cm:  
**20,5 / 19,8 / 12,3**

**On-Wall Mounting Set With Audio For v26, Black**

Artikelno.: **Mx-M-OWA-AU-b**



**Description:**

On-Wall Set with Audio for v26 • Consists of on-wall mount, mounting parts, integrated speaker, microphone and camera plug-in connection cable • Enables on-wall cabling of the camera and integrates two additional Interface Box modules • Housing color: black

EAN:  
**4047438030335**

HS:  
**90079100**

Weight ( incl. packaging):  
**300 g**

Dimensions (l/w/h) in cm:  
**20,5 / 19,8 / 12,3**

**On-Wall Mounting Set With Audio For v25, White**

Artikelno.: **MX-MT-OW2-AUD**



**Description:**

Suitable for: v25 • Consists of on-wall mount, mounting parts, integrated speaker, microphone and camera plug-in connection cable • Enables on-wall cabling of the camera and integrates two additional Interface Box modules • Housing color: white

EAN:  
**4047438027632**

HS:  
**90079100**

Weight ( incl. packaging):  
**300 g**

Dimensions (l/w/h) in cm:  
**20,5 / 19,8 / 12,3**

**On-Wall Mounting Set With Audio For v25, Black**

Artikelno.: **MX-MT-OW2-AUD-b**



**Description:**

Suitable for: v25 • Consists of on-wall mount, mounting parts, integrated speaker, microphone and camera plug-in connection cable • Enables on-wall cabling of the camera and integrates two additional Interface Box modules • Housing color: black

EAN:  
**4047438027670**

HS:  
**90079100**

Weight ( incl. packaging):  
**300 g**

Dimensions (l/w/h) in cm:  
**20,5 / 19,8 / 12,3**

**MxTubeMount Ceiling Suspension System**

Artikelno.: **MX-MT-TUBE**



**Description:**

For suspended ceiling installation of the cameras M1x/M2x/v2x/PTMount/PT-Mount-Thermal (each can be attached directly to the MxTubeMount) and of the cameras D2x/Q2x/c2x/p2x (each can only be attached to the MxTubeMount when using the optional on-wall mounting set of the camera) • Incl. drop down protection wire (length: 2.2 m/7.2 ft) • Additionally needed suspension tube MxTube with a length of 1m (3.3 ft) or 2 m (6.6 ft) to be ordered separately (MX-MT-TUBE100, MX-MT-TUBE200) • Alternative suspension with customary tubes: outer diameter 30 mm or 26.9 mm (R3/4" according to DIN 2440), max. length: 2 m (6.6 ft), max. weight: 2.5 kg (5.5 lb), color/material of choice

EAN:  
**4047438027557**


HS:  
**90079100**

Weight ( incl. packaging):  
**500 g**

Dimensions (l/w/h) in cm:  
**20,5 / 19,8 / 12,3**

**MxTube, 1 m**

Artikelno.: **MX-MT-TUBE100**



**Description:**

Suspension tube for MxTubeMount • Length: 1 m (3.3 ft) • Anodized aluminium • Outer diameter: 30 mm, wall thickness: 2 mm

EAN:  
**4047438027687**


HS:  
**90079100**

Weight ( incl. packaging):  
**500 g**

Dimensions (l/w/h) in cm:  
**110,0 / 3,8 / 3,8**

**MxTube, 2 m**

Artikelno.: **MX-MT-TUBE200**



**Description:**

Suspension tube for MxTubeMount • Length: 2 m (6.6 ft) • Anodized aluminium • Outer diameter: 30 mm, wall thickness: 2 mm

EAN:

**4047438027564**

HS:

**90079100**

Weight ( incl. packaging):

**1.000 g**

Dimensions (l/w/h) in cm:

**201,0 / 3,8 / 3,8**

**Cavity Wall Installation Set i2x**

Artikelno.: **MX-OPT-UP1**



**Description:**

Cavity Wall Installation Set for the i2x • With cavity wall socket, stainless steel mounting plate, 2 Allen screws with washers • For installing the camera directly on the mounting plate, no dowels required • Mounting plate is screwed onto the cavity wall socket • Recommended only for wall installations

EAN:

**4047438022118**

HS:

**90079100**

Weight ( incl. packaging):

**116 g**

Dimensions (l/w/h) in cm:

**14,8 / 9,8 / 9,0**

**On-Wall Mounting Set For i2x**

Artikelno.: **MX-OPT-AP2**



**Description:**

Suitable for: i25 • Consists of on-wall mount and mounting parts • Enables on-wall cabling of the camera • Camera distance from the wall: ca. 25 mm • Recommended only for wall installation • Color: white

EAN:

**4047438025898**

HS:

**90079100**

Weight ( incl. packaging):

**96 g**

Dimensions (l/w/h) in cm:

**14,8 / 9,8 / 9,0**

**On-Wall Mounting Set For c2x/p2x**

Artikelno.: **MX-MT-OW-1**



**Description:**

Suitable for: c2x und p2x • Consists of on-wall mount and mounting parts • Enables on-wall cabling of the camera and integrates additional modules (e.g. two Interface Boxes) • Camera distance from the wall: ca. 80 mm • Diameter: 140 mm • Recommended only for ceiling installation • Color: White

EAN:

**4047438027083**

HS:

**90079100**

Weight ( incl. packaging):

**700 g**

Dimensions (l/w/h) in cm:

**20,5 / 19,8 / 12,3**

**Corner Mounting Set For c2x**

Artikelno.: **MX-MT-CM-1**



**Description:**

Suitable for: c2x • Consists of on-wall mount and mounting parts • Mounting in a room corner • Mounting position plus 35° tilt angle enable one camera (e.g. c2x with 103° lens B036) to capture an entire room • Color: White

EAN:

**4047438027076**

HS:

**90079100**

Weight ( incl. packaging):

**600 g**

Dimensions (l/w/h) in cm:

**30,5 / 24,0 / 16,5**

**On-Wall Mounting Set For Q2x/D2x/ExtIO**

Artikelno.: **MX-OPT-AP**



**Description:**

Suitable for: Q2x, D2x, ExtIO • Consists of on-wall mount and mounting parts • Protects the cabling • Allows integrating additional modules • Dimensions: 165 mm x 37 mm

EAN:

**4047438011358**

HS:

**90079100**

Weight ( incl. packaging):

**608 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 9,0**

**On-Wall Mounting Set For Q2x/D2x/ExtIO, 10°**

Artikelno.: **MX-OPT-AP-10DEG**



**Description:**

Suitable for: Q2x, D2x, ExtIO • Consists of on-wall mount and mounting parts • Camera can be mounted at a 10° tilt angle • Protects the cabling • Allows integrating additional modules • Dimensions: 165 mm x 37 mm

EAN:  
**4047438010283**

HS:  
**90079100**

Weight ( incl. packaging):  
**548 g**

Dimensions (l/w/h) in cm:  
**29,6 / 19,6 / 9,0**

**Wall & Pole/Corner Mount Set For D1x**

Artikelno.: **MX-D15-OPT-WHMH-Set**



**Description:**

Suitable for: D1x • Set consisting of pole/corner mount (MX-MH-Dome-ESWS) and wall mount (MX-WH-Dome) • Mounted to the corner, one camera can cover two sides of a building simultaneously • Pole/corner mount for fastening of wall mount: 3 mm stainless steel, white • Wall mount consists of shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Wall mount raises camera protection class from IP54 to IP65 • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm

EAN:  
**4047438018159**

HS:  
**90079100**

Weight ( incl. packaging):  
**5.000 g**

Dimensions (l/w/h) in cm:  
**40,8 / 31,0 / 38,5**

**Wall & Pole/Corner Mount Set For Q2x/D2x/ExtIO**

Artikelno.: **MX-OPT-WHMH-Set**



**Description:**

Suitable for: Q2x, D2x, ExtIO • Set consisting of pole/corner mount (MX-OPT-MH) and wall mount (MX-OPT-WH) • Pole/corner mount for fastening of wall mount: 3 mm stainless steel, white • Wall mount consists of shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm

EAN:  
**4047438011396**

HS:  
**90079100**

Weight ( incl. packaging):  
**2.410 g**

Dimensions (l/w/h) in cm:  
**30,5 / 24,0 / 16,5**

**Wall Mount For D1x**

Artikelno.: **MX-WH-Dome**



**Description:**

Suitable for: D1x • Shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Raises camera protection class from IP54 to IP66 • Incl. mounting parts

EAN:  
**4047438002233**

HS:  
**90079100**

Weight ( incl. packaging):  
**2.000 g**

Dimensions (l/w/h) in cm:  
**39,5 / 29,6 / 18,0**

**Wall Mount For Q2x/D2x/ExtIO**

Artikelno.: **MX-OPT-WH**



**Description:**

Suitable for: Q2x, D2x, ExtIO • Wall mount consists of shock-resistant fiberglass-reinforced plastic (PBT), white • Covers RJ45 wall outlets • Ample room inside for extras (e.g., interface boxes) • Incl. mounting parts

EAN:  
**4047438011372**

HS:  
**90079100**

Weight ( incl. packaging):  
**1.040 g**

Dimensions (l/w/h) in cm:  
**30,5 / 24,0 / 16,5**

**Wall/Ceiling Mount For M12/M10/M1**

Artikelno.: **MX-WH-SecureFlex**



**Description:**

Suitable for: M12/M10/M1 (not M15) • Shock-resistant fiberglass-reinforced composite (PBT), white • Patented tamper-proof concealed cabling • Can be turned left/right 90°, tilted downwards 70° • Includes stainless steel mounting set, caps and dowels

EAN:  
**4047438002219**

HS:  
**90079100**

Weight ( incl. packaging):  
**390 g**

Dimensions (l/w/h) in cm:  
**20,0 / 15,0 / 11,0**

**Pole/Corner Mount For MX-WH-Dome**

Artikelno.: **MX-MH-Dome-ESWS**



**Description:**

Suitable for: D1x • Pole/corner mount for fastening of wall mount MX-WH-Dome (to be ordered individually) • Made of 3 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm

EAN:  
**4047438002240**

HS:  
**90079100**

Weight ( incl. packaging):  
**3.000 g**

Dimensions (l/w/h) in cm:  
**34,0 / 18,5 / 11,5**

**Pole Mount For M1x/M2x**

Artikelno.: **MX-MH-SecureFlex-ESWS**



**Description:**

Suitable for: M1x, M2x • Mount for fastening the standard camera wall mount SecureFlex (M12/M10, M22) and VarioFlex (M15, M2x) • Made of 3 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm

EAN:  
**4047438002226**

HS:  
**90079100**

Weight ( incl. packaging):  
**1.230 g**

Dimensions (l/w/h) in cm:  
**20,0 / 15,2 / 8,0**

**Pole/Corner Mount For MX-OPT-WH**

Artikelno.: **MX-OPT-MH**



**Description:**

Suitable for: Q2x, D2x, ExtIO • Mount for fastening the wall mount MX-OPT-WH (to be ordered separately) • A set consisting of Pole/Corner Mount and Wall Mount is also available (MX-OPT-WMH-Set) • Made of 3 mm stainless steel, white • Incl. mounting parts and 2 stainless steel straps for pole diameters of 60 to 180 mm

EAN:  
**4047438011389**

HS:  
**90079100**

Weight ( incl. packaging):  
**1.370 g**

Dimensions (l/w/h) in cm:  
**34,0 / 18,5 / 11,5**

**In-Ceiling Set For Q2x/D2x/ExtIO, Matt**

Artikelno.: **MX-OPT-IC-ESMA**



**Description:**

Suitable for: Q2x, D2x, ExtIO • Stainless steel ring (matt) • Consists of in-ceiling mount and mounting parts • Easy mounting from front • Provides optimum protection for the camera • Inconspicuous, as the visible profile is reduced to a minimum • Installation dimension (diameter): 150 mm

EAN:  
**4047438011433**

HS:  
**90079100**

Weight ( incl. packaging):  
**724 g**

Dimensions (l/w/h) in cm:  
**30,5 / 24,0 / 12,0**

**In-Ceiling Set For Q2x/D2x/ExtIO, Polished**

Artikelno.: **MX-OPT-IC-ESPO**



**Description:**

Suitable for: Q2x, D2x, ExtIO • Stainless steel ring (polished) • Consists of in-ceiling mount and mounting parts • Easy mounting from front • Provides optimum protection for the camera • Inconspicuous, as the visible profile is reduced to a minimum • Installation dimension (diameter): 150 mm

EAN:  
**4047438011426**

HS:  
**90079100**

Weight ( incl. packaging):  
**724 g**

Dimensions (l/w/h) in cm:  
**30,5 / 24,0 / 12,0**

**In-Ceiling Set For Q2x/D2x/ExtIO, White**

Artikelno.: **MX-OPT-IC**



**Description:**

Suitable for: Q2x, D2x, ExtIO • Consists of in-ceiling mount and mounting parts • Easy mounting from front • Provides optimum protection for the camera • Inconspicuous, as the visible profile is reduced to a minimum • Installation dimension (diameter): 150 mm

EAN:  
**4047438011365**

HS:  
**90079100**

Weight ( incl. packaging):  
**550 g**

Dimensions (l/w/h) in cm:  
**30,5 / 24,0 / 12,0**

## Demo Table/Wall Mount For Q2x/D2x

Artikelno.: **MX-OPT-TW-Demo-1**



### Description:

Useful mount for testing and for finding the optimum mounting position of the single lens cameras Q2x Hemispheric or D2x Dome. The set includes an Allen wrench and a Torx screw with dowel and the corresponding Torx wrench for installing as alternative wall mount for testing. The camera can be placed on a flat surface or can be mounted on a tripod (1/4" tripod thread at the bottom of the mount).

EAN:

**4047438013055**

HS:

**90079100**

Weight (incl. packaging):

**200 g**

Dimensions (l/w/h) in cm:

**14,8 / 9,8 / 9,0**

**Sensor Module Cable For M1x, 0.15 m**

Artikelno.: **MX-FLEX-OPT-CBL-015**



Description:  
sensor cable (HS Code 85444210)

EAN:  
**4047438019941**

HS:  
**85444210**

Weight ( incl. packaging):  
**16 g**

Dimensions (l/w/h) in cm:  
**9,8 / 7,5 / 9,0**

**Sensor Cable For S1x, 0.5 m**

Artikelno.: **MX-FLEX-OPT-CBL-05**



Description:  
Sensor cable, length 0.5 m/1,6 ft • For connecting optical sensor modules, BlockFlexMounts and thermal sensor modules to the camera module

EAN:  
**4047438018890**

HS:  
**85444210**

Weight ( incl. packaging):  
**66 g**

Dimensions (l/w/h) in cm:  
**9,8 / 7,5 / 9,0**

**Sensor Cable For S1x, 1 m**

Artikelno.: **MX-FLEX-OPT-CBL-1**



Description:  
Sensor cable, length 1 m/3,3 ft • For connecting optical sensor modules, BlockFlexMounts and thermal sensor modules to the camera module

EAN:  
**4047438018883**

HS:  
**85444210**

Weight ( incl. packaging):  
**85 g**

Dimensions (l/w/h) in cm:  
**9,8 / 7,5 / 9,0**

**Sensor Cable For S1x, 2 m**

Artikelno.: **MX-FLEX-OPT-CBL-2**



Description:  
Sensor cable, length 2 m/6,6 ft • For connecting optical sensor modules, BlockFlexMounts and thermal sensor modules to the camera module

EAN:  
**4047438018876**

HS:  
**85444210**

Weight ( incl. packaging):  
**113 g**

Dimensions (l/w/h) in cm:  
**9,8 / 7,5 / 9,0**

**Sensor Cable For S1x (6MP/Thermal), 3 m**

Artikelno.: **MX-FLEX-OPT-CBL-3**



Description:  
Sensor cable, length 3 m/9,8 ft • For connecting optical sensor modules and BlockFlexMounts with 6MP sensors and Thermal sensor modules to the S1x camera module • Not compatible with PTMount-Thermal, S14D and 5MP modules

EAN:  
**4047438024303**

HS:  
**85444210**

Weight ( incl. packaging):  
**146 g**

Dimensions (l/w/h) in cm:  
**9,8 / 7,5 / 9,0**

**USB Device Cable For M/Q/T2x, 0.5 m**

Artikelno.: **MX-CBL-MU-EN-AB-05**



Description:  
MiniUSB angled > USB-A straight • Length 0,5 m/1,6 ft • For M1x, M2x, Q2x, T2x • To connect ext. USB device

EAN:  
**4047438016728**

HS:  
**85444210**

Weight ( incl. packaging):  
**52 g**

Dimensions (l/w/h) in cm:  
**9,8 / 7,5 / 9,0**

**USB Device Cable For M/Q/T2x, 2 m**

Artikelno.: **MX-CBL-MU-EN-AB-2**



**Description:**

MiniUSB angled > USB-A straight • Length 2 m/6,6 ft • For M1x, M2x, Q2x, T2x • To connect ext. USB-Gerät

EAN:

**4047438016711**

HS:

**85444210**

Weight ( incl. packaging):

**102 g**

Dimensions (l/w/h) in cm:

**9,8 / 7,5 / 9,0**

**USB Device Cable For M/Q/T2x, 5 m**

Artikelno.: **MX-CBL-MU-EN-AB-5**



**Description:**

MiniUSB angled > USB-A straight • Length 5 m/16,4 ft • For M1x, M2x, Q2x, T2x • To connect ext. USB device

EAN:

**4047438016704**

HS:

**85444210**

Weight ( incl. packaging):

**194 g**

Dimensions (l/w/h) in cm:

**9,8 / 7,5 / 9,0**

**ExtIO Cable For M/Q/T2x, 0,5 m**

Artikelno.: **MX-CBL-MU-EN-EN-PG-05**



**Description:**

MiniUSB angled > MiniUSB+ angled • Length 0,5 m/1,6 ft • For M1x, M2x, Q2x, T2x • To connect MX-ExtIO

EAN:

**4047438020947**

HS:

**85444210**

Weight ( incl. packaging):

**52 g**

Dimensions (l/w/h) in cm:

**9,8 / 7,5 / 9,0**

**ExtIO Cable For M/Q/T2x, 2 m**

Artikelno.: **MX-CBL-MU-EN-EN-PG-2**



**Description:**

MiniUSB angled > MiniUSB+ angled • Length 2 m/6,6 m • For M1x, M2x, Q2x, T2x • To connect MX-ExtIO

EAN:

**4047438020930**

HS:

**85444210**

Weight ( incl. packaging):

**102 g**

Dimensions (l/w/h) in cm:

**9,8 / 7,5 / 9,0**

**ExtIO Cable for M/Q/T2x, 5 m**

Artikelno.: **MX-CBL-MU-EN-EN-PG-5**



**Description:**

MiniUSB angled > MiniUSB+ angled • Length 5 m/16,4 ft • For M1x, M2x, Q2x, T2x • To connect MX-ExtIO

EAN:

**4047438020923**

HS:

**85444210**

Weight ( incl. packaging):

**194 g**

Dimensions (l/w/h) in cm:

**9,8 / 7,5 / 9,0**

**USB Device Cable For D2x, 0,5 m**

Artikelno.: **MX-CBL-MU-EN-PG-AB-05**



**Description:**

MiniUSB+ angled > USB-A straight • Length 0,5 m/1,6 ft • For D2x • To connect ext. USB device

EAN:

**4047438020916**

HS:

**85444210**

Weight ( incl. packaging):

**52 g**

Dimensions (l/w/h) in cm:

**9,8 / 7,5 / 9,0**



**USB Device Cable For D2x, 2 m**

Artikelno.: **MX-CBL-MU-EN-PG-AB-2**



Description:

MiniUSB+ angled > USB-A straight • Length 2 m/6,6 ft • For D2x • to connect ext. USB device

EAN:  
**4047438020909**

HS:  
**85444210**

Weight ( incl. packaging):  
**102 g**

Dimensions (l/w/h) in cm:  
**9,8 / 7,5 / 9,0**

**USB Device Cable For D2x, 5 m**

Artikelno.: **MX-CBL-MU-EN-PG-AB-5**



Description:

MiniUSB+ angled > USB-A straight • Length 5 m/16,4 ft • For D2x • To connect ext. USB device

EAN:  
**4047438020893**

HS:  
**85444210**

Weight ( incl. packaging):  
**194 g**

Dimensions (l/w/h) in cm:  
**9,8 / 7,5 / 9,0**

**ExtIO Cable For D2x, 0.5 m**

Artikelno.: **MX-CBL-MU-EN-PG-EN-PG-05**



Description:

MiniUSB+ angled > MiniUSB+ angled • Length 0,5 m/1,6 ft • For D2x • To connect MX-ExtIO

EAN:  
**4047438020886**

HS:  
**85444210**

Weight ( incl. packaging):  
**52 g**

Dimensions (l/w/h) in cm:  
**9,8 / 7,5 / 9,0**

**ExtIO Cable For D2x, 2 m**

Artikelno.: **MX-CBL-MU-EN-PG-EN-PG-2**



Description:

MiniUSB+ angled > MiniUSB+ angled • Length 2 m/6,6 ft • For D2x • To connect MX-ExtIO

EAN:  
**4047438020879**

HS:  
**85444210**

Weight ( incl. packaging):  
**102 g**

Dimensions (l/w/h) in cm:  
**9,8 / 7,5 / 9,0**

**ExtIO Cable For D2x, 5 m**

Artikelno.: **MX-CBL-MU-EN-PG-EN-PG-5**



Description:

MiniUSB+ angled > MiniUSB+ angled • Length 5 m/16,4 ft • For D2x • To connect MX-ExtIO

EAN:  
**4047438020862**

HS:  
**85444210**

Weight ( incl. packaging):  
**194 g**

Dimensions (l/w/h) in cm:  
**9,8 / 7,5 / 9,0**

**232-IO-Box Cable For D2x, 0.5 m**

Artikelno.: **MX-CBL-MU-EN-PG-STR-05**



Description:

MiniUSB+ angled > MiniUSB straight • Length 0,5 m/1,6 ft • For D2x • To connect MX-232-IO-Box

EAN:  
**4047438020855**

HS:  
**85444210**

Weight ( incl. packaging):  
**52 g**

Dimensions (l/w/h) in cm:  
**9,8 / 7,5 / 9,0**

**232-IO-Box Cable For D2x, 2 m**

Artikelno.: **MX-CBL-MU-EN-PG-STR-2**



Description:  
MiniUSB+ angled > MiniUSB straight • Length 2 m/6,6 ft • For D2x • To connect MX-232-IO-Box

EAN:  
**4047438020848**  
HS:  
**85444210**  
Weight ( incl. packaging):  
**102 g**  
Dimensions (l/w/h) in cm:  
**9,8 / 7,5 / 9,0**

**232-IO-Box Cable For D2x, 5 m**

Artikelno.: **MX-CBL-MU-EN-PG-STR-5**



Description:  
MiniUSB+ angled > MiniUSB straight • Length 5 m/16,4 ft • For D2x • To connect MX-232-IO-Box

EAN:  
**4047438020831**  
HS:  
**85444210**  
Weight ( incl. packaging):  
**194 g**  
Dimensions (l/w/h) in cm:  
**9,8 / 7,5 / 9,0**

**232-IO-Box Cable For M/Q/T2x, 0.5 m**

Artikelno.: **MX-CBL-MU-EN-STR-05**



Description:  
MiniUSB angled > MiniUSB straight • Length 0,5 m/1,6 ft • For M1x, M2x, Q2x, T2x • To connect MX-232-IO-Box

EAN:  
**4047438016667**  
HS:  
**85444210**  
Weight ( incl. packaging):  
**49 g**  
Dimensions (l/w/h) in cm:  
**9,8 / 7,5 / 9,0**

**232-IO-Box Cable For M/Q/T2x, 2 m**

Artikelno.: **MX-CBL-MU-EN-STR-2**



Description:  
MiniUSB angled > MiniUSB straight • Length 2 m/6.6 ft • For M1x, M2x, Q2x, T2x • To connect MX-232-IO-Box

EAN:  
**4047438016650**  
HS:  
**85444210**  
Weight ( incl. packaging):  
**95 g**  
Dimensions (l/w/h) in cm:  
**9,8 / 7,5 / 9,0**

**232-IO-Box Cable For M/Q/T2x, 5 m**

Artikelno.: **MX-CBL-MU-EN-STR-5**



Description:  
MiniUSB angled > MiniUSB straight • Length 5 m/16,4 ft • For M1x, M2x, Q2x, T2x • To connect MX-232-IO-Box

EAN:  
**4047438016643**  
HS:  
**85444210**  
Weight ( incl. packaging):  
**189 g**  
Dimensions (l/w/h) in cm:  
**9,8 / 7,5 / 9,0**

**232-IO-Box Cable For D/S/V1x, 0.5 m**

Artikelno.: **MX-CBL-MU-STR-05**



Description:  
MiniUSB straight > MiniUSB straight • Length 0,5 m/1,6 ft • For D1x, S1x, V1x • To connect MX-232-IO-Box

EAN:  
**4047438016605**  
HS:  
**85444210**  
Weight ( incl. packaging):  
**48 g**  
Dimensions (l/w/h) in cm:  
**9,8 / 7,5 / 9,0**

**232-IO-Box Cable For D/S/V1x, 2 m**

Artikelno.: **MX-CBL-MU-STR-2**



Description:

MiniUSB straight > MiniUSB straight • Length 2 m/6,6 ft • For D1x, S1x, V1x • To connect MX-232-IO-Box

EAN:  
**4047438016599**

HS:  
**85444210**

Weight ( incl. packaging):  
**96 g**

Dimensions (l/w/h) in cm:  
**9,8 / 7,5 / 9,0**

**232-IO-Box Cable For D/S/V1x, 5 m**

Artikelno.: **MX-CBL-MU-STR-5**



Description:

MiniUSB straight > MiniUSB straight • Length 5 m/16,4 ft • For D1x, S1x, V1x • To connect MX-232-IO-Box

EAN:  
**4047438016445**

HS:  
**85444210**

Weight ( incl. packaging):  
**196 g**

Dimensions (l/w/h) in cm:  
**9,8 / 7,5 / 9,0**

**USB Device Cable For D/S/V1x, 0.5 m**

Artikelno.: **MX-CBL-MU-STR-AB-05**



Description:

MiniUSB straight > USB-A straight • Length 0,5 m/1,6 ft • For D1x, S1x, V1x • To connect ext. USB device

EAN:  
**4047438016698**

HS:  
**85444210**

Weight ( incl. packaging):  
**52 g**

Dimensions (l/w/h) in cm:  
**9,8 / 7,5 / 9,0**

**USB Device Cable For D/S/V1x, 2 m**

Artikelno.: **MX-CBL-MU-STR-AB-2**



Description:

MiniUSB straight > USB-A straight • Length 2 m/6,6 ft • D1x, S1x, V1x • To connect ext. USB device

EAN:  
**4047438016681**

HS:  
**85444210**

Weight ( incl. packaging):  
**102 g**

Dimensions (l/w/h) in cm:  
**9,8 / 7,5 / 9,0**

**USB Device Cable For D/S/V1x, 5 m**

Artikelno.: **MX-CBL-MU-STR-AB-5**



Description:

MiniUSB straight > USB-A straight • Length 5 m /16,4 ft • For D1x, S1x, V1x • To connect ext. USB device

EAN:  
**4047438016674**

HS:  
**85444210**

Weight ( incl. packaging):  
**194 g**

Dimensions (l/w/h) in cm:  
**9,8 / 7,5 / 9,0**

**ExtIO Cable For D/S/V1x, 0.5 m**

Artikelno.: **MX-CBL-MU-STR-EN-PG-05**



Description:

MiniUSB straight > MiniUSB+ angled • Length 0,5 m/1,6 ft • For D1x, S1x, V1x • To connect MX-ExtIO

EAN:  
**4047438020978**

HS:  
**85444210**

Weight ( incl. packaging):  
**52 g**

Dimensions (l/w/h) in cm:  
**9,8 / 7,5 / 9,0**

**ExtIO Cable For D/S/V1x, 2 m**

Artikelno.: **MX-CBL-MU-STR-EN-PG-2**



Description:  
MiniUSB straight > MiniUSB+ angled • Length 2 m/6,6 ft • For D1x, S1x, V1x • To connect MX-ExtIO

EAN:  
**4047438020961**  
HS:  
**85444210**  
Weight ( incl. packaging):  
**102 g**  
Dimensions (l/w/h) in cm:  
**9,8 / 7,5 / 9,0**

**ExtIO Cable For D/S/V1x, 5 m**

Artikelno.: **MX-CBL-MU-STR-EN-PG-5**



Description:  
MiniUSB straight > MiniUSB+ angled • Length 5 m/16,4 ft • For D1x, S1x, V1x • To connect MX-ExtIO

EAN:  
**4047438020954**  
HS:  
**85444210**  
Weight ( incl. packaging):  
**194 g**  
Dimensions (l/w/h) in cm:  
**9,8 / 7,5 / 9,0**

**Ethernet Patch Cable, 1 m**

Artikelno.: **MX-OPT-CBL-LAN-1**



Description:  
Ethernet Patch Cable for MOBOTIX systems • Lenght 1 m/3,3 ft • 2x RJ45 plug with special MOBOTIX sealing ring

EAN:  
**4047438012300**  
HS:  
**85444210**  
Weight ( incl. packaging):  
**36 g**  
Dimensions (l/w/h) in cm:  
**23,5 / 15,0 / 2,0**

**Ethernet Patch Cable, 10 m**

Artikelno.: **MX-OPT-CBL-LAN-10**



Description:  
Ethernet Patch Cable for MOBOTIX systems • Lenght 10 m/32,8 ft • 2x RJ45 plug with special MOBOTIX sealing ring

EAN:  
**4047438012331**  
HS:  
**85444210**  
Weight ( incl. packaging):  
**264 g**  
Dimensions (l/w/h) in cm:  
**27,0 / 17,0 / 4,0**

**Ethernet Patch Cable, 2 m**

Artikelno.: **MX-OPT-CBL-LAN-2**



Description:  
Ethernet Patch Cable for MOBOTIX systems • Lenght 2 m/6,6 ft • 2x RJ45 plug with special MOBOTIX sealing ring

EAN:  
**4047438012317**  
HS:  
**85444210**  
Weight ( incl. packaging):  
**62 g**  
Dimensions (l/w/h) in cm:  
**23,5 / 15,0 / 2,0**

**Ethernet Patch Cable, 5 m**

Artikelno.: **MX-OPT-CBL-LAN-5**



Description:  
Ethernet Patch Cable for MOBOTIX systems • Lenght 5 m/16,4 ft • 2x RJ45 plug with special MOBOTIX sealing ring

EAN:  
**4047438012324**  
HS:  
**85444210**  
Weight ( incl. packaging):  
**144 g**  
Dimensions (l/w/h) in cm:  
**23,5 / 15,0 / 4,0**

**IO Connection Cable For M15, 0.15 m**

Artikelno.: **MX-FLEX-IO-CBL-015**



**Description:**

Length: 0.15 m/0,5 ft, IO cable to the front element of the camera, only for M1x (inside camera housing)

EAN:

**4047438019958**

HS:

**85444210**

Weight ( incl. packaging):

**10 g**

Dimensions (l/w/h) in cm:

**13,5 / 8,0 / 2,0**

**NPA Battery Cable, 2 m**

Artikelno.: **MX-CBL-NPA-BAT-2**



**Description:**

NPA-PoE Battery Cable • Provides a power supply for the camera from car batteries or other power sources from 12 to 24 Volts • With self-resetting fuse • RJ45 connector to PoE injector, „+/-“ terminals for power source • Can only be used with Mx-NPA PoE injector • Length: 2 m/6.6 ft

EAN:

**4047438013949**

HS:

**85444210**

Weight ( incl. packaging):

**54 g**

Dimensions (l/w/h) in cm:

**10,7 / 5,2 / 8,7**

**Sealing Ring For Hemispheric Sensor Modules, Black**

Artikelno.: **MX-OPT-Ring-L10-L12-BL**



**Description:**

Enables weather resistance when removing the plastic dome of black hemispheric sensor modules (S1x/M1x) • To avoid burns by the hot lens, the dome must not be removed within the reach of persons • Color: black

EAN:  
**4047438021241**

HS:  
**90079100**

Weight ( incl. packaging):  
**16 g**

Dimensions (l/w/h) in cm:  
**7,5 / 4,9 / 9,0**

**Sealing Ring For Hemispheric Sensor Modules, White**

Artikelno.: **MX-OPT-Ring-L10-L12-PW**



**Description:**

Enables weather resistance when removing the plastic dome of white hemispheric sensor modules (S1x/M1x) • To avoid burns by the hot lens, the dome must not be removed within the reach of persons • Color: white

EAN:  
**4047438021234**


HS:  
**90079100**

Weight ( incl. packaging):  
**16 g**

Dimensions (l/w/h) in cm:  
**7,5 / 4,9 / 9,0**

**Security Screw Set With Allen Bit For M1x/M2x**

Artikelno.: **MX-OPT-SEC-SCREWS-SET**



**Description:**

Triple set of anti-theft screws for plugs (4 pcs 6x50) and for machine threads (4 pcs M6x15, 4 pcs M6x30) to securely attach the VarioFlex wall mount • Incl. Allen bit for power screwdrivers (1/4" in drive with hole for security pin)

EAN:  
**4047438021265**

HS:  
**90079100**

Weight ( incl. packaging):  
**120 g**

Dimensions (l/w/h) in cm:  
**7,5 / 4,9 / 9,0**

**Blind Module M1x**

Artikelno.: **MX-SM-Blind-PW**



**Description:**

For M1x and M1x Thermal • When operating the camera, it needs to be fitted either with sensor or blind modules. This closes off the front element and protects the camera against foreign objects, insects and water.

EAN:  
**4047438019965**

HS:  
**90079100**

Weight ( incl. packaging):  
**38 g**

Dimensions (l/w/h) in cm:  
**6,2 / 3,9 / 9,0**

**MX-BPA-BOX**Artikelno.: **MX-OPT-BPA1-EXT****Description:**

Power supply for several MxBus modules of one MxBus line • 2x2 connection terminals for MxBus • 2 connection terminals for external power supply from 12 to 48 V DC (2 terminals) • Max. output rating: 9 W • IP65, -30 bis 60 °C / -22 to 140 °F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x, D2x

EAN:

**4047438025881**

HS:

**85299065**

Weight ( incl. packaging):

**120 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5****MX-NPA-Box**Artikelno.: **MX-OPT-NPA1-EXT****Description:**

Weatherproof PoE Injector (IEEE 802.3af) and network connector • Needs external power supply units and batteries from 12 to 57 V DC • Protection class IP65, -30 to 60°C / -22 to 140°F • Important: only use with original MOBOTIX patch cables • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x and D2x

EAN:

**4047438015424**

HS:

**85043180**

Weight ( incl. packaging):

**120 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5****Network Connector with Surge Protection, LSA Version**Artikelno.: **MX-Overvoltage-Protection-Box-LSA****Description:**

Weatherproof connection of one MOBOTIX patch cable (RJ45, from camera) and the network installation cable • Protects one MOBOTIX camera against surges of up to 4 kV on the PoE network cabling • Complete set including mounting supplies • Protection class IP65, -30 to 60°C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x, D2x

EAN:

**4047438018470**

HS:

**85299065**

Weight ( incl. packaging):

**146 g**

Dimensions (l/w/h) in cm:

**9,8 / 7,5 / 9,0****Network Connector with Surge Protection, RJ45 Version**Artikelno.: **MX-Overvoltage-Protection-Box-RJ45****Description:**

Weatherproof connection of two MOBOTIX patch cables (RJ45, one from the camera) • Protects one MOBOTIX camera against surges of up to 4 kV on the PoE network cabling • Complete set including mounting supplies • Protection class IP65, -30 to 60°C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x, D2x

EAN:

**4047438018463**

HS:

**85299065**

Weight ( incl. packaging):

**120 g**

Dimensions (l/w/h) in cm:

**9,8 / 7,5 / 9,0****MX-Input-Box**Artikelno.: **MX-OPT-Input1-EXT****Description:**

Weatherproof connection of external sensors • Connection to camera using MxBus • 6 self-powered inputs for connecting up to 6 external sensors • Protection class IP65, -30 to 60°C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x, D2x

EAN:

**4047438021227**

HS:

**85299065**

Weight ( incl. packaging):

**120 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5****MX-Output-Box**Artikelno.: **MX-OPT-Output1-EXT****Description:**

Weatherproof connection of external devices and power relays • Connection to the camera via MxBus • Six self-powered outputs (12 V, each 10 mA) • Two isolated outputs (can be switched to "self-powered" using a jumper: 12 V, max. 50 mA) • Protection class IP65, -30 to 60 °C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x, D2x

EAN:

**4047438021944**

HS:

**85299065**

Weight ( incl. packaging):

**120 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5**

**MX-232-IO-Box**Artikelno.: **MX-OPT-RS1-EXT****Description:**

Weatherproof connection of external sensors and switching of external devices via MOBOTIX cameras • Connection to camera using USB or MxBus • 2 self-powered inputs for connecting sensors • 2 outputs: 1 powered output, 1 isolated relay output (can be switched to second powered output) • RS232 interface when using MOBOTIX USB cable to connect to camera • Protection class IP65, -30 to 60°C / -22 to 140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x and D2x

EAN:

**4047438015417**

HS:

**85299065**

Weight (incl. packaging):

**120 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5****MX-GPS-Box**Artikelno.: **MX-OPT-GPS1-EXT****Description:**

Weatherproof GPS time base for MOBOTIX systems • Includes outdoor temperature and illumination sensors • Connects via MxBus 2-wire cable • Protection class IP65, -30 to 60°C / -22 to +140°F • Box can be mounted safely out of reach in the wall mounts of M1x, M2x, D1x and D2x

EAN:

**4047438015400**

HS:

**85299065**

Weight (incl. packaging):

**120 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5****MX-Proximity-Box**Artikelno.: **MX-PROX-BOX****Description:**

Weatherproof proximity sensor for MOBOTIX systems • Accurate detection of approaching objects based on radar microwave technology • Covered area (horizontal x vertical): 80° x 34° • Camera connection and supply via MxBus • Protection class IP66, -20 to 60°C / -4 to 140°F • Box can also be mounted behind walls (e.g. wooden, plastic, glass or dry walls) • It is not possible to install the MX-Proximity-Box behind some materials since they absorb or reflect the radar waves (e.g., metal or metal-coated surfaces). Other materials are better suited since they absorb radar waves only slightly (e.g., uncoated glass, plastics, various wood-based materials, drywall).

EAN:

**4047438025935**

HS:

**85299065**

Weight (incl. packaging):

**165 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5****MxDigitizer For S1x**Artikelno.: **MX-OPT-DIGI-INT****Description:**

Interface box to connect one analog camera directly to a S1x Body as alternative image source (instead of one sensor module) • Up to two MxDigitizer boxes or two analog cameras can be connected to one S1x Body • Easy integration of analog cameras into the MOBOTIX IP video system incl. the support of MOBOTIX integrated image analysis tools (e.g. MxActivitySensor) • Box digitizes the analog signal input (NTSC/PAL) • Output format PAL: 704 x 525 pixels, up to 25 frames per second • Output format NTSC: 640 x 480 pixels, up to 30 frames per second • BNC connection of analog camera to MxDigitizer • Sensor cable connection of MxDigitizer to S1x Body (to be ordered separately, maximum length 3 m/9.8 ft) • Operating conditions: Indoors, 0 to 40°C (32 to 104°F) • Color: white

EAN:

**4047438028790**

HS:

**85299065**

Weight (incl. packaging):

**120 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5**



## Mx2wire+ Set, Ethernet And PoE Via Two-Wire-Cable

Artikelno.: **MX-2WirePlus-Set-PW**



### Description:

Mx2wire+ turns an existing two-wire cable into a modern multimedia cable • Ethernet and PoE data transfer using a two-wire cable • Simple connection of 10/100 Mbps Ethernet end devices (e.g., IP camera, IP telephone) • Power supply for Mx2wire+ and end device via PoE/PoE+ or 48-57 V DC, 600 mA • Connected end devices are supplied with up to 13 watts via PoE (PoE class 3) • Maximum data transfer range of 500 m and data rate of up to 50 Mbps (depending on distance) • No need for expensive and time-consuming installation of network cables • Perfect for wireless communication is not possible (due to distance to sender, thickness of walls, etc.) • Network extension, including PoE, by connecting a Cat7 cable of up to 500 m in length as a two-wire cable • Simple installation in standard sockets (surface- or flush-mounted) • Two LEDs display current connection and supply statuses • Developed, produced and patented by MOBOTIX Germany • Ambient temperature: -30 to 50°C / -22 to 122°F • Complete set consisting of two Mx2wire+ units, on-walls sockets and mounting parts

EAN:

**4047438015356**

HS:

**85176200**

Weight (incl. packaging):

**696 g**

Dimensions (l/w/h) in cm:

**17,8 / 9,5 / 21,7**

## MxThinClient

Artikelno.: **Mx-A-TCLIENTA**



### Description:

PoE-supplied IP video device to transfer live pictures of cameras and door stations to a monitor/TV set • Password protected web interface • Automatic change of video source via sequencer (time-controlled) or via MxMessageSystem (event-controlled) • Input (connection to PoE switch): 1x Ethernet 100Base-T (RJ45) • Output (connection to monitor/TV set): 1x HDMI Type D (MicroHDMI) • Connection cables (Ethernet, HDMI) are not included • Indoor-use only: Protection class IP20, ambient temperature 0 to 40 °C (32 to 104°F) • With the supplied adhesive strips, the device can easily be attached to the backside of the monitor/TV

EAN:

**4047438028899**

HS:

**84714900**

Weight (incl. packaging):

**200 g**

Dimensions (l/w/h) in cm:

**13,2 / 12,2 / 4,2**

## ExtIO Extension Module For All MOBOTIX Cameras

Artikelno.: **MX-ExtIO**



### Description:

ExtIO Weatherproof extension for all MOBOTIX cameras (except Basic models) • Power supply: PoE (Class 2, IEEE 802.3af) or USB (connection cable to be ordered individually) • Microphone/speaker • Line-in / Line-out • PIR sensor for motion detection • Temperature sensor • 2 buttons (e.g., lights, door bell) • 2 galvanically separated inputs • 2 galvanically separated outputs • Protection class IP65, -30 to 60°C / -22 to 140°F • Robust housing made of fiber-reinforced plastic PBT-GF30 • Mounting to a wall or ceiling, optionally with MOBOTIX mounting accessories (to be ordered individually) • Connecting via Network or USB

EAN:

**4047438009850**

HS:

**85299065**

Weight (incl. packaging):

**936 g**

Dimensions (l/w/h) in cm:

**29,6 / 19,6 / 9,0**

## MxMultiSense Indoor (HS Code 8299065)

Artikelno.: **MX-MULTISENSE1**



### Description:

Multi-sensor module for indoor use with four environmental sensors: passive infrared sensor PIR, brightness sensor, temperature sensor and acoustic sensor (sound pressure) • Camera connection and supply via MxBus • MxBus cable length up to 100 m / 330 ft. • Power consumption: typ. 0.1 W • Status LED • Compact device using a screwable sensor module housing • Easy installation without accessories (e.g., in suspended ceilings) • Compatible with all MOBOTIX sensor module mounts and standard mounts for recessed spotlights • Protection class meets IP40 • IK05 • Ambient temperature: 0 to 40°C / 32 to 104°F • Housing color: white

EAN:

**4047438028851**

HS:

**85299065**

Weight (incl. packaging):

**110 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5**

## MxMultiSense Outdoor

Artikelno.: **MX-MULTISENSE1-EXT**



### Description:

Weatherproof multi-sensor module with four environmental sensors: passive infrared sensor PIR, brightness sensor, temperature sensor ( $\pm 0.1^\circ\text{C} / 0.18^\circ\text{F}$ ) and acoustic sensor (level of sound waves) • Camera connection and supply via MxBus: power consumption approx. 0.3 W, MxBus cable length up to 100 m / 330 ft. • Status LED • Compact device using a screwable sensor module housing • Easy installation without accessories (e.g., in suspended ceilings) • Compatible with all MOBOTIX mounts for sensor modules and standard mounts for recessed spotlights • Protection class IP66 • IK05 • Ambient temperature -20 to 60°C / -4 to 140°F • Housing color: white

EAN:

**4047438028905**

HS:

**85299065**

Weight (incl. packaging):

**110 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5**

## Extension Module For c25, i25, p25 And v25

Artikelno.: **MX-OPT-IO3-INT**



### Description:

Extension module for the indoor cameras x25 (to be mounted on the backside) • Not compatible with x26 indoor cameras • For the connection of external sensors (e.g., door or window contacts) and switching of external devices (e.g., relays with lamps and motors) • Two input lines (galvanically isolated, 0 to 48 V AC/DC) • Two output lines: 2x isolated (contact load max. 30 W or 1 A or 48 V AC/DC) or 2x 12 V DC (max. 50 mA per output line) • MxBus terminal (1x2) • Ambient temperature: 0 to 4°C (32 to 104°F) • Power consumption: 1 W

EAN:

**4047438025928**

HS:

**85299065**

Weight (incl. packaging):

**45 g**

Dimensions (l/w/h) in cm:

**10,7 / 5,2 / 8,7**

## Extension Module For c26, i26, p26 And v26

Artikelno.: **Mx-A-IOA-IC**



### Description:

Expansion module for Indoor Cameras c26, i26, p26 and v26 (installed on the back) • Not suitable for x25 indoor cameras • For connecting external sensors (e.g., door and window contacts) and switches of external devices (e.g., relays with lamps and motors) • Two inputs (galvanically separated): 0 V to 48 V AC/DC • Two outputs: 2x floating (load per contact max. 30 W or 1 A or 48 V AC/DC) or 2x 12 V DC (max. 50 mA per output) • 2x MxBus terminal connector (MxBus will be supported only by later available hardware versions of the x26 cameras) • Ambient temperature: 0°C to 40°C (32°F to 104°F) • Power consumption: 1 W

EAN:

**4047438029032**

HS:

**85299065**

Weight (incl. packaging):

**45 g**

Dimensions (l/w/h) in cm:

**10,7 / 5,2 / 8,7**

## MxSplitProtect Installation Box, IP66

Artikelno.: **Mx-A-SPA**



### Description:

Weatherproof installation box with integrated 4-kV surge protection (Type 2 P4) for connecting two IP cameras/PoE devices using one Ethernet cable • Interfaces (weatherproof): 1 LSA (with shield clip) for Ethernet 2 100Base-T, 2 MxRJ45 for Ethernet 100Base-T with PoE Mode A, 1 protective earth terminal • IP66 and IK08, ambient temperature: -30°C to 60°C (-22°F to 140°F) • Accessories (available separately): MxSplitProtectHR Hat Rail module (Mx-A-SPA-HR), cover with camera mount in three versions (Mx-A-SPCA-M/-H/-V), pole mount (MX-MH-SecureFlex-ESWS) • Housing color: white

EAN:  
**4047438030229**

HS:  
**85299065**

Weight (incl. packaging):  
**1.200 g**

Dimensions (l/w/h) in cm:  
**30,5 / 24,0 / 16,5**

## MxSplitProtectHR Hat Rail Module

Artikelno.: **Mx-A-SPA-HR**



### Description:

Compatible with MxSplitProtect Installation Box (Mx-A-SPA): Hat rail module (for 35 mm DIN rails) with integrated 4-kV surge protection (Type 2 P4) for connecting two IP cameras/PoE devices using one Ethernet cable • Interfaces: 3x RJ45 for Ethernet 100Base-T, 1x protective earth terminal • Only use in indoor areas, ambient temperature: 0°C to 40°C (32°F to 104°F) • Accessories (available separately): MxSwitch (MX-SWITCH1) • Housing color: gray

EAN:  
**4047438030236**

HS:  
**85299065**

Weight (incl. packaging):  
**131 g**

Dimensions (l/w/h) in cm:  
**9,8 / 7,5 / 9,0**

## MxSplitProtect Cover, M-Cameras

Artikelno.: **Mx-A-SPCA-M**



### Description:

Cover/mounting option with camera mount • Accessories for the MxSplitProtect Installation Box (Mx-A-SPA) • Also possible to install the standard VarioFlex wall mount of an M15/M16/M25/M26 camera directly to the cover • Color: white

EAN:  
**4047438028820**

HS:  
**85299065**

Weight (incl. packaging):  
**850 g**

Dimensions (l/w/h) in cm:  
**30,5 / 24,0 / 16,5**

## MxSplitProtect Cover, Horizontal

Artikelno.: **Mx-A-SPCA-H**



### Description:

Cover/mounting option with camera mount • Accessories for the MxSplitProtect Installation Box (Mx-A-SPA) • Also possible to (vertically) install a Q2x (orD2x) camera with a 15° tilt angle without an additional mount directly to the cover • Color: white

EAN:  
**4047438028837**

HS:  
**85299065**

Weight (incl. packaging):  
**850 g**

Dimensions (l/w/h) in cm:  
**30,5 / 24,0 / 16,5**

## MxSplitProtect Cover, Vertical

Artikelno.: **Mx-A-SPCA-V**



### Description:

Cover/mounting option with camera mount • Accessories for the MxSplitProtect Installation Box (Mx-A-SPA) • Also possible to (horizontally) install a Q2x/D2x camera without an additional mount directly to the cover • Color: white

EAN:  
**4047438028844**

HS:  
**85299065**

Weight (incl. packaging):  
**850 g**

Dimensions (l/w/h) in cm:  
**30,5 / 24,0 / 16,5**

## MxIRLight Infrared Illuminator (860 nm), 120°x120°

Artikelno.: **Mx-A-IRA-120**



### Description:

Infrared illuminator with 120° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 20 m (66 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white

EAN:  
**4047438030342**

HS:  
**85394900**

Weight (incl. packaging):  
**900 g**

Dimensions (l/w/h) in cm:  
**17,7 / 21,4 / 12,1**

## MxIRLight Infrared Illuminator (860 nm), 90°x90°

Artikelno.: **Mx-A-IRA-90**



### Description:

Infrared illuminator with 90° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 35 m (115 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white

EAN:

**4047438030359**

HS:

**85394900**

Weight (incl. packaging):

**900 g**

Dimensions (l/w/h) in cm:

**17,7 / 21,4 / 12,1**

## MxIRLight Infrared Illuminator (860 nm), 60°x60°

Artikelno.: **Mx-A-IRA-60**



### Description:

Infrared illuminator with 60° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 50 m (165 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white

EAN:

**4047438030366**

HS:

**85394900**

Weight (incl. packaging):

**900 g**

Dimensions (l/w/h) in cm:

**17,7 / 21,4 / 12,1**

## MxIRLight Infrared Illuminator (860 nm), 45°x45°

Artikelno.: **Mx-A-IRA-45**



### Description:

Infrared illuminator with 45° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 80 m (262 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white

EAN:

**4047438030373**

HS:

**85394900**

Weight (incl. packaging):

**900 g**

Dimensions (l/w/h) in cm:

**17,7 / 21,4 / 12,1**

## MxIRLight Infrared Illuminator (860 nm), 30°x30°

Artikelno.: **Mx-A-IRA-30**



### Description:

Infrared illuminator with 30° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 120 m (394 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white

EAN:

**4047438030380**

HS:

**85394900**

Weight (incl. packaging):

**900 g**

Dimensions (l/w/h) in cm:

**17,7 / 21,4 / 12,1**

## MxIRLight Infrared Illuminator (860 nm), 15°x15°

Artikelno.: **Mx-A-IRA-15**



### Description:

Infrared illuminator with 15° illumination angle (horizontal and vertical), aluminum housing • 860 nm • IP67 • Range: up to 160 m (525 ft.) • PoE+ power supply via network cable (IEEE 802.3at), 19 W (max.) power consumption • Photosensor for automatic switching on/off (threshold value: 3 lux, delay for switching off: 150 s) • Including standard mount for installing on wall and ceiling, screws, preassembled 0.9 m patch cable with RJ45 connector and MOBOTIX special sealing ring • Optional accessories: mounting brackets for M1x/M2x (Mx-M-IRA-ML/Mx-M-IRA-M) • Housing color: white

EAN:

**4047438030397**

HS:

**85394900**

Weight (incl. packaging):

**900 g**

Dimensions (l/w/h) in cm:

**17,7 / 21,4 / 12,1**

## MxIRLight Mounting Brackets For M1x

Artikelno.: **Mx-M-IRA-ML**



### Description:

Mounting brackets „Large“ for the MOBOTIX M15/M16 AllroundDual cameras • Accessories for the MxIRLight Infrared Illuminator • Material: aluminum • Color: white

EAN:

**4047438030403**

HS:

**85399090**

Weight (incl. packaging):

**400 g**

Dimensions (l/w/h) in cm:

**8,5 / 2,0 / 18,0**



## MxIRLight Mounting Brackets For M2x

Artikelno.: **Mx-M-IRA-M**



### Description:

Mounting brackets for the MOBOTIX M25/M26 Allround cameras • Accessories for the MxIRLight Infrared Illuminator • Material: aluminum • Color: white

EAN:

**4047438030410**

HS:

**85399090**

Weight (incl. packaging):

**280 g**

Dimensions (l/w/h) in cm:

**10,0 / 2,0 / 13,0**

### MxSwitch For DIN Rail Mounting

Artikelno.: **MX-SWITCH1**



**Description:**

PoE+ Switch for the top-hat rail • 5x RJ45 port with 100 MBit/s (1x uplink, 4x PoE+ with max. 75 W) • Supply: 48 V DC, max. 75 W • Simplified cabling for door stations due to available connectivity for anti-theft protection, door opener and MxBus • MxBus, anti-theft protection, door and lock contact can be connected via separate wires of the ethernet cable

EAN:

**4047438028882**

HS:

**85176200**

Weight ( incl. packaging):

**400 g**

Dimensions (l/w/h) in cm:

**17,5 / 14,0 / 13,5**

### PoE Power Adapter Set, EU

Artikelno.: **MX-NPA-PoE-EU-Set**



**Description:**

PoE injector incl. crossover function for direct connection to the PC • With power plug for Europe • For all MOBOTIX cameras (except for M1 und M10), Mx2wire+ and all PoE devices • Provides compliant PoE power supply (IEEE 802.3af) for direct connection to PC and camera • Kit includes blue adapter with 3 sockets RJ45 and universal power supply with RJ45 plug

EAN:

**4047438012249**

HS:

**85043180**

Weight ( incl. packaging):

**273 g**

Dimensions (l/w/h) in cm:

**14,8 / 9,8 / 9,0**

### PoE Power Adapter Set, INT

Artikelno.: **MX-NPA-PoE-INT-Set**



**Description:**

PoE injector incl. crossover function for direct connection to the PC • With 4 exchangeable power plugs for Europe, United Kingdom, USA and Australia • For all MOBOTIX cameras (except for M1 und M10), Mx2wire+ and all PoE devices • Provides compliant PoE power supply (IEEE 802.3af) for direct connection to PC and camera • Kit includes blue adapter with 3 sockets RJ45 and universal power supply with RJ45 plug

EAN:

**4047438012256**

HS:

**85043180**

Weight ( incl. packaging):

**314 g**

Dimensions (l/w/h) in cm:

**14,8 / 9,8 / 9,0**

### PoE Power Adapter

Artikelno.: **MX-NPA-PoE-RJ**



**Description:**

PoE injector (IEEE 802.3af) incl. crossover function for direct connection to the PC • Blue adapter with 3 sockets RJ45 and universal power supply with RJ45 plug • Without power plug, additional power supply (12 to 57 V DC) and connection cable needed

EAN:

**4047438013932**

HS:

**85043180**

Weight ( incl. packaging):

**90 g**

Dimensions (l/w/h) in cm:

**7,5 / 4,9 / 9,0**

### Universal Power Supply With 4 Power Plugs

Artikelno.: **MX-SNT-INT-PoE**



**Description:**

For international use thanks to broad input voltage range and interchangeable power plugs (no tools required) • With 4 power plugs for Europe, United Kingdom, USA and Australia • Connections: 1x RJ45 (for adapter), 1x network (up to 4x interchangeable adapter) • Nominal data input: 100 V to 240 V, 50 to 60 Hz/400 mA • Nominal data output: DC 24 V/750 mA • Ambient temperature: 0 to 40°C / 32 to 104 °F

EAN:

**4047438013925**

HS:

**85043180**

Weight ( incl. packaging):

**160 g**

Dimensions (l/w/h) in cm:

**9,8 / 7,5 / 9,0**





## Simply Smart. Simply Manageable.

There's no such thing as too big or too small. The MOBOTIX IP Video Door Station is a modular system that can be adapted to customers' changing requirements. For a majority of applications, MOBOTIX recommend the practical complete sets, together with all the modules required for fast, easy and secure system installation.



**MxDisplay+, White**Artikelno.: **MX-DISPLAY3****Description:**

MxDisplay+ with second generation CPU • Indoor remote station for MOBOTIX Door Stations and video systems • Full duplex hands-free talking, HD sound with echo/noise suppression and automatic volume control • Ambilight sensor • 3 inputs, 1 relay output, connection for external temperature sensor and MxBus (MxMessageSystem) • Ethernet, RFID and Wi-Fi • 1 x admin card • Mounting parts • Frame and in-wall housing can be ordered separately (for example, FlatMount Frame MX-OPT-FlatMount-EXT-PW) • Color: white

EAN:

**4047438027151**

HS:

**85285291**

Weight (incl. packaging):

**300 g**

Dimensions (l/w/h) in cm:

**13,8 / 6,5 / 14,8****MxDisplay+, Black**Artikelno.: **MX-DISPLAY3-b****Description:**

MxDisplay+ with second generation CPU • Indoor remote station for MOBOTIX Door Stations and video systems • Full duplex hands-free talking, HD sound with echo/noise suppression and automatic volume control • Ambilight sensor • 3 inputs, 1 relay output, connection for external temperature sensor and MxBus (MxMessageSystem) • Ethernet, RFID and Wi-Fi • 1 x admin card • Mounting parts • Frame and in-wall housing can be ordered separately (for example, FlatMount Frame MX-OPT-FlatMount-EXT-BL) • Color: black

EAN:

**4047438027168**

HS:

**85285291**

Weight (incl. packaging):

**300 g**

Dimensions (l/w/h) in cm:

**13,8 / 6,5 / 14,8****MxDisplay+ Outdoor, White**Artikelno.: **MX-DISPLAY3-EXT****Description:**

Weatherproof MxDisplay+ for mounting outdoors or in rooms with special requirements • Operating conditions: IP65, -30 to 60°C (-22 to 140°F) • Remote station for MOBOTIX Door Stations and video systems • Full duplex hands-free talking • HD sound with echo/noise suppression and automatic volume control • Ambilight sensor • 3 inputs, 1 relay output, connection for external temperature sensor and MxBus • Ethernet, RFID and WiFi (2.4 & 5 GHz), Bluetooth V3.0 HS • MxBus and Bluetooth available with upcoming software update • 1x admin card • Mounting parts • Frame and in-wall housing to be ordered separately (e.g., FlatMount Frame MX-OPT-FlatMount-EXT-PW) • Color: white

EAN:

**4047438028776**

HS:

**85285291**

Weight (incl. packaging):

**300 g**

Dimensions (l/w/h) in cm:

**13,8 / 6,5 / 14,8****MxDisplay+ Outdoor, Black**Artikelno.: **MX-DISPLAY3-EXT-b****Description:**

Weatherproof MxDisplay+ for mounting outdoors or in rooms with special requirements • Operating conditions: IP65, -30 to 60°C (-22 to 140°F) • Remote station for MOBOTIX Door Stations and video systems • Full duplex hands-free talking • HD sound with echo/noise suppression and automatic volume control • Ambilight sensor • 3 inputs, 1 relay output, connection for external temperature sensor and MxBus • Ethernet, RFID and WiFi (2.4 & 5 GHz), Bluetooth V3.0 HS • MxBus and Bluetooth available with upcoming software update • 1x admin card • Mounting parts • Frame and in-wall housing to be ordered separately (e.g., FlatMount Frame MX-OPT-FlatMount-EXT-BL) • Color: black

EAN:

**4047438028783**

HS:

**85285291**

Weight (incl. packaging):

**300 g**

Dimensions (l/w/h) in cm:

**13,8 / 6,5 / 14,8**

**T25 Smart Access Set 1**

Artikelno.: **MX-T25-SMART-SET1**



**Description:**

T25 IP Video Door Station with MxDisplay+ as preconfigured complete set for use in family homes • Delivery outdoor remote station (IP65, -30 to 50°C, -22 to 122°F): CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) and Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • BellRFID module with one big key with blue functional bar, 1x admin and 6x user card, MX-OPT-IO2 Ethernet board, double frame set for in-wall or on-wall installation, pen for plastic film, mounting material • Delivery indoor remote station: MX-DISPLAY3, FlatMount Frame with In-Wall-Housing • All devices and frames colored in white

EAN:  
**4047438028769**

HS:  
**85258091**

Weight (incl. packaging):  
**2.500 g**

Dimensions (l/w/h) in cm:  
**34,0 / 34,0 / 16,0**

**T25 Smart Access Set 2**

Artikelno.: **MX-T25-SMART-SET2**



**Description:**

T25 IP Video Door Station with MxDisplay+ and MxSwitch • Preconfigured complete set for use in family homes • Delivery outdoor remote station (IP65, -30 to 50°C, -22 to 122°F): CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) and Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • BellRFID module with one big key with blue functional bar, 1x admin and 6x user card, MX-OPT-IO2 Ethernet board, double frame set for in-wall or on-wall installation, pen for plastic film, mounting material • Delivery indoor remote station: MX-DISPLAY3, FlatMount Frame with In-Wall-Housing • All devices and frames colored in white

EAN:  
**4047438028875**

HS:  
**85258091**

Weight (incl. packaging):  
**2.700 g**

Dimensions (l/w/h) in cm:  
**34,0 / 34,0 / 16,0**

**T25 6MP Set 1, Ethernet, Keypad, White**

Artikelno.: **MX-T25-SET1**



**Description:**

Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info Module • MX-OPT-IO2 Ethernet board • IP65, -30 to 50°C (-22 to 122°F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: White

EAN:  
**4047438025362**

HS:  
**85258091**

Weight (incl. packaging):  
**3.000 g**

Dimensions (l/w/h) in cm:  
**34,5 / 34,0 / 16,0**

**T25 6MP Set 2, Two-Wire, Keypad, DoorMaster, White**

Artikelno.: **MX-T25-SET2**



**Description:**

Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info2wire+ (Info Module with indoor unit) • MX-DoorMaster (in-wall) with different frames • IP65, -30 to 50°C (-22 to 122°F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: White

EAN:  
**4047438025379**

HS:  
**85258091**

Weight (incl. packaging):  
**3.000 g**

Dimensions (l/w/h) in cm:  
**34,5 / 34,0 / 16,0**

**T25 6MP Set 3, Ethernet, Keypad, DoorMaster, White**

Artikelno.: **MX-T25-SET3**



**Description:**

Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info Module • MX-OPT-IO2 Ethernet board • MX-DoorMaster (in-wall) with different frames • IP65, -30 to 50°C (-22 to 122°F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: White

EAN:  
**4047438025386**

HS:  
**85258091**

Weight (incl. packaging):  
**3.000 g**

Dimensions (l/w/h) in cm:  
**34,5 / 34,0 / 16,0**

## Supplementary Program (SUP)

The supplementary program encompasses other camera models which include complete sets that are pre-assembled and focus calibrated. This service takes approximately 5 business days. These kits can also be ordered from the standard program as individual components for self-assembly.

Please note: Black colored IP Video Door Stations should NOT be exposed to direct sunlight (risk of overheating on dark surfaces).

### T25 6MP Set 1, Ethernet, Keypad, Dark Gray

Artikelno.: **MX-T25-SET1-d**



#### Description:

Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info Module • MX-OPT-IO2 Ethernet board • IP65, -30 to 50°C (-22 to 122°F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: Dark Gray

EAN:

**4047438025522**

HS:

**85258091**

Weight (incl. packaging):

**3.000 g**

Dimensions (l/w/h) in cm:

**34,0 / 34,0 / 16,0**

### T25 6MP Set 1, Ethernet, Keypad, Black

Artikelno.: **MX-T25-SET1-b**



#### Description:

Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info Module • MX-OPT-IO2 Ethernet board • IP65, -30 to 50°C (-22 to 122°F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: Black

EAN:

**4047438025447**

HS:

**85258091**

Weight (incl. packaging):

**3.000 g**

Dimensions (l/w/h) in cm:

**34,5 / 34,0 / 16,0**

### T25 6MP Set 1, Ethernet, Keypad, Silver

Artikelno.: **MX-T25-SET1-s**



#### Description:

Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info Module • MX-OPT-IO2 Ethernet board • IP65, -30 to 50°C (-22 to 122°F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: Silver

EAN:

**4047438025607**

HS:

**85258091**

Weight (incl. packaging):

**3.000 g**

Dimensions (l/w/h) in cm:

**34,5 / 34,0 / 16,0**

### T25 6MP Set 2, Two-Wire, Keypad, DoorMaster, Silver

Artikelno.: **MX-T25-SET2-s**



#### Description:

Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info2wire+ (Info Module with indoor unit) • MX-DoorMaster (in-wall) with different frames • IP65, -30 to 50°C (-22 to 122°F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: Silver

EAN:

**4047438025614**

HS:

**85258091**

Weight (incl. packaging):

**3.000 g**

Dimensions (l/w/h) in cm:

**34,5 / 34,0 / 16,0**

### T25 6MP Set 2, Two-Wire, Keypad, DoorMaster, Dark Gray

Artikelno.: **MX-T25-SET2-d**



#### Description:

Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info2wire+ (Info Module with indoor unit) • MX-DoorMaster (in-wall) with different frames • IP65, -30 to 50°C (-22 to 122°F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: Dark Gray

EAN:

**4047438025539**

HS:

**85258091**

Weight (incl. packaging):

**3.000 g**

Dimensions (l/w/h) in cm:

**34,0 / 34,0 / 16,0**

**T25 6MP Set 2, Two-Wire, Keypad, DoorMaster, Black**

Artikelno.: **MX-T25-SET2-b**



**Description:**

Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info2wire+ (Info Module with indoor unit) • MX-DoorMaster (in-wall) with different frames • IP65, -30 to 50°C (-22 to 122°F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: Black

EAN:  
**4047438025454**

HS:  
**85258091**

Weight (incl. packaging):  
**3.000 g**

Dimensions (l/w/h) in cm:  
**34,5 / 34,0 / 16,0**

**T25 6MP Set 3, Ethernet, Keypad, DoorMaster, Silver**

Artikelno.: **MX-T25-SET3-s**



**Description:**

Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info Module • MX-OPT-IO2 Ethernet board • MX-DoorMaster (in-wall) with different frames • IP65, -30 to 50°C (-22 to 122°F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: Silver

EAN:  
**4047438025621**

HS:  
**85258091**

Weight (incl. packaging):  
**3.000 g**

Dimensions (l/w/h) in cm:  
**34,5 / 34,0 / 16,0**

**T25 6MP Set 3, Ethernet, Keypad, DoorMaster, Dark Gray**

Artikelno.: **MX-T25-SET3-d**



**Description:**

Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info Module • MX-OPT-IO2 Ethernet board • MX-DoorMaster (in-wall) with different frames • IP65, -30 to 50°C (-22 to 122°F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: Dark Gray

EAN:  
**4047438025546**

HS:  
**85258091**

Weight (incl. packaging):  
**3.000 g**

Dimensions (l/w/h) in cm:  
**34,0 / 34,0 / 16,0**

**T25 6MP Set 3, Ethernet, Keypad, DoorMaster, Black**

Artikelno.: **MX-T25-SET3-b**



**Description:**

Complete Kit IP Video Door Station • CamCore T25 with 6 Megapixel Moonlight Sensor, color (day) • Fisheye Lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • KeypadRFID incl. one admin and six user cards • Info Module • MX-OPT-IO2 Ethernet board • MX-DoorMaster (in-wall) with different frames • IP65, -30 to 50°C (-22 to 122°F) • Triple frame set for in-wall or on-wall installation • USB stick, pen for plastic film, mounting material • Color: Black

EAN:  
**4047438025461**

HS:  
**85258091**

Weight (incl. packaging):  
**3.000 g**

Dimensions (l/w/h) in cm:  
**34,5 / 34,0 / 16,0**

**CamCore T25, 6MP, B016, Day, White**

Artikelno.: **MX-T25-D016**



**Description:**

Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: White

EAN:  
**4047438025263**

HS:  
**85258091**

Weight (incl. packaging):  
**1.240 g**

Dimensions (l/w/h) in cm:  
**19,6 / 14,8 / 9,0**

**CamCore T25, 6MP, B016, Day, Silver**

Artikelno.: **MX-T25-D016-s**



**Description:**

Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Silver

EAN:  
**4047438025270**

HS:  
**85258091**

Weight (incl. packaging):  
**1.240 g**

Dimensions (l/w/h) in cm:  
**19,6 / 14,8 / 9,0**

**CamCore T25, 6MP, B016, Day, Dark Gray**

Artikelno.: **MX-T25-D016-d**



**Description:**

Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Dark Gray

EAN:  
**4047438025287**

HS:  
**85258091**

Weight (incl. packaging):  
**1.240 g**

Dimensions (l/w/h) in cm:  
**19,6 / 14,8 / 9,0**

**CamCore T25, 6MP, B016, Day, Black**

Artikelno.: **MX-T25-D016-b**



**Description:**

Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, color (day) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Black

EAN:  
**4047438025300**

HS:  
**85258091**

Weight (incl. packaging):  
**1.240 g**

Dimensions (l/w/h) in cm:  
**19,6 / 14,8 / 9,0**

**CamCore T25, 6MP, B016, Night, White**

Artikelno.: **MX-T25-N016**



**Description:**

Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: White

EAN:  
**4047438025317**

HS:  
**85258091**

Weight (incl. packaging):  
**1.240 g**

Dimensions (l/w/h) in cm:  
**19,6 / 14,8 / 9,0**

**CamCore T25, 6MP, B016, Night, Silver**

Artikelno.: **MX-T25-N016-s**



**Description:**

Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Silver

EAN:  
**4047438025324**

HS:  
**85258091**

Weight (incl. packaging):  
**1.240 g**

Dimensions (l/w/h) in cm:  
**19,6 / 14,8 / 9,0**

**CamCore T25, 6MP, B016, Night, Dark Gray**

Artikelno.: **MX-T25-N016-d**



**Description:**

Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Dark Gray

EAN:

**4047438025331**

HS:

**85258091**

Weight (incl. packaging):

**1.240 g**

Dimensions (l/w/h) in cm:

**19,6 / 14,8 / 9,0**

**CamCore T25, 6MP, B016, Night, Black**

Artikelno.: **MX-T25-N016-b**



**Description:**

Hemispheric IP door station camera with 6 Megapixel Moonlight Sensor, B/W (night) • HD premium fisheye lens B016 (focal length 1.6 mm, f/2.0, 180° x 180°) • Max. image size: 6MP (3072 x 2048) • IP65, -30 to 50°C (-22 to 122°F) • Internal DVR: 4 GB microSD • LED lighting strips, two buttons (doorbell, outdoor light), temperature sensor, shock detector, MxActivitySensor, MxAnalytics, ethernet patch cable 0.5 m/1.6 ft • Interfaces: Ethernet 10/100 (RJ45 and LSA), MxBus, USB • Color: Black

EAN:

**4047438025355**

HS:

**85258091**

Weight (incl. packaging):

**1.240 g**

Dimensions (l/w/h) in cm:

**19,6 / 14,8 / 9,0**

**BellRFID Bell Button Set F1**Artikelno.: **MX-Bell1-Button-F1****Description:**

1 big key with blue functional bar • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: [www.mobotix.com](http://www.mobotix.com) > Support • Delivery with UV resistant paper label

EAN:

**4047438017190**

HS:

**85299065**

Weight (incl. packaging):

**94 g**

Dimensions (l/w/h) in cm:

**10,3 / 1,7 / 10,3****BellRFID Bell Button Set F2**Artikelno.: **MX-Bell1-Button-F2****Description:**

2 medium-sized keys with blue functional bar • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: [www.mobotix.com](http://www.mobotix.com) > Support • Delivery with UV resistant paper label

EAN:

**4047438017176**

HS:

**85299065**

Weight (incl. packaging):

**94 g**

Dimensions (l/w/h) in cm:

**10,3 / 1,7 / 10,3****BellRFID Bell Button Set F3**Artikelno.: **MX-Bell1-Button-F3****Description:**

1 medium-sized and 2 small keys with blue functional bar • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: [www.mobotix.com](http://www.mobotix.com) > Support • Delivery with UV resistant paper label

EAN:

**4047438017527**

HS:

**85299065**

Weight (incl. packaging):

**94 g**

Dimensions (l/w/h) in cm:

**10,3 / 1,7 / 10,3****BellRFID Bell Button Set F4**Artikelno.: **MX-Bell1-Button-F4****Description:**

4 small keys with blue functional bar • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: [www.mobotix.com](http://www.mobotix.com) > Support • Delivery with UV resistant paper label

EAN:

**4047438017183**

HS:

**85299065**

Weight (incl. packaging):

**94 g**

Dimensions (l/w/h) in cm:

**10,3 / 1,7 / 10,3****BellRFID Bell Button Set 05**Artikelno.: **MX-Bell1-Button-05****Description:**

5 small keys (without blue functional bar) • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: [www.mobotix.com](http://www.mobotix.com) > Support • Delivery with UV resistant paper label

EAN:

**4047438017534**

HS:

**85299065**

Weight (incl. packaging):

**94 g**

Dimensions (l/w/h) in cm:

**10,3 / 1,7 / 10,3****BellRFID Bell Button Set XL1**Artikelno.: **MX-Bell1-Button-XL1****Description:**

1 big XL key (without blue functional bar) • For usage with any BellRFID base module (to be ordered individually) • Suitable for all colors • Protection class IP65, -30 to 50°C / -22 to 122°F • Printing service free of charge: [www.mobotix.com](http://www.mobotix.com) > Support • Delivery with UV resistant paper label

EAN:

**4047438017169**

HS:

**85299065**

Weight (incl. packaging):

**94 g**

Dimensions (l/w/h) in cm:

**10,3 / 1,7 / 10,3**

**BellRFID Base Module, White**Artikelno.: **MX-Bell1-Core-EXT-PW****Description:**

BellRFID access module for MOBOTIX IP Video Door Stations • For usage with any BellRFID Bell Button Set (to be ordered individually) • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: White

EAN:

**4047438017152**

HS:

**85299065**

Weight (incl. packaging):

**256 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5****BellRFID Base Module, Silver**Artikelno.: **MX-Bell1-Core-EXT-SV****Description:**

BellRFID access module for MOBOTIX IP Video Door Stations • For usage with any BellRFID Bell Button Set (to be ordered individually) • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrierte RFID-Technik für schlüssellosen Zutritt • Stromversorgung über die Türkamera via Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Silver

EAN:

**4047438017114**

HS:

**85299065**

Weight (incl. packaging):

**256 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5****BellRFID Base Module, Dark Gray**Artikelno.: **MX-Bell1-Core-EXT-DG****Description:**

BellRFID access module for MOBOTIX IP Video Door Stations • For usage with any BellRFID Bell Button Set (to be ordered individually) • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to +50°C / -22 to 122°F • Color: Dark Gray

EAN:

**4047438017121**

HS:

**85299065**

Weight (incl. packaging):

**256 g**

Dimensions (l/w/h) in cm:

**10,5 / 10,3 / 6,5****BellRFID Base Module, Black**Artikelno.: **MX-Bell1-Core-EXT-BL****Description:**

BellRFID access module for MOBOTIX IP Video Door Stations • For usage with any BellRFID Bell Button Set (to be ordered individually) • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Black

EAN:

**4047438017145**

HS:

**85299065**

Weight (incl. packaging):

**256 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5**



**Keypad With RFID Technology, White**Artikelno.: **MX-Keypad1-EXT-PW****Description:**

Keypad access module for MOBOTIX IP Video Door Stations • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: White

EAN:

**4047438014946**

HS:

**85371091**

Weight (incl. packaging):

**210 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5****Keypad With RFID Technology, Silver**Artikelno.: **MX-Keypad1-EXT-SV****Description:**

Keypad access module for MOBOTIX IP Video Door Stations • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrierte RFID-Technik für schlüssellosen Zutritt • Stromversorgung über die Türkamera via Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Silver

EAN:

**4047438014984**

HS:

**85371091**

Weight (incl. packaging):

**210 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5****Keypad With RFID Technology, Dark Gray**Artikelno.: **MX-Keypad1-EXT-DG****Description:**

Keypad access module for MOBOTIX IP Video Door Stations • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Dark Gray

EAN:

**4047438014977**

HS:

**85371091**

Weight (incl. packaging):

**210 g**

Dimensions (l/w/h) in cm:

**10,0 / 6,5 / 10,0****Keypad With RFID Technology, Black**Artikelno.: **MX-Keypad1-EXT-BL****Description:**

Keypad access module for MOBOTIX IP Video Door Stations • Incl. one admin and five user RFID cards • Doorbell function and mailbox control • Integrated RFID technology for keyless entry • Powered by the door camera via MxBus • Up to 60 hrs backup power supply using MX-DoorMaster (accessory) • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Black

EAN:

**4047438014960**

HS:

**85371091**

Weight (incl. packaging):

**210 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5**

**Info Module With LEDs, White**Artikelno.: **MX-Info1-EXT-PW****Description:**

Standard info module for MOBOTIX IP Video Door Stations • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: [www.mobotix.com](http://www.mobotix.com) > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: White

EAN:

**4047438014991**

HS:

**85414090**

Weight ( incl. packaging):

**193 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5****Info Module With LEDs, Silver**Artikelno.: **MX-Info1-EXT-SV****Description:**

Standard info module for MOBOTIX IP Video Door Stations • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: [www.mobotix.com](http://www.mobotix.com) > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Silver

EAN:

**4047438015035**

HS:

**85414090**

Weight ( incl. packaging):

**193 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5****Info Module With LEDs, Dark Gray**Artikelno.: **MX-Info1-EXT-DG****Description:**

Standard info module for MOBOTIX IP Video Door Stations • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: [www.mobotix.com](http://www.mobotix.com) > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Dark Gray

EAN:

**4047438015028**

HS:

**85414090**

Weight ( incl. packaging):

**193 g**

Dimensions (l/w/h) in cm:

**11,0 / 10,0 / 6,5****Info Module With LEDs, Black**Artikelno.: **MX-Info1-EXT-BL****Description:**

Standard info module for MOBOTIX IP Video Door Stations • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: [www.mobotix.com](http://www.mobotix.com) > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Black

EAN:

**4047438015011**

HS:

**85414090**

Weight ( incl. packaging):

**193 g**

Dimensions (l/w/h) in cm:

**10,5 / 6,8 / 10,5**

**Info Module Mx2wire+ With LEDs, White**Artikelno.: **MX-2wirePlus-Info1-EXT-PW****Description:**

Info module with Mx2wire+ technology and a second Mx2wire+ unit for mounting inside the building • To connect and supply power to the door station via existing two-wire cabling instead of a network cable • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: [www.mobotix.com](http://www.mobotix.com) > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: White

EAN:

**4047438015042**

HS:

**85176200**

Weight ( incl. packaging):

**626 g**

Dimensions (l/w/h) in cm:

**19,6 / 14,8 / 9,0****Info Module Mx2wire+ With LEDs, Silver**Artikelno.: **MX-2wirePlus-Info1-EXT-SV****Description:**

Info module with Mx2wire+ technology and a second Mx2wire+ unit for mounting inside the building • To connect and supply power to the door station via existing two-wire cabling instead of a network cable • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: [www.mobotix.com](http://www.mobotix.com) > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Silver

EAN:

**4047438015080**

HS:

**85176200**

Weight ( incl. packaging):

**626 g**

Dimensions (l/w/h) in cm:

**19,6 / 14,8 / 9,0****Info Module Mx2wire+ With LEDs, Dark Gray**Artikelno.: **MX-2wirePlus-Info1-EXT-DG****Description:**

Info module with Mx2wire+ technology and a second Mx2wire+ unit for mounting inside the building • To connect and supply power to the door station via existing two-wire cabling instead of a network cable • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: [www.mobotix.com](http://www.mobotix.com) > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Dark Gray

EAN:

**4047438015073**

HS:

**85176200**

Weight ( incl. packaging):

**626 g**

Dimensions (l/w/h) in cm:

**19,6 / 14,8 / 9,0****Info Module Mx2wire+ With LEDs, Black**Artikelno.: **MX-2wirePlus-Info1-EXT-BL****Description:**

Info module with Mx2wire+ technology and a second Mx2wire+ unit for mounting inside the building • To connect and supply power to the door station via existing two-wire cabling instead of a network cable • To attach the house number and/or name • With backlighting using energy-saving and long-lasting LED technology • Powered by the door camera via MxBus • Printing service free of charge: [www.mobotix.com](http://www.mobotix.com) > Support • Protection class IP65, -30 to 50°C / -22 to 122°F • Color: Black

EAN:

**4047438015066**

HS:

**85176200**

Weight ( incl. packaging):

**626 g**

Dimensions (l/w/h) in cm:

**19,6 / 14,8 / 9,0**

### DoorMaster For On-Wall Mounting

Artikelno.: **MX-Door2-INT-ON-PW**



#### Description:

Security Door Opener with integrated access code memory for on-wall mounting • Complete set including DoorMaster module, on-wall housing, three device frames, neutral housing covering, battery pack and mounting parts • Suitable for: IP Video Door Station with T2x and S1x as door camera • Built-in backup power supply (battery) for access modules • Doorbell • Direct connection and power supply for electric Door Opener und door sensors • Interface and power supply: MxBus • Two status LEDs, two function buttons, integrated • Speaker (doorbell) • Two galvanically separated inputs (AC/DC, selfpowered • up to 48 V) • Isolated relay output (AC/DC, 24 V/1 A) or port for standard door openers (6 to 12 V AC) • Outlet for MOBOTIX antitheft protection (12 V DC) • Protection class: IP20 • Ambient temperature: -5 to 40 °C / 23 to 104 °F • Color: white

EAN:

**4047438021876**

HS:

**85363010**

Weight ( incl. packaging):

**412 g**

Dimensions (l/w/h) in cm:

**14,8 / 9,8 / 9,0**

### DoorMaster For In-Wall Mounting

Artikelno.: **MX-Door2-INT-PW**



#### Description:

Security door opener with internal access code memory: A MOBOTIX door station may be coupled with the MOBOTIX MX-DoorMaster, making it impossible to open the door by forcibly removing the system and bypassing the connecting cable • 2nd product generation, suitable for: IP video door stations with an T2x and S1x as door camera • Integrated (rechargeable) battery power supply for access modules • Security door opener/bell with access code storage (protected against manipulation) • Connection for door opener, door sensor and door lock sensor • Interface and power supply: MxBus (max. 50 m distance to door station) • User interfaces: 2 status LEDs, 2 function buttons, integrated speaker (doorbell) • Inputs: 2 galvanically separated inputs with shared ground connection (AC/DC, self-powered up to 48 V) • Outputs: 1 isolated relay output (AC/DC, 24 V/1 A) or 1 connector for standard door opener (6 to 12 V AC), 1 output for MOBOTIX theft protection (12 V DC) • Protection class: IP20 (DIN EN 60529) • Operating temperature: -5 to 40°C / 23 to 104°F (DIN EN 50155) • Switch time: max. 5 s

EAN:

**4047438019934**

HS:

**85363010**

Weight ( incl. packaging):

**314 g**

Dimensions (l/w/h) in cm:

**14,8 / 9,8 / 9,0**

**Single Frame, White**

Artikelno.: **MX-OPT-Frame-1-EXT-PW**



**Description:**

Suitable for: 1 module, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 143 x 18 mm (W x H x D) • Color: White

EAN:  
**4047438014892**

HS:  
**90079100**

Weight (incl. packaging):  
**268 g**

Dimensions (l/w/h) in cm:  
**13,5 / 14,5 / 5,5**

**Single Frame, Silver**

Artikelno.: **MX-OPT-Frame-1-EXT-SV**



**Description:**

Suitable for: 1 module, outdoors • Integrated electromagnetic anti-theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 143 x 18 mm (W x H x D) • Color: Silver

EAN:  
**4047438014939**

HS:  
**90079100**

Weight (incl. packaging):  
**268 g**

Dimensions (l/w/h) in cm:  
**13,5 / 14,5 / 5,5**

**Single Frame, Dark Gray**

Artikelno.: **MX-OPT-Frame-1-EXT-DG**



**Description:**

Suitable for: 1 module, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 143 x 18 mm (W x H x D) • Color: Dark Gray

EAN:  
**4047438014922**

HS:  
**90079100**

Weight (incl. packaging):  
**268 g**

Dimensions (l/w/h) in cm:  
**13,5 / 14,5 / 5,5**

**Single Frame, Black**

Artikelno.: **MX-OPT-Frame-1-EXT-BL**



**Description:**

Suitable for: 1 module, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 143 x 18 mm (W x H x D) • Color: Black

EAN:  
**4047438014915**

HS:  
**90079100**

Weight (incl. packaging):  
**268 g**

Dimensions (l/w/h) in cm:  
**13,5 / 14,5 / 5,5**

**Single On-Wall-Housing, White**

Artikelno.: **MX-OPT-Box-1-EXT-ON-PW**



**Description:**

Suitable for: 1 module, outdoors • Metal-reinforced housing: 126 x 138 x 31 mm (W x H x D) • Color: White

EAN:  
**4047438015202**

HS:  
**90079100**

Weight (incl. packaging):  
**286 g**

Dimensions (l/w/h) in cm:  
**14,5 / 13,5 / 3,5**

**Single On-Wall-Housing, Silver**

Artikelno.: **MX-OPT-Box-1-EXT-ON-SV**



**Description:**

Suitable for: 1 module, outdoors • Metal-reinforced housing: 126 x 138 x 31 mm (W x H x D) • Color: Silver

EAN:  
**4047438015240**

HS:  
**90079100**

Weight (incl. packaging):  
**286 g**

Dimensions (l/w/h) in cm:  
**14,5 / 13,5 / 3,5**

**Single On-Wall-Housing, Dark Gray**

Artikelno.: **MX-OPT-Box-1-EXT-ON-DG**



**Description:**

Suitable for: 1 module, outdoors • Metal-reinforced housing: 126 x 138 x 31 mm (W x H x D) • Color: Dark Gray

EAN:

**4047438015233**

HS:

**90079100**

Weight ( incl. packaging):

**286 g**

Dimensions (l/w/h) in cm:

**14,5 / 13,5 / 5,0**

**Single On-Wall-Housing, Black**

Artikelno.: **MX-OPT-Box-1-EXT-ON-BL**



**Description:**

Suitable for: 1 module, outdoors • Metal-reinforced housing: 126 x 138 x 31 mm (W x H x D) • Color: Black

EAN:

**4047438015226**

HS:

**90079100**

Weight ( incl. packaging):

**286 g**

Dimensions (l/w/h) in cm:

**14,5 / 13,5 / 3,5**

**Single In-Wall-Housing**

Artikelno.: **MX-OPT-Box-1-EXT-IN**



**Description:**

Suitable for: 1 module, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 129 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm

EAN:

**4047438015271**

HS:

**90079100**

Weight ( incl. packaging):

**186 g**

Dimensions (l/w/h) in cm:

**14,5 / 13,5 / 3,5**

**Double Frame, White**

Artikelno.: **MX-OPT-Frame-2-EXT-PW**



**Description:**

Suitable for: 2 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: White

EAN:

**4047438014847**

HS:

**90079100**

Weight ( incl. packaging):

**333 g**

Dimensions (l/w/h) in cm:

**23,5 / 13,5 / 3,5**

**Double Frame, Silver**

Artikelno.: **MX-OPT-Frame-2-EXT-SV**



**Description:**

Suitable for: 2 modules, outdoors • Integrated electromagnetic anti-theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: Silver

EAN:

**4047438014885**

HS:

**90079100**

Weight ( incl. packaging):

**333 g**

Dimensions (l/w/h) in cm:

**23,5 / 13,5 / 3,5**

**Double Frame, Dark Gray**

Artikelno.: **MX-OPT-Frame-2-EXT-DG**



**Description:**

Suitable for: 2 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: Dark Gray

EAN:

**4047438014878**

HS:

**90079100**

Weight ( incl. packaging):

**333 g**

Dimensions (l/w/h) in cm:

**23,5 / 13,5 / 5,0**

**Double Frame, Black**

Artikelno.: **MX-OPT-Frame-2-EXT-BL**



**Description:**

Suitable for: 2 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: Black

EAN:  
**4047438014861**

HS:  
**90079100**

Weight ( incl. packaging):  
**333 g**

Dimensions (l/w/h) in cm:  
**23,5 / 13,5 / 3,5**

**Double On-Wall-Housing, White**

Artikelno.: **MX-OPT-Box-2-EXT-ON-PW**



**Description:**

Suitable for: 2 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: White

EAN:  
**4047438015158**

HS:  
**90079100**

Weight ( incl. packaging):  
**430 g**

Dimensions (l/w/h) in cm:  
**23,5 / 13,5 / 3,5**

**Double On-Wall-Housing, Silver**

Artikelno.: **MX-OPT-Box-2-EXT-ON-SV**



**Description:**

Suitable for: 2 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Silver

EAN:  
**4047438015196**

HS:  
**90079100**

Weight ( incl. packaging):  
**430 g**

Dimensions (l/w/h) in cm:  
**23,5 / 13,5 / 3,5**

**Double On-Wall-Housing, Dark Gray**

Artikelno.: **MX-OPT-Box-2-EXT-ON-DG**



**Description:**

Suitable for: 2 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Dark Gray

EAN:  
**4047438015189**

HS:  
**90079100**

Weight ( incl. packaging):  
**430 g**

Dimensions (l/w/h) in cm:  
**23,5 / 13,5 / 3,0**

**Double On-Wall-Housing, Black**

Artikelno.: **MX-OPT-Box-2-EXT-ON-BL**



**Description:**

Suitable for: 2 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Black

EAN:  
**4047438015172**

HS:  
**90079100**

Weight ( incl. packaging):  
**430 g**

Dimensions (l/w/h) in cm:  
**23,5 / 13,5 / 3,5**

**Double In-Wall-Housing**

Artikelno.: **MX-OPT-Box-2-EXT-IN**



**Description:**

Suitable for: 2 modules, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 218 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm

EAN:  
**4047438015264**

HS:  
**90079100**

Weight ( incl. packaging):  
**270 g**

Dimensions (l/w/h) in cm:  
**23,5 / 13,5 / 3,5**

**Triple Frame, White**

Artikelno.: **MX-OPT-Frame-3-EXT-PW**



**Description:**

Suitable for: 3 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: White

EAN:

**4047438014793**

HS:

**90079100**

Weight ( incl. packaging):

**426 g**

Dimensions (l/w/h) in cm:

**33,5 / 13,5 / 5,5**

**Triple Frame, Silver**

Artikelno.: **MX-OPT-Frame-3-EXT-SV**



**Description:**

Suitable for: 3 modules, outdoors • Integrated electromagnetic anti-theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: Silver

EAN:

**4047438014830**

HS:

**90079100**

Weight ( incl. packaging):

**426 g**

Dimensions (l/w/h) in cm:

**33,5 / 13,5 / 5,5**

**Triple Frame, Dark Gray**

Artikelno.: **MX-OPT-Frame-3-EXT-DG**



**Description:**

Suitable for: 3 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: Dark Gray

EAN:

**4047438014823**

HS:

**90079100**

Weight ( incl. packaging):

**426 g**

Dimensions (l/w/h) in cm:

**33,5 / 13,5 / 5,0**

**Triple Frame, Black**

Artikelno.: **MX-OPT-Frame-3-EXT-BL**



**Description:**

Suitable for: 3 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 131 x 233 x 18 mm (W x H x D) • Color: Black

EAN:

**4047438014816**

HS:

**90079100**

Weight ( incl. packaging):

**426 g**

Dimensions (l/w/h) in cm:

**33,5 / 13,5 / 5,5**

**Triple On-Wall-Housing, White**

Artikelno.: **MX-OPT-Box-3-EXT-ON-PW**



**Description:**

Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: White

EAN:

**4047438015103**

HS:

**90079100**

Weight ( incl. packaging):

**574 g**

Dimensions (l/w/h) in cm:

**33,5 / 13,5 / 3,5**

**Triple On-Wall-Housing, Silver**

Artikelno.: **MX-OPT-Box-3-EXT-ON-SV**



**Description:**

Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Silver

EAN:

**4047438015141**

HS:

**90079100**

Weight ( incl. packaging):

**574 g**

Dimensions (l/w/h) in cm:

**33,5 / 13,5 / 3,5**



**Triple On-Wall-Housing, Dark Gray**

Artikelno.: **MX-OPT-Box-3-EXT-ON-DG**



**Description:**

Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Dark Gray

EAN:

**4047438015134**

HS:

**90079100**

Weight ( incl. packaging):

**574 g**

Dimensions (l/w/h) in cm:

**33,5 / 13,5 / 3,0**

**Triple On-Wall-Housing, Black**

Artikelno.: **MX-OPT-Box-3-EXT-ON-BL**



**Description:**

Suitable for: 3 modules, outdoors • Metal-reinforced housing: 126 x 327 x 31 mm (W x H x D) • Color: Black

EAN:

**4047438015127**

HS:

**90079100**

Weight ( incl. packaging):

**574 g**

Dimensions (l/w/h) in cm:

**33,5 / 13,5 / 3,5**

**Triple In-Wall-Housing**

Artikelno.: **MX-OPT-Box-3-EXT-IN**



**Description:**

Suitable for: 3 modules, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 117 x 318 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm

EAN:

**4047438015257**

HS:

**90079100**

Weight ( incl. packaging):

**362 g**

Dimensions (l/w/h) in cm:

**33,5 / 13,5 / 3,5**

**Quad Frame, White**

Artikelno.: **MX-OPT-Frame-4-EXT-PW**



**Description:**

Suitable for: 4 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 233 x 233 x 18 mm (W x H x D) • Color: White

EAN:

**4047438017398**

HS:

**90079100**

Weight ( incl. packaging):

**516 g**

Dimensions (l/w/h) in cm:

**25,0 / 25,0 / 5,5**

**Quad Frame, Silver**

Artikelno.: **MX-OPT-Frame-4-EXT-SV**



**Description:**

Suitable for: 4 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 233 x 233 x 18 mm (W x H x D) • Color: Silver

EAN:

**4047438017435**

HS:

**90079100**

Weight ( incl. packaging):

**516 g**

Dimensions (l/w/h) in cm:

**25,0 / 25,0 / 5,5**

**Quad Frame, Dark Gray**

Artikelno.: **MX-OPT-Frame-4-EXT-DG**



**Description:**

Suitable for: 4 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 233 x 233 x 18 mm (W x H x D) • Color: Dark Gray

EAN:

**4047438017428**

HS:

**90079100**

Weight ( incl. packaging):

**516 g**

Dimensions (l/w/h) in cm:

**25,0 / 25,0 / 5,5**

**Quad Frame, Black**

Artikelno.: **MX-OPT-Frame-4-EXT-BL**



**Description:**

Suitable for: 4 modules, outdoors • Integrated electromagnetic theft protection • Includes special key for module unlocking, housing gasket and installation material • Dimensions: 233 x 233 x 18 mm (W x H x D) • Color: Black

EAN:

**4047438017411**

HS:

**90079100**

Weight ( incl. packaging):

**516 g**

Dimensions (l/w/h) in cm:

**25,0 / 25,0 / 5,5**

**Quad On-Wall-Housing, White**

Artikelno.: **MX-OPT-Box-4-EXT-ON-PW**



**Description:**

Suitable for: 4 modules, outdoors • Metal-reinforced housing: 227 x 227 x 31 mm (W x H x D) • Color: White

EAN:

**4047438017442**

HS:

**90079100**

Weight ( incl. packaging):

**620 g**

Dimensions (l/w/h) in cm:

**25,0 / 25,0 / 3,3**

**Quad On-Wall-Housing, Silver**

Artikelno.: **MX-OPT-Box-4-EXT-ON-SV**



**Description:**

Suitable for: 4 modules, outdoors • Metal-reinforced housing: 227 x 227 x 31 mm (W x H x D) • Color: Silver

EAN:

**4047438017480**

HS:

**90079100**

Weight ( incl. packaging):

**620 g**

Dimensions (l/w/h) in cm:

**25,0 / 25,0 / 3,3**

**Quad On-Wall-Housing, Dark Gray**

Artikelno.: **MX-OPT-Box-4-EXT-ON-DG**



**Description:**

Suitable for: 4 modules, outdoors • Metal-reinforced housing: 227 x 227 x 31 mm (W x H x D) • Color: Dark Gray

EAN:

**4047438017473**

HS:

**90079100**

Weight ( incl. packaging):

**620 g**

Dimensions (l/w/h) in cm:

**25,0 / 25,0 / 5,5**

**Quad On-Wall-Housing, Black**

Artikelno.: **MX-OPT-Box-4-EXT-ON-BL**



**Description:**

Suitable for: 4 modules, outdoors • Metal-reinforced housing: 227 x 227 x 31 mm (W x H x D) • Color: Black

EAN:

**4047438017466**

HS:

**90079100**

Weight ( incl. packaging):


**620 g**

Dimensions (l/w/h) in cm:

**25,0 / 25,0 / 3,3**

**Quad In-Wall-Housing**

Artikelno.: **MX-OPT-Box-4-EXT-IN**



**Description:**

Suitable for: 4 modules, outdoors • The blue housing is firmly connected to the subsurface or brick work. It can also be used to ensure easy installation in cavities: Drill opening, position housing and screw tightly in place; the retaining wings, which automatically swing out, secure the housing, while the plastic bars at the edge of the housing prevent it from sliding into the cavity. • Required flushmounting opening: 218 x 218 mm (width x height) • Permissible wall thickness for cavity installation: 7 to 27 mm

EAN:

**4047438017497**

HS:

**90079100**

Weight ( incl. packaging):

**434 g**

Dimensions (l/w/h) in cm:

**25,0 / 25,0 / 3,3**

**FlatMount Frame, white**

Artikelno.: **MX-OPT-FlatMount-EXT-PW**



**Description:**

For flush-mounting of MxDisplay and door station modules in wall cavities • Integrated electromagnetic theft protection • W x H: 124 x 124 mm • Color: white

EAN:  
**4047438019811**

HS:  
**90079100**

Weight (incl. packaging):  
**190 g**

Dimensions (l/w/h) in cm:  
**14,7 / 13,7 / 5,5**

**FlatMount Frame, black**

Artikelno.: **MX-OPT-FlatMount-EXT-BL**



**Description:**

For flush-mounting of MxDisplay and door station modules in wall cavities • Integrated electromagnetic theft protection • W x H: 124 x 124 mm • Color: black

EAN:  
**4047438019835**

HS:  
**90079100**

Weight (incl. packaging):  
**190 g**

Dimensions (l/w/h) in cm:  
**14,7 / 13,7 / 5,5**

**FlatMount Frame In-Wall Housing**

Artikelno.: **MX-OPT-FlatMount-Box-EXT-IN**



**Description:**

In-wall housing for FlatMount Frame • To be affixed securely with the subsurface or brick work • Size of cavity for flush-mounting (W x H x D): 112 x 112 x 60 mm

EAN:  
**4047438019866**

HS:  
**90079100**

Weight (incl. packaging):  
**130 g**

Dimensions (l/w/h) in cm:  
**13,8 / 6,5 / 13,8**

### Admin RFID Transponder Card (Red)

Artikelno.: **MX-AdminCard1**



**Description:**

For system configuration IP Video Door Station via KeypadRFID and BellRFID • Type/encryption: MIFARE DESFire EV1 3K3DES/AES

EAN:  
**4047438015288**

HS:  
**85235200**

Weight ( incl. packaging):  
**2 g**

Dimensions (l/w/h) in cm:  
**8,5 / 5,5 / 0,1**

### User RFID Transponder Card (Blue)

Artikelno.: **MX-UserCard1**



**Description:**

For keyless entry via with KeypadRFID or BellRFID (IP video door station) • Type/encryption: MIFARE DESFire EV1 3K3DES/AES

EAN:  
**4047438015295**

HS:  
**85235200**

Weight ( incl. packaging):  
**2 g**

Dimensions (l/w/h) in cm:  
**8,5 / 5,5 / 0,1**

### Extended Terminal Board (IO Module)

Artikelno.: **MX-OPT-IO1**



**Description:**

Suitable for: T2x, delivers extended connection options for the door station (e.g., doorbell buttons, light, garage door opener, etc.) • Connect the IO Module to the camera module via MxBus, which connects it to the network. It has eight physical signal inputs that allow it to distinguish in AC operation between a pending full-wave and half-wave. This makes it possible to connect two switches to each signal input terminal so that 16 button inputs are made available. The inputs can be used for, e.g., bell buttons. The outputs can be used for external devices such as a doorbell, or for outdoor lights or garage door openers (via a power relay).

EAN:  
**4047438013307**

HS:  
**85299065**

Weight ( incl. packaging):  
**86 g**

Dimensions (l/w/h) in cm:  
**10,7 / 5,2 / 8,7**

### Ethernet Terminal Board

Artikelno.: **MX-OPT-IO2**



**Description:**

Suitable for: T2x • The Ethernet terminal board is used to connect the door station for the versions without Mx2wire+ technology. It securely connects the camera module with the 8 connected wires of the network patch cable via RJ45 connector. The Ethernet terminal board is screwed on to the housing (on-wall or in-wall) behind the camera module

EAN:  
**4047438014786**

HS:  
**85299065**

Weight ( incl. packaging):  
**58 g**

Dimensions (l/w/h) in cm:  
**10,7 / 5,2 / 8,7**





Lens Type	B016 Fisheye	B036 Ultra Wide	B041 Super Wide	B061 Wide	B079 Standard	B119 Tele	B237 Distant	B500 Super Tele	B045-100 CS Vario
Image angle(horizontal)									
Focal length	1.6 mm	3.6 mm	4.1 mm	6.1 mm	7.9 mm	11.9 mm	23.7 mm	50 mm	4.5 - 10 mm
35 mm equivalent	10 mm	20 mm	22 mm	32 mm	43 mm	65 mm	135 mm	270 mm	24 - 54 mm
Aperture f/	2.0	1.8	1.8	1.8	1.8	1.8	1.8	2.5	1.6 - 2.3
Image angle (horiz. x vertical)	180° x 180°	103° x 77°	90° x 67°	60° x 45°	45° x 34°	31° x 23°	15° x 11°	8° x 6°	39°-89° x 29°-65°

Outdoor Single Lens		Day	Night	Day	Night	Day	Night	Day	Night	Day	Night	Day	Night	Day	Night	Day	Night
	D25/26	-	-	●	●	●	●	●	●	●	●	●	●	●	●	-	-
	M25/26	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Q25/26	●	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	S15M/26	●	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Outdoor Dual Lens		Day	Night	Day	Night	Day	Night	Day	Night	Day	Night	Day	Night	Day	Night	Day	Night	Day	Night
	D15/16 Fix	--	--	●	●	●	●	●	●	●	●	●	●	●	●	Two parallel aligned sensors			
	D15/16 Pano	--	--	--	--	●	●	Two lenses B041 installed											
	D15/16 Day/Night	--	--	● & ●	● & ●	● & ●	● & ●	● & ●	● & ●	● & ●	● & ●	● & ●	● & ●	--	--	--	--		
	M15/16	● & ●	● & ●	● & ●	● & ●	● & ●	● & ●	● & ●	● & ●	● & ●	● & ●	● & ●	● & ●	● & ●	● & ●	● & ●	● & ●		
	S15/16 Set 1	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
	S15/16 Set 2	● & ●	-	● & ●	-	-	-	-	-	-	-	-	-	-	-	-	-		
	S15/16 Set 3	● & ●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		

Indoor Single Lens		Day	Night	Day	Night	Day	Night	Day	Night	Day	Night	Day	Night	Day	Night	Day	Night
	i25/26	●	●	●	●	-	-	-	-	-	-	-	-	-	-	-	-
	i25/26 Audio	●	●	●	●	-	-	-	-	-	-	-	-	-	-	-	-
	c25/26	●	●	●	●	-	-	-	-	-	-	-	-	-	-	-	-
	c25/26 Audio	●	●	●	●	-	-	-	-	-	-	-	-	-	-	-	-
	p25/26	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	p25/26 Audio	●	●	●	●	-	-	-	-	-	-	-	-	-	-	-	-
	v25/26	-	-	●	●	●	●	●	●	●	●	●	●	●	●	-	-



Lens Type	B016 Fisheye	B036 Ultra Wide	B041 Super Wide	B061 Wide	B079 Standard	B119 Tele	B237 Distant	B500 Super Tele	B045-100 CS Vario
-----------	-----------------	--------------------	--------------------	--------------	------------------	--------------	-----------------	--------------------	----------------------

Home Automation		Day	Night	Day	Night	Day	Night	Day	Night	Day	Night	Day	Night	Day	Night	Day	Night
	T25	●	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	T25 Set 1, 2, 3	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	T25 SmartAccess 1, 2	●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

Thermal Cameras		L43 B079	L65 B119	L135 B237
	M15/16 Thermal	●	●	●
	M15/16 Thermal TR			
	S15/16 Thermal	●	●	●
	S15/16 Thermal TR			
	PTMount Thermal	●	●	●
	PTMount TR			

**PLEASE NOTE – Special Export Regulations For Thermographic Cameras**

Cameras with thermographic image sensors ("thermographic cameras") are subject to special U.S. and ITAR (International Traffic in Arms Regulation) export regulations.

Visit [www.mobotix.com](http://www.mobotix.com) > Products > Thermographic Cameras for further information.

EN\_07/17

**MOBOTIX AG**

Kaiserstrasse  
D-67722 Langmeil  
Tel.: +49 6302 9816-103  
Fax: +49 6302 9816-190  
sales@mobotix.com  
www.mobotix.com

Distributed by:

